

In the Matter of the
Establishment of a Water District in the Town of
Lima, Livingston County, New York, to be known
as the “Town of Lima Water District No. 5.”

**RESOLUTION #7 of 2025
TO ESTABLISH
DISTRICT**
(Pursuant to Town Law
§209-e)

WHEREAS, it is the intent of the Town of Lima to create the Town of Lima Water District No. 5., to include all of the real property indicated in the map, plan and report prepared by Clark Patterson Lee, dated January, 2025 and being styled “Final Map, Plan and Report for the Town of Lima Water District No. 5.” (hereafter “Map, Plan and Report”), said real property being located in the Town of Lima, County of Livingston and State of New York; and

WHEREAS, the real property that will be included in the district is more particularly described in said Map, Plan and Report filed in the Lima Town Clerk’s Office and as being described in Schedule “A” attached hereto and made a part hereof; and

WHEREAS, the Town of Lima Town Board (hereafter “Town Board”), by resolution adopted on October 1, 2024, pursuant to New York State Town Law §209-b, directed the Town Engineer to prepare a map, plan and report with respect to the proposed district formation; and

WHEREAS, the Town Board therein directed that the charges incurred for the preliminary map, plan and report shall be a Town charge until such time as the district formation shall take place, at which time they shall become a district charge; and

WHEREAS, the above referenced resolution authorizing the preparation of the Map, Plan and Report was adopted subject to permissive referendum as required by New York State Town Law §209-b, and pursuant to New York State Town Law §90, a Public Notice of Resolution Adopted Subject to Permissive Referendum was subsequently published in the official newspaper of the Town of Lima within ten (10) days of the adoption of such resolution, said notice having appeared in The Mendon-Honeoye Falls-Lima Sentinel on October 10, 2024; and

WHEREAS, on November 12, 2024, the Town Clerk of the Town of Lima certified that no petitions meeting the requirements of New York State Town Law §91 and New York State Election Law §6-140(1)(a), seeking a permissive referendum with regard to the published notice, were filed within thirty (30) days after the adoption of such resolution; and

WHEREAS, on January 7, 2025, the Town Board adopted a resolution accepting the Map, Plan and Report; and

WHEREAS, the Map, Plan and Report was subsequently filed in the office of the Lima Town Clerk on January 8, 2025; and

WHEREAS, the Town Board on January 9, 2025 adopted a Resolution and Order pursuant to Town Law §209-d, directing that a public hearing be held on February 11, 2025, to receive public comment relating to the possible adoption of a resolution to establish the Town of Lima Water District No. 5.; and

WHEREAS, the notice of public hearing was properly posted and published pursuant to New York State Town Law §209-d, appearing in the Town's official newspaper (The Mendon-Honeoye Falls-Lima Sentinel) on January 30, 2025; and

WHEREAS, the notice of public hearing contained all necessary information to comply with New York State Town Law §209-d; and

WHEREAS, a public hearing having been held on the 11th day of February, 2025, at 6:30 P.M. at the Lima Town Hall located at 7329 East Main Street, Lima, New York, with respect to the creation of the Town of Lima Water District No. 5, to include the property noted in the Map, Plan and Report and as more particularly described in the Map, Plan and Report on file at the Lima Town Clerk's Office, in the Town of Lima, County of Livingston and State of New York; and

WHEREAS, a copy of the Map, Plan and Report describing the proposed district boundaries, the improvements to be constructed therein and a detailed explanation of the estimated cost of hook-up fees and the cost to the typical property, as well as the boundaries of the entire Town of Lima Water District No. 5, was available for the public inspection at the Lima Town Clerk's Office prior to and at the public hearing referenced above and is attached hereto and made a part hereof; and

WHEREAS, the Board having previously complied with the relevant provisions of SEQR; and

WHEREAS, the Board having given due consideration to the testimony and evidence given at the public hearing conducted on February 11, 2025; and

WHEREAS, the Map, Plan and Report calls for the installation of approximately 86,810 linear feet of 8-inch and 12-inch water main, fire hydrants, gate valves and water services. The water main will be installed along portions of Poplar Hill Road, Woodruff Road, Briggs Road, Doran Road, Jenks Road, Chase Road, Pond Road, Gleason Road, York Street, Corby Road, Dalton Road, Heath Markham Road and Egan Road and will provide water supply to approximately 201 residential and commercial properties. There are an additional 47 properties that will not be provided with service, as they are vacant; and

WHEREAS, that the maximum amount proposed to be expended for the improvements above is \$15,260,000.00, of which \$5,951,400.00 is anticipated to come from a USDA-Rural Development grant, \$5,000,000.00 is anticipated to come from a NYS EFC WIIA grant and \$4,308,600.00 will be financed through a low interest USDA-Rural Development loan; and

WHEREAS, the anticipated annual cost to the typical property located within the Town of Lima Water District No. 5 shall be on a benefit basis and is estimated to be \$1,076.00; and

WHEREAS, that the estimated one-time costs for hook-up fees are \$3,750.00 for the typical property, including installation of a service line at the costs of approximately \$30.00 per linear foot (\$3,000.00 average), \$250.00 LCWSA permitting/inspection fee and \$500.00 for well isolation and interior plumbing modifications; and

WHEREAS, adoption of this Resolution and Order shall be subject to permissive referendum pursuant to Article 12A and Article 7 of the New York State Town Law; and

WHEREAS, because the anticipated cost to the typical property located within the Town of Lima Water District No. 5 is estimated to be at or below that of the cost computed by the New York State Comptroller for the establishment of similar types of districts, the formation of the Town of Lima Water District No. 5 will not require approval of the New York State Comptroller's Office.

NOW THEREFORE, be it

RESOLVED and ORDERED by the Town Board of the Town of Lima as follows:

1. That the notice of public hearing for the February 11, 2025 public hearing was published and posted as required by law and was otherwise sufficient;
2. That all of the property and property owners within the proposed Town of Lima Water District No. 5 are benefited thereby;
3. That all of the property and property owners benefited by the Town of Lima Water District No. 5 are included within the limits of the proposed district; and
4. That it is in the public interest to form the Town of Lima Water District No. 5 as set forth; and it is further

RESOLVED and ORDERED, that subject to permissive referendum pursuant to Article 12A and Article 7 of the New York State Town Law, the Town Board of the Town of Lima does hereby establish the Town of Lima Water District No. 5 as set forth in the Map, Plan and Report and as described on Schedule "A" attached hereto; and it is further

RESOLVED and ORDERED, that subject to permissive referendum pursuant to Article 12A and Article 7 of the New York State Town Law, the Town Board of the Town of Lima does hereby approve the installation of approximately 86,810 linear feet of 8-inch and 12-inch water main, fire hydrants, gate valves and water services. The water main will be installed along portions of Poplar Hill Road, Woodruff Road, Briggs Road, Doran Road, Jenks Road, Chase Road, Pond Road, Gleason Road, York Street, Corby Road, Dalton Road, Heath Markham Road and Egan Road and will provide water supply to approximately 201 residential and commercial properties, with the maximum amount proposed to be expended for the improvements above is \$15,260,000.00, of which \$5,951,400.00 is anticipated to come from a USDA-Rural Development grant, \$5,000,000.00 is anticipated to come from a NYS EFC WIIA grant and

\$4,308,600.00 will be financed through a low interest USDA-Rural Development loan, and with the anticipated cost to the typical property located within the Town of Lima Central Lima Water District to be on a benefit basis and be \$1,076.00 (which includes debt services and water usage charges) per equivalent dwelling unit; and it is further

RESOLVED and ORDERED, that within ten (10) days after the adoption of this Resolution, the Town Clerk is directed to publish a Notice that this resolution was adopted subject to permissive referendum as required by New York State Town Law §90.

The question of the adoption of the foregoing Resolution was duly submitted for approval by vote of the Lima Town Board on March 4, 2025, recorded as follows:

VOTE OF THE BOARD:

The vote duly taken resulted as follows:

Michael J. Falk, Supervisor	Aye
Mark Petroski, Deputy Supervisor	Aye
Bill Carey	Aye
Steve Werner	Nay
Ron Blodgett	Nay

This is to certify that I, the undersigned, Clerk of the Town Board of the Town of Lima, Livingston Count, New York, was duly adopted by the Town Board of said Town on the date above, and that the same is a true and correct transcript of said resolution.

In witness where of I have hereunto set my hand and the official seal of the Town Clerk this 4th day of March, 2025.

Jennifer A. Heim – CMC, RMC - Town Clerk

**SCHEDULE A
TOWN OF LIMA**

PROPOSED TOWN OF LIMA WATER DISTRICT NO. 5

**TOWN OF LIMA
WATER DISTRICT NO. 5**

All that tract or parcel of land situate in the Town of Lima, County of Livingston, State of New York, being described as follows:

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1070575.0980' and whose Easting is 1407673.7616'; thence,

1. Bearing S 76° 38' 20" W for a distance of 137.05 feet, more or less, to a point; thence,
2. Bearing S 76° 38' 20" W for a distance of 67.09 feet, more or less, to a point; thence,
3. Bearing S 74° 38' 10" W for a distance of 173.88 feet, more or less, to a point; thence,
4. Bearing S 72° 48' 44" W for a distance of 106.73 feet, more or less, to a point; thence,
5. Bearing S 01° 00' 04" W for a distance of 26.42 feet, more or less, to a point; thence,
6. Bearing S 01° 00' 03" W for a distance of 400.84 feet, more or less, to a point; thence,
7. Bearing S 01° 18' 07" W for a distance of 1080.42 feet, more or less, to a point; thence,
8. Bearing S 90° 00' 00" W for a distance of 233.93 feet, more or less, to a point; thence,
9. Bearing S 89° 52' 18" W for a distance of 411.56 feet, more or less, to a point; thence,
10. Bearing S 00° 40' 18" E for a distance of 323.95 feet, more or less, to a point; thence,
11. Bearing S 00° 33' 05" E for a distance of 192.76 feet, more or less, to a point; thence,
12. Bearing S 00° 41' 58" E for a distance of 151.99 feet, more or less, to a point; thence,
13. Bearing S 00° 29' 10" W for a distance of 218.70 feet, more or less, to a point; thence,
14. Bearing S 01° 12' 35" E for a distance of 179.50 feet, more or less, to a point; thence,
15. Bearing S 02° 19' 25" E for a distance of 137.26 feet, more or less, to a point; thence,
16. Bearing S 00° 44' 41" E for a distance of 142.72 feet, more or less, to a point; thence,
17. Bearing S 89° 35' 18" W for a distance of 102.29 feet, more or less, to a point; thence,
18. Bearing S 35° 52' 10" W for a distance of 478.00 feet, more or less, to a point; thence,
19. Bearing S 25° 26' 44" W for a distance of 22.89 feet, more or less, to a point; thence,

20. Bearing S 25° 26' 39" W for a distance of 102.31 feet, more or less, to a point; thence,
21. Bearing S 15° 45' 09" W for a distance of 282.18 feet, more or less, to a point; thence,
22. Bearing S 01° 00' 07" W for a distance of 353.32 feet, more or less, to a point; thence,
23. Bearing S 88° 57' 08" E for a distance of 124.77 feet, more or less, to a point; thence,
24. Bearing S 88° 52' 24" E for a distance of 123.99 feet, more or less, to a point; thence,
25. Bearing S 00° 07' 49" E for a distance of 204.68 feet, more or less, to a point; thence,
26. Bearing S 00° 00' 00" W for a distance of 71.73 feet, more or less, to a point; thence,
27. Bearing S 00° 21' 20" E for a distance of 199.12 feet, more or less, to a point; thence,
28. Bearing S 00° 49' 22" E for a distance of 201.70 feet, more or less, to a point; thence,
29. Bearing N 88° 40' 14" W for a distance of 488.78 feet, more or less, to a point; thence,
30. Bearing S 12° 54' 31" E for a distance of 389.68 feet, more or less, to a point; thence,
31. Bearing S 71° 05' 00" W for a distance of 119.00 feet, more or less, to a point; thence,
32. Bearing S 87° 39' 07" W for a distance of 106.01 feet, more or less, to a point; thence,
33. Bearing S 00° 12' 05" E for a distance of 72.77 feet, more or less, to a point; thence,
34. Bearing N 88° 52' 17" W for a distance of 745.88 feet, more or less, to a point; thence,
35. Bearing N 88° 46' 08" W for a distance of 453.19 feet, more or less, to a point; thence,
36. Bearing N 88° 26' 07" W for a distance of 421.05 feet, more or less, to a point; thence,
37. Bearing N 88° 35' 23" W for a distance of 154.87 feet, more or less, to a point; thence,
38. Bearing S 00° 26' 10" W for a distance of 328.04 feet, more or less, to a point; thence,
39. Bearing S 89° 19' 13" W for a distance of 391.70 feet, more or less, to a point; thence,
40. Bearing N 00° 49' 18" E for a distance of 564.26 feet, more or less, to a point; thence,
41. Bearing N 00° 49' 18" E for a distance of 268.74 feet, more or less, to a point; thence,
42. Bearing S 89° 44' 59" W for a distance of 19.41 feet, more or less, to a point; thence,
43. Bearing S 89° 44' 59" W for a distance of 149.67 feet, more or less, to a point; thence,
44. Bearing S 89° 15' 41" W for a distance of 168.84 feet, more or less, to a point; thence,
45. Bearing N 00° 23' 09" E for a distance of 513.46 feet, more or less, to a point; thence,
46. Bearing S 88° 45' 52" W for a distance of 352.91 feet, more or less, to a point; thence,

47. Bearing N 01° 02' 24" W for a distance of 1081.10 feet, more or less, to a point; thence,
48. Bearing S 88° 47' 46" E for a distance of 2027.87 feet, more or less, to a point; thence,
49. Bearing N 00° 18' 35" E for a distance of 343.82 feet, more or less, to a point; thence,
50. Bearing N 00° 20' 07" E for a distance of 159.21 feet, more or less, to a point; thence,
51. Bearing N 64° 14' 50" E for a distance of 30.00 feet, more or less, to a point; thence,
52. Bearing N 00° 16' 30" E for a distance of 118.71 feet, more or less, to a point; thence,
53. Bearing N 00° 23' 44" W for a distance of 277.30 feet, more or less, to a point; thence,
54. Bearing N 00° 25' 22" W for a distance of 269.73 feet, more or less, to a point; thence,
55. Bearing N 00° 23' 21" W for a distance of 30.03 feet, more or less, to a point; thence,
56. Bearing N 89° 02' 11" E for a distance of 318.76 feet, more or less, to a point; thence,
57. Bearing N 00° 07' 25" E for a distance of 169.58 feet, more or less, to a point; thence,
58. Bearing N 00° 15' 42" W for a distance of 228.16 feet, more or less, to a point; thence,
59. Bearing N 00° 06' 20" E for a distance of 255.04 feet, more or less, to a point; thence,
60. Bearing N 00° 20' 41" E for a distance of 428.30 feet, more or less, to a point; thence,
61. Bearing N 00° 32' 40" E for a distance of 60.54 feet, more or less, to a point; thence,
62. Bearing N 00° 32' 40" E for a distance of 227.04 feet, more or less, to a point; thence,
63. Bearing N 02° 32' 51" E for a distance of 173.92 feet, more or less, to a point; thence,
64. Bearing N 01° 08' 39" E for a distance of 569.14 feet, more or less, to a point; thence,
65. Bearing N 00° 48' 36" E for a distance of 322.25 feet, more or less, to a point; thence,
66. Bearing S 78° 42' 44" W for a distance of 256.71 feet, more or less, to a point; thence,
67. Bearing N 00° 20' 25" W for a distance of 227.60 feet, more or less, to a point; thence,
68. Bearing N 83° 54' 30" W for a distance of 26.69 feet, more or less, to a point; thence,
69. Bearing N 01° 12' 25" W for a distance of 243.12 feet, more or less, to a point; thence,
70. Bearing N 00° 01' 51" W for a distance of 33.40 feet, more or less, to a point; thence,
71. Bearing N 01° 12' 53" W for a distance of 356.08 feet, more or less, to a point; thence,
72. Bearing S 89° 30' 27" E for a distance of 432.20 feet, more or less, to a point; thence,

73. Bearing S 89° 43' 55" E for a distance of 372.45 feet, more or less, to a point; thence,
74. Bearing S 01° 04' 30" W for a distance of 118.79 feet, more or less, to a point; thence,
75. Bearing S 00° 53' 19" W for a distance of 125.01 feet, more or less, to a point; thence,
76. Bearing N 88° 57' 46" E for a distance of 1359.48 feet, more or less, to a point; thence,
77. Bearing N 89° 13' 16" E for a distance of 600.91 feet, more or less, to a point; thence,
78. Bearing S 00° 44' 31" E for a distance of 148.43 feet, more or less, to a point; thence,
79. Bearing S 03° 30' 24" E for a distance of 43.77 feet, more or less, to a point; thence,
80. Bearing S 00° 00' 00" W for a distance of 13.37 feet, more or less, to a point; thence,
81. Bearing S 00° 18' 57" W for a distance of 92.67 feet, more or less, to a point; thence,
82. Bearing S 00° 46' 30" E for a distance of 302.26 feet, more or less, to a point; thence,
83. Bearing S 00° 05' 18" W for a distance of 210.69 feet, more or less, to a point; thence,
84. Bearing S 00° 10' 18" E for a distance of 245.35 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1070267.9902' and whose Easting is 1415285.3672'; thence,

1. Bearing S 85° 37' 21" E for a distance of 167.06 feet, more or less, to a point; thence,
2. Bearing S 85° 55' 36" E for a distance of 169.47 feet, more or less, to a point; thence,
3. Bearing S 05° 18' 56" W for a distance of 448.45 feet, more or less, to a point; thence,
4. Bearing N 89° 43' 22" W for a distance of 405.42 feet, more or less, to a point; thence,
5. Bearing S 88° 06' 41" W for a distance of 199.95 feet, more or less, to a point; thence,
6. Bearing S 01° 47' 27" W for a distance of 21.47 feet, more or less, to a point; thence,
7. Bearing S 00° 10' 04" W for a distance of 204.39 feet, more or less, to a point; thence,
8. Bearing S 00° 43' 17" E for a distance of 426.59 feet, more or less, to a point; thence,
9. Bearing S 89° 53' 21" W for a distance of 390.67 feet, more or less, to a point; thence,
10. Bearing S 89° 45' 18" W for a distance of 381.80 feet, more or less, to a point; thence,
11. Bearing S 00° 28' 58" W for a distance of 234.27 feet, more or less, to a point; thence,
12. Bearing S 00° 16' 15" W for a distance of 64.27 feet, more or less, to a point; thence,
13. Bearing S 89° 14' 35" W for a distance of 462.61 feet, more or less, to a point; thence,
14. Bearing S 00° 16' 19" E for a distance of 149.17 feet, more or less, to a point; thence,

15. Bearing S 55° 02' 06'' W for a distance of 996.35 feet, more or less, to a point; thence,
16. Bearing N 83° 49' 59'' W for a distance of 616.89 feet, more or less, to a point; thence,
17. Bearing N 04° 57' 44'' W for a distance of 956.96 feet, more or less, to a point; thence,
18. Bearing N 04° 44' 50'' W for a distance of 1328.84 feet, more or less, to a point; thence,
19. Bearing S 86° 06' 58'' E for a distance of 46.84 feet, more or less, to a point; thence,
20. Bearing S 86° 37' 10'' E for a distance of 387.07 feet, more or less, to a point; thence,
21. Bearing S 86° 14' 13'' E for a distance of 242.36 feet, more or less, to a point; thence,
22. Bearing N 00° 15' 46'' E for a distance of 349.19 feet, more or less, to a point; thence,
23. Bearing S 87° 28' 20'' E for a distance of 224.39 feet, more or less, to a point; thence,
24. Bearing S 87° 28' 20'' E for a distance of 306.68 feet, more or less, to a point; thence,
25. Bearing S 88° 20' 57'' E for a distance of 535.40 feet, more or less, to a point; thence,
26. Bearing N 00° 00' 00'' E for a distance of 77.13 feet, more or less, to a point; thence,
27. Bearing N 87° 23' 38'' E for a distance of 294.79 feet, more or less, to a point; thence,
28. Bearing N 13° 04' 56'' W for a distance of 289.09 feet, more or less, to a point; thence,
29. Bearing N 13° 00' 23'' W for a distance of 289.86 feet, more or less, to a point; thence,
30. Bearing N 88° 39' 19'' E for a distance of 227.73 feet, more or less, to a point; thence,
31. Bearing N 88° 41' 03'' E for a distance of 92.62 feet, more or less, to a point; thence,
32. Bearing S 88° 53' 18'' E for a distance of 109.64 feet, more or less, to a point; thence,
33. Bearing N 89° 20' 30'' E for a distance of 92.60 feet, more or less, to a point; thence,
34. Bearing N 90° 00' 00'' E for a distance of 103.23 feet, more or less, to a point; thence,
35. Bearing N 89° 32' 58'' E for a distance of 135.17 feet, more or less, to a point; thence,
36. Bearing N 90° 00' 00'' E for a distance of 106.43 feet, more or less, to a point; thence,
37. Bearing N 89° 21' 08'' E for a distance of 97.73 feet, more or less, to a point; thence,
38. Bearing N 90° 00' 00'' E for a distance of 104.30 feet, more or less, to a point; thence,
39. Bearing N 89° 29' 51'' E for a distance of 121.33 feet, more or less, to a point; thence,
40. Bearing N 88° 36' 16'' E for a distance of 87.30 feet, more or less, to a point; thence,
41. Bearing S 00° 54' 18'' W for a distance of 1123.27 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1049574.1632' and whose Easting is 1403626.4165'; thence,

1. Bearing S 05° 14' 44" W for a distance of 314.00 feet, more or less, to a point;
thence,
2. Bearing S 89° 42' 12" E for a distance of 701.87 feet, more or less, to a point;
thence,
3. Bearing S 01° 10' 48" W for a distance of 905.77 feet, more or less, to a point;
thence,
4. Bearing S 00° 42' 23" W for a distance of 1348.79 feet, more or less, to a point;
thence,
5. Bearing S 89° 49' 24" W for a distance of 1550.25 feet, more or less, to a point;
thence,
6. Bearing N 01° 29' 35" E for a distance of 2023.09 feet, more or less, to a point;
thence,
7. Bearing S 88° 19' 28" W for a distance of 125.42 feet, more or less, to a point;
thence,
8. Bearing S 89° 55' 13" W for a distance of 1281.75 feet, more or less, to a point;
thence,
9. Bearing S 37° 34' 36" W for a distance of 3.27 feet, more or less, to a point;
thence,
10. Bearing N 89° 34' 11" W for a distance of 1416.40 feet, more or less, to a point;
thence,
11. Bearing S 00° 23' 34" E for a distance of 424.99 feet, more or less, to a point;
thence,
12. Bearing S 00° 39' 20" E for a distance of 425.85 feet, more or less, to a point;
thence,
13. Bearing S 00° 24' 38" E for a distance of 677.56 feet, more or less, to a point;
thence,
14. Bearing S 00° 12' 48" E for a distance of 498.02 feet, more or less, to a point;
thence,
15. Bearing S 01° 51' 44" E for a distance of 133.55 feet, more or less, to a point;
thence,
16. Bearing S 00° 10' 41" W for a distance of 2088.54 feet, more or less, to a point;
thence,
17. Bearing S 88° 54' 00" W for a distance of 831.00 feet, more or less, to a point;
thence,
18. Bearing S 88° 37' 44" W for a distance of 264.98 feet, more or less, to a point;
thence,
19. Bearing S 89° 06' 19" W for a distance of 304.60 feet, more or less, to a point;
thence,
20. Bearing N 00° 08' 13" W for a distance of 647.31 feet, more or less, to a point;
thence,
21. Bearing N 00° 00' 00" E for a distance of 527.80 feet, more or less, to a point;
thence,
22. Bearing N 89° 53' 11" W for a distance of 183.53 feet, more or less, to a point;
thence,

23. Bearing N 89° 45' 20" W for a distance of 39.75 feet, more or less, to a point;
thence,
24. Bearing S 23° 58' 29" W for a distance of 397.61 feet, more or less, to a point;
thence,
25. Bearing S 23° 39' 01" W for a distance of 344.94 feet, more or less, to a point;
thence,
26. Bearing S 23° 52' 40" W for a distance of 260.83 feet, more or less, to a point;
thence,
27. Bearing S 23° 49' 06" W for a distance of 286.05 feet, more or less, to a point;
thence,
28. Bearing S 22° 35' 07" W for a distance of 269.68 feet, more or less, to a point;
thence,
29. Bearing S 19° 41' 52" W for a distance of 253.39 feet, more or less, to a point;
thence,
30. Bearing S 17° 53' 44" W for a distance of 9.31 feet, more or less, to a point;
thence,
31. Bearing N 89° 55' 02" W for a distance of 165.70 feet, more or less, to a point;
thence,
32. Bearing S 01° 14' 56" E for a distance of 279.83 feet, more or less, to a point;
thence,
33. Bearing S 00° 14' 13" E for a distance of 1160.55 feet, more or less, to a point;
thence,
34. Bearing N 86° 38' 03" W for a distance of 27.01 feet, more or less, to a point;
thence,
35. Bearing S 00° 22' 43" E for a distance of 480.26 feet, more or less, to a point;
thence,
36. Bearing S 00° 01' 30" W for a distance of 801.39 feet, more or less, to a point;
thence,
37. Bearing N 88° 41' 57" W for a distance of 214.19 feet, more or less, to a point;
thence,
38. Bearing N 00° 37' 56" E for a distance of 723.34 feet, more or less, to a point;
thence,
39. Bearing N 87° 51' 21" W for a distance of 457.26 feet, more or less, to a point;
thence,
40. Bearing S 09° 34' 39" W for a distance of 490.00 feet, more or less, to a point;
thence,
41. Bearing N 85° 37' 05" W for a distance of 1131.28 feet, more or less, to a point;
thence,
42. Bearing N 12° 03' 05" W for a distance of 219.59 feet, more or less, to a point;
thence,
43. Bearing N 89° 23' 37" W for a distance of 87.72 feet, more or less, to a point;
thence,
44. Bearing S 17° 42' 30" W for a distance of 155.14 feet, more or less, to a point;
thence,
45. Bearing S 17° 53' 32" W for a distance of 126.40 feet, more or less, to a point;
thence,

46. Bearing N 72° 19' 17" W for a distance of 386.49 feet, more or less, to a point;
thence,
47. Bearing N 17° 28' 35" E for a distance of 283.84 feet, more or less, to a point;
thence,
48. Bearing N 16° 59' 11" E for a distance of 342.14 feet, more or less, to a point;
thence,
49. Bearing N 15° 54' 12" E for a distance of 350.69 feet, more or less, to a point;
thence,
50. Bearing N 52° 08' 47" W for a distance of 36.81 feet, more or less, to a point;
thence,
51. Bearing S 88° 40' 18" W for a distance of 428.53 feet, more or less, to a point;
thence,
52. Bearing N 89° 16' 50" W for a distance of 213.32 feet, more or less, to a point;
thence,
53. Bearing N 00° 53' 40" E for a distance of 1336.78 feet, more or less, to a point;
thence,
54. Bearing S 89° 25' 04" E for a distance of 141.38 feet, more or less, to a point;
thence,
55. Bearing N 07° 00' 58" E for a distance of 1005.91 feet, more or less, to a point;
thence,
56. Bearing N 06° 56' 18" E for a distance of 423.00 feet, more or less, to a point;
thence,
57. Bearing N 01° 27' 16" E for a distance of 91.60 feet, more or less, to a point;
thence,
58. Bearing N 87° 57' 21" E for a distance of 51.41 feet, more or less, to a point;
thence,
59. Bearing N 00° 01' 39" W for a distance of 189.59 feet, more or less, to a point;
thence,
60. Bearing N 89° 38' 11" W for a distance of 440.70 feet, more or less, to a point;
thence,
61. Bearing N 02° 12' 21" W for a distance of 910.88 feet, more or less, to a point;
thence,
62. Bearing N 03° 37' 39" W for a distance of 110.60 feet, more or less, to a point;
thence,
63. Bearing N 89° 52' 04" W for a distance of 21.22 feet, more or less, to a point;
thence,
64. Bearing N 00° 00' 00" E for a distance of 30.10 feet, more or less, to a point;
thence,
65. Bearing N 00° 47' 14" W for a distance of 128.11 feet, more or less, to a point;
thence,
66. Bearing N 00° 57' 15" W for a distance of 624.31 feet, more or less, to a point;
thence,
67. Bearing N 00° 50' 51" W for a distance of 247.42 feet, more or less, to a point;
thence,
68. Bearing N 01° 00' 45" W for a distance of 288.25 feet, more or less, to a point;
thence,

69. Bearing N 00° 31' 16" W for a distance of 1194.38 feet, more or less, to a point;
thence,
70. Bearing N 00° 35' 02" W for a distance of 591.98 feet, more or less, to a point;
thence,
71. Bearing N 84° 17' 37" W for a distance of 20.86 feet, more or less, to a point;
thence,
72. Bearing N 00° 29' 03" W for a distance of 388.54 feet, more or less, to a point;
thence,
73. Bearing N 00° 18' 47" E for a distance of 585.54 feet, more or less, to a point;
thence,
74. Bearing N 89° 58' 19" W for a distance of 373.17 feet, more or less, to a point;
thence,
75. Bearing N 25° 13' 07" W for a distance of 34.97 feet, more or less, to a point;
thence,
76. Bearing N 19° 40' 06" W for a distance of 27.66 feet, more or less, to a point;
thence,
77. Bearing N 18° 26' 57" W for a distance of 47.08 feet, more or less, to a point;
thence,
78. Bearing N 16° 16' 22" W for a distance of 46.52 feet, more or less, to a point;
thence,
79. Bearing N 10° 53' 38" W for a distance of 49.27 feet, more or less, to a point;
thence,
80. Bearing N 28° 37' 45" W for a distance of 46.64 feet, more or less, to a point;
thence,
81. Bearing N 36° 53' 35" W for a distance of 46.53 feet, more or less, to a point;
thence,
82. Bearing N 31° 26' 56" W for a distance of 39.26 feet, more or less, to a point;
thence,
83. Bearing N 17° 22' 02" W for a distance of 31.19 feet, more or less, to a point;
thence,
84. Bearing N 14° 02' 52" W for a distance of 23.02 feet, more or less, to a point;
thence,
85. Bearing N 33° 42' 41" W for a distance of 26.84 feet, more or less, to a point;
thence,
86. Bearing N 05° 42' 52" W for a distance of 37.40 feet, more or less, to a point;
thence,
87. Bearing N 00° 00' 00" E for a distance of 31.63 feet, more or less, to a point;
thence,
88. Bearing N 17° 22' 01" W for a distance of 62.39 feet, more or less, to a point;
thence,
89. Bearing S 89° 38' 55" E for a distance of 556.07 feet, more or less, to a point;
thence,
90. Bearing S 02° 43' 22" E for a distance of 212.44 feet, more or less, to a point;
thence,
91. Bearing N 89° 43' 41" E for a distance of 761.17 feet, more or less, to a point;
thence,

92. Bearing N 89° 43' 41" E for a distance of 521.48 feet, more or less, to a point;
thence,
93. Bearing N 00° 10' 25" W for a distance of 861.03 feet, more or less, to a point;
thence,
94. Bearing S 85° 22' 04" E for a distance of 40.55 feet, more or less, to a point;
thence,
95. Bearing N 89° 43' 21" E for a distance of 848.42 feet, more or less, to a point;
thence,
96. Bearing N 89° 54' 24" E for a distance of 1211.24 feet, more or less, to a point;
thence,
97. Bearing N 06° 35' 01" E for a distance of 99.73 feet, more or less, to a point;
thence,
98. Bearing N 08° 35' 21" E for a distance of 135.71 feet, more or less, to a point;
thence,
99. Bearing N 12° 43' 23" E for a distance of 97.35 feet, more or less, to a point;
thence,
100. Bearing N 13° 45' 08" E for a distance of 102.95 feet, more or less, to a point;
thence,
101. Bearing N 15° 03' 56" E for a distance of 259.22 feet, more or less, to a point;
thence,
102. Bearing N 14° 58' 00" E for a distance of 383.19 feet, more or less, to a point;
thence,
103. Bearing N 15° 32' 55" E for a distance of 462.18 feet, more or less, to a point;
thence,
104. Bearing N 15° 25' 34" E for a distance of 369.51 feet, more or less, to a point;
thence,
105. Bearing N 15° 43' 50" E for a distance of 215.53 feet, more or less, to a point;
thence,
106. Bearing N 15° 22' 37" E for a distance of 241.08 feet, more or less, to a point;
thence,
107. Bearing N 15° 06' 10" E for a distance of 167.47 feet, more or less, to a point;
thence,
108. Bearing N 09° 33' 17" E for a distance of 86.18 feet, more or less, to a point;
thence,
109. Bearing N 08° 57' 26" E for a distance of 10.94 feet, more or less, to a point;
thence,
110. Bearing N 29° 28' 07" W for a distance of 28.96 feet, more or less, to a point;
thence,
111. Bearing N 26° 37' 36" W for a distance of 173.67 feet, more or less, to a point;
thence,
112. Bearing N 33° 34' 34" W for a distance of 195.73 feet, more or less, to a point;
thence,
113. Bearing N 32° 59' 14" W for a distance of 283.72 feet, more or less, to a point;
thence,
114. Bearing N 29° 59' 32" W for a distance of 245.84 feet, more or less, to a point;
thence,

115. Bearing N 27° 16' 34" W for a distance of 189.31 feet, more or less, to a point;
thence,
116. Bearing N 24° 11' 37" W for a distance of 144.10 feet, more or less, to a point;
thence,
117. Bearing N 21° 02' 23" W for a distance of 110.42 feet, more or less, to a point;
thence,
118. Bearing N 19° 01' 06" W for a distance of 114.61 feet, more or less, to a point;
thence,
119. Bearing N 15° 44' 29" W for a distance of 141.00 feet, more or less, to a point;
thence,
120. Bearing N 12° 22' 20" W for a distance of 186.20 feet, more or less, to a point;
thence,
121. Bearing N 09° 42' 56" W for a distance of 165.21 feet, more or less, to a point;
thence,
122. Bearing N 07° 56' 52" W for a distance of 142.75 feet, more or less, to a point;
thence,
123. Bearing N 05° 03' 05" W for a distance of 297.96 feet, more or less, to a point;
thence,
124. Bearing N 03° 19' 31" W for a distance of 360.10 feet, more or less, to a point;
thence,
125. Bearing N 02° 46' 59" W for a distance of 482.94 feet, more or less, to a point;
thence,
126. Bearing N 02° 46' 11" W for a distance of 647.69 feet, more or less, to a point;
thence,
127. Bearing N 31° 28' 47" E for a distance of 77.56 feet, more or less, to a point;
thence,
128. Bearing S 67° 09' 28" E for a distance of 39.64 feet, more or less, to a point;
thence,
129. Bearing S 76° 17' 35" E for a distance of 162.97 feet, more or less, to a point;
thence,
130. Bearing S 88° 20' 32" E for a distance of 195.10 feet, more or less, to a point;
thence,
131. Bearing N 83° 49' 22" E for a distance of 69.93 feet, more or less, to a point;
thence,
132. Bearing N 83° 49' 22" E for a distance of 198.48 feet, more or less, to a point;
thence,
133. Bearing N 83° 28' 20" E for a distance of 243.62 feet, more or less, to a point;
thence,
134. Bearing N 83° 52' 13" W for a distance of 272.93 feet, more or less, to a point;
thence,
135. Bearing N 76° 29' 55" W for a distance of 163.21 feet, more or less, to a point;
thence,
136. Bearing N 00° 10' 19" W for a distance of 498.44 feet, more or less, to a point;
thence,
137. Bearing N 00° 38' 40" W for a distance of 230.32 feet, more or less, to a point;
thence,

138. Bearing N 00° 00' 00" E for a distance of 230.30 feet, more or less, to a point;
thence,
139. Bearing N 00° 00' 00" E for a distance of 222.54 feet, more or less, to a point;
thence,
140. Bearing N 89° 26' 51" E for a distance of 499.09 feet, more or less, to a point;
thence,
141. Bearing N 00° 15' 52" E for a distance of 182.30 feet, more or less, to a point;
thence,
142. Bearing N 00° 18' 04" W for a distance of 195.18 feet, more or less, to a point;
thence,
143. Bearing S 66° 46' 09" E for a distance of 906.85 feet, more or less, to a point;
thence,
144. Bearing S 00° 00' 00" W for a distance of 90.57 feet, more or less, to a point;
thence,
145. Bearing S 01° 31' 21" E for a distance of 193.15 feet, more or less, to a point;
thence,
146. Bearing S 01° 28' 11" W for a distance of 201.90 feet, more or less, to a point;
thence,
147. Bearing S 00° 25' 41" E for a distance of 346.76 feet, more or less, to a point;
thence,
148. Bearing S 83° 26' 08" W for a distance of 615.28 feet, more or less, to a point;
thence,
149. Bearing S 00° 39' 05" W for a distance of 84.19 feet, more or less, to a point;
thence,
150. Bearing N 90° 00' 00" W for a distance of 22.98 feet, more or less, to a point;
thence,
151. Bearing S 06° 53' 40" E for a distance of 257.71 feet, more or less, to a point;
thence,
152. Bearing S 82° 54' 26" W for a distance of 115.32 feet, more or less, to a point;
thence,
153. Bearing S 84° 47' 24" W for a distance of 121.10 feet, more or less, to a point;
thence,
154. Bearing S 84° 47' 24" W for a distance of 2.72 feet, more or less, to a point;
thence,
155. Bearing S 02° 46' 11" E for a distance of 667.57 feet, more or less, to a point;
thence,
156. Bearing S 02° 46' 59" E for a distance of 478.21 feet, more or less, to a point;
thence,
157. Bearing S 03° 19' 31" E for a distance of 340.31 feet, more or less, to a point;
thence,
158. Bearing S 05° 03' 05" E for a distance of 251.21 feet, more or less, to a point;
thence,
159. Bearing S 80° 16' 37" E for a distance of 76.84 feet, more or less, to a point;
thence,
160. Bearing N 11° 22' 18" E for a distance of 341.52 feet, more or less, to a point;
thence,

161. Bearing S 78° 47' 38" E for a distance of 202.66 feet, more or less, to a point;
thence,
162. Bearing S 11° 16' 12" W for a distance of 394.61 feet, more or less, to a point;
thence,
163. Bearing N 80° 37' 38" W for a distance of 259.86 feet, more or less, to a point;
thence,
164. Bearing S 07° 56' 52" E for a distance of 45.66 feet, more or less, to a point;
thence,
165. Bearing S 09° 42' 56" E for a distance of 126.60 feet, more or less, to a point;
thence,
166. Bearing S 12° 22' 20" E for a distance of 133.60 feet, more or less, to a point;
thence,
167. Bearing S 15° 44' 29" E for a distance of 82.99 feet, more or less, to a point;
thence,
168. Bearing S 19° 01' 06" E for a distance of 68.36 feet, more or less, to a point;
thence,
169. Bearing S 21° 02' 23" E for a distance of 65.25 feet, more or less, to a point;
thence,
170. Bearing S 24° 11' 37" E for a distance of 89.66 feet, more or less, to a point;
thence,
171. Bearing S 27° 16' 34" E for a distance of 138.70 feet, more or less, to a point;
thence,
172. Bearing S 29° 59' 32" E for a distance of 195.99 feet, more or less, to a point;
thence,
173. Bearing S 32° 59' 14" E for a distance of 252.44 feet, more or less, to a point;
thence,
174. Bearing S 33° 34' 34" E for a distance of 251.31 feet, more or less, to a point;
thence,
175. Bearing S 26° 37' 36" E for a distance of 159.70 feet, more or less, to a point;
thence,
176. Bearing S 00° 18' 07" E for a distance of 347.52 feet, more or less, to a point;
thence,
177. Bearing S 00° 03' 04" E for a distance of 82.80 feet, more or less, to a point;
thence,
178. Bearing N 89° 36' 27" E for a distance of 128.00 feet, more or less, to a point;
thence,
179. Bearing N 89° 36' 29" E for a distance of 484.90 feet, more or less, to a point;
thence,
180. Bearing N 83° 39' 49" E for a distance of 57.02 feet, more or less, to a point;
thence,
181. Bearing S 00° 20' 47" E for a distance of 229.84 feet, more or less, to a point;
thence,
182. Bearing S 04° 40' 14" W for a distance of 701.36 feet, more or less, to a point;
thence,
183. Bearing S 00° 20' 26" E for a distance of 620.53 feet, more or less, to a point;
thence,

184. Bearing S 00° 29' 42" E for a distance of 399.51 feet, more or less, to a point;
thence,
185. Bearing S 00° 58' 05" W for a distance of 178.38 feet, more or less, to a point;
thence,
186. Bearing S 16° 05' 56" W for a distance of 2.03 feet, more or less, to a point;
thence,
187. Bearing S 14° 58' 00" W for a distance of 375.02 feet, more or less, to a point;
thence,
188. Bearing S 15° 03' 56" W for a distance of 238.68 feet, more or less, to a point;
thence,
189. Bearing S 13° 45' 08" W for a distance of 63.33 feet, more or less, to a point;
thence,
190. Bearing S 12° 43' 23" W for a distance of 10.00 feet, more or less, to a point;
thence,
191. Bearing S 08° 35' 21" W for a distance of 31.84 feet, more or less, to a point;
thence,
192. Bearing S 06° 35' 01" W for a distance of 30.19 feet, more or less, to a point;
thence,
193. Bearing S 02° 32' 05" W for a distance of 33.62 feet, more or less, to a point;
thence,
194. Bearing S 00° 30' 03" E for a distance of 249.36 feet, more or less, to a point;
thence,
195. Bearing S 00° 31' 00" E for a distance of 709.52 feet, more or less, to a point;
thence,
196. Bearing S 00° 43' 08" E for a distance of 576.80 feet, more or less, to a point;
thence,
197. Bearing S 00° 31' 58" E for a distance of 87.84 feet, more or less, to a point;
thence,
198. Bearing N 89° 58' 34" E for a distance of 2526.89 feet, more or less, to a point;
thence,
199. Bearing S 11° 55' 08" W for a distance of 5.32 feet, more or less, to a point;
thence,
200. Bearing N 89° 35' 20" E for a distance of 505.65 feet, more or less, to a point;
thence,
201. Bearing N 86° 10' 31" E for a distance of 9.76 feet, more or less, to a point;
thence,
202. Bearing N 84° 13' 27" E for a distance of 296.08 feet, more or less, to a point;
thence,
203. Bearing N 85° 15' 37" E for a distance of 346.26 feet, more or less, to a point;
thence,
204. Bearing S 88° 10' 25" E for a distance of 154.50 feet, more or less, to a point;
thence,
205. Bearing S 89° 35' 16" E for a distance of 130.41 feet, more or less, to a point;
thence,
206. Bearing N 90° 00' 00" E for a distance of 115.24 feet, more or less, to a point;
thence,

207. Bearing S 04° 22' 01" W for a distance of 633.74 feet, more or less, to a point; thence,
208. Bearing S 86° 49' 21" W for a distance of 197.64 feet, more or less, to a point; thence,
209. Bearing S 01° 32' 24" E for a distance of 188.33 feet, more or less, to a point; thence,
210. Bearing S 89° 35' 16" E for a distance of 38.91 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1049842.8393' and whose Easting is 1418560.4806'; thence,

1. Bearing N 89° 11' 20" E for a distance of 141.46 feet, more or less, to a point; thence,
2. Bearing N 89° 06' 58" E for a distance of 471.84 feet, more or less, to a point; thence,
3. Bearing N 89° 09' 29" E for a distance of 111.96 feet, more or less, to a point; thence,
4. Bearing N 01° 30' 58" W for a distance of 628.87 feet, more or less, to a point; thence,
5. Bearing N 88° 09' 06" W for a distance of 656.12 feet, more or less, to a point; thence,
6. Bearing N 00° 18' 34" W for a distance of 1297.45 feet, more or less, to a point; thence,
7. Bearing N 00° 18' 34" W for a distance of 813.66 feet, more or less, to a point; thence,
8. Bearing S 89° 24' 52" W for a distance of 796.58 feet, more or less, to a point; thence,
9. Bearing S 89° 24' 53" W for a distance of 309.90 feet, more or less, to a point; thence,
10. Bearing N 01° 02' 33" W for a distance of 646.63 feet, more or less, to a point; thence,
11. Bearing N 85° 14' 25" E for a distance of 283.32 feet, more or less, to a point; thence,
12. Bearing N 02° 06' 12" W for a distance of 641.08 feet, more or less, to a point; thence,
13. Bearing N 05° 43' 52" W for a distance of 70.92 feet, more or less, to a point; thence,
14. Bearing N 00° 23' 44" W for a distance of 256.00 feet, more or less, to a point; thence,
15. Bearing N 00° 51' 49" W for a distance of 1043.49 feet, more or less, to a point; thence,
16. Bearing N 87° 26' 04" W for a distance of 738.62 feet, more or less, to a point; thence,
17. Bearing S 88° 55' 19" W for a distance of 1307.13 feet, more or less, to a point; thence,

18. Bearing N 00° 48' 40" W for a distance of 646.14 feet, more or less, to a point; thence,
19. Bearing N 00° 40' 43" W for a distance of 763.93 feet, more or less, to a point; thence,
20. Bearing N 01° 04' 06" W for a distance of 740.38 feet, more or less, to a point; thence,
21. Bearing S 89° 47' 29" E for a distance of 1328.74 feet, more or less, to a point; thence,
22. Bearing N 00° 44' 07" W for a distance of 485.25 feet, more or less, to a point; thence,
23. Bearing N 01° 07' 42" E for a distance of 81.41 feet, more or less, to a point; thence,
24. Bearing N 00° 04' 53" W for a distance of 1179.03 feet, more or less, to a point; thence,
25. Bearing N 03° 29' 51" W for a distance of 816.42 feet, more or less, to a point; thence,
26. Bearing N 00° 38' 51" E for a distance of 78.71 feet, more or less, to a point; thence,
27. Bearing S 88° 55' 19" E for a distance of 701.37 feet, more or less, to a point; thence,
28. Bearing S 88° 55' 19" E for a distance of 1283.57 feet, more or less, to a point; thence,
29. Bearing N 01° 25' 59" E for a distance of 199.75 feet, more or less, to a point; thence,
30. Bearing N 00° 48' 48" E for a distance of 199.74 feet, more or less, to a point; thence,
31. Bearing N 88° 17' 42" W for a distance of 162.17 feet, more or less, to a point; thence,
32. Bearing N 01° 12' 45" E for a distance of 228.19 feet, more or less, to a point; thence,
33. Bearing N 22° 05' 27" E for a distance of 282.28 feet, more or less, to a point; thence,
34. Bearing N 22° 00' 13" E for a distance of 424.78 feet, more or less, to a point; thence,
35. Bearing N 89° 46' 01" E for a distance of 547.59 feet, more or less, to a point; thence,
36. Bearing S 08° 09' 14" E for a distance of 61.43 feet, more or less, to a point; thence,
37. Bearing S 07° 19' 28" E for a distance of 77.14 feet, more or less, to a point; thence,
38. Bearing S 10° 56' 00" E for a distance of 51.38 feet, more or less, to a point; thence,
39. Bearing S 03° 55' 44" E for a distance of 85.05 feet, more or less, to a point; thence,
40. Bearing S 01° 48' 42" E for a distance of 21.49 feet, more or less, to a point; thence,
41. Bearing S 89° 39' 27" E for a distance of 334.98 feet, more or less, to a point; thence,
42. Bearing S 87° 36' 55" E for a distance of 929.74 feet, more or less, to a point; thence,
43. Bearing S 00° 33' 45" E for a distance of 65.59 feet, more or less, to a point; thence,
44. Bearing S 00° 33' 45" E for a distance of 158.83 feet, more or less, to a point; thence,
45. Bearing S 00° 41' 50" E for a distance of 1258.81 feet, more or less, to a point; thence,
46. Bearing S 00° 45' 35" E for a distance of 672.25 feet, more or less, to a point; thence,

47. Bearing N 89° 25' 53" E for a distance of 1321.65 feet, more or less, to a point; thence,
48. Bearing S 01° 07' 41" E for a distance of 510.57 feet, more or less, to a point; thence,
49. Bearing S 01° 42' 38" E for a distance of 453.60 feet, more or less, to a point; thence,
50. Bearing S 01° 47' 28" E for a distance of 791.88 feet, more or less, to a point; thence,
51. Bearing N 89° 47' 28" W for a distance of 408.88 feet, more or less, to a point; thence,
52. Bearing N 00° 00' 00" E for a distance of 101.32 feet, more or less, to a point; thence,
53. Bearing N 89° 55' 43" W for a distance of 866.91 feet, more or less, to a point; thence,
54. Bearing S 01° 29' 44" E for a distance of 635.66 feet, more or less, to a point; thence,
55. Bearing S 89° 19' 52" W for a distance of 163.94 feet, more or less, to a point; thence,
56. Bearing S 07° 00' 43" E for a distance of 657.77 feet, more or less, to a point; thence,
57. Bearing N 90° 00' 00" E for a distance of 408.00 feet, more or less, to a point; thence,
58. Bearing N 90° 00' 00" E for a distance of 319.79 feet, more or less, to a point; thence,
59. Bearing N 26° 27' 43" E for a distance of 411.34 feet, more or less, to a point; thence,
60. Bearing S 86° 59' 25" E for a distance of 37.10 feet, more or less, to a point; thence,
61. Bearing N 01° 47' 27" W for a distance of 68.00 feet, more or less, to a point; thence,
62. Bearing N 32° 21' 32" E for a distance of 56.08 feet, more or less, to a point; thence,
63. Bearing N 42° 26' 20" E for a distance of 272.00 feet, more or less, to a point; thence,
64. Bearing N 88° 12' 32" E for a distance of 198.90 feet, more or less, to a point; thence,
65. Bearing N 88° 12' 22" E for a distance of 88.84 feet, more or less, to a point; thence,
66. Bearing N 04° 47' 47" E for a distance of 22.72 feet, more or less, to a point; thence,
67. Bearing S 84° 59' 34" E for a distance of 571.35 feet, more or less, to a point; thence,
68. Bearing S 17° 36' 49" E for a distance of 1147.80 feet, more or less, to a point; thence,
69. Bearing S 18° 02' 52" E for a distance of 229.82 feet, more or less, to a point; thence,
70. Bearing N 73° 27' 19" E for a distance of 294.46 feet, more or less, to a point; thence,
71. Bearing N 80° 57' 23" E for a distance of 290.97 feet, more or less, to a point; thence,
72. Bearing N 87° 02' 29" E for a distance of 295.37 feet, more or less, to a point; thence,
73. Bearing S 02° 54' 47" W for a distance of 130.52 feet, more or less, to a point; thence,
74. Bearing N 83° 00' 26" W for a distance of 22.79 feet, more or less, to a point; thence,
75. Bearing N 85° 02' 03" W for a distance of 31.54 feet, more or less, to a point; thence,
76. Bearing N 80° 11' 17" W for a distance of 72.09 feet, more or less, to a point; thence,
77. Bearing N 85° 14' 38" W for a distance of 19.26 feet, more or less, to a point; thence,

78. Bearing S 75° 04' 46'' W for a distance of 42.42 feet, more or less, to a point; thence,
79. Bearing S 88° 29' 38'' W for a distance of 51.93 feet, more or less, to a point; thence,
80. Bearing S 87° 52' 50'' W for a distance of 73.82 feet, more or less, to a point; thence,
81. Bearing S 83° 50' 06'' W for a distance of 50.84 feet, more or less, to a point; thence,
82. Bearing S 74° 38' 06'' W for a distance of 56.67 feet, more or less, to a point; thence,
83. Bearing S 65° 56' 30'' W for a distance of 70.32 feet, more or less, to a point; thence,
84. Bearing S 64° 49' 01'' W for a distance of 51.33 feet, more or less, to a point; thence,
85. Bearing S 62° 43' 07'' W for a distance of 47.65 feet, more or less, to a point; thence,
86. Bearing S 57° 48' 40'' W for a distance of 86.34 feet, more or less, to a point; thence,
87. Bearing S 55° 08' 48'' W for a distance of 54.94 feet, more or less, to a point; thence,
88. Bearing S 49° 25' 17'' W for a distance of 50.37 feet, more or less, to a point; thence,
89. Bearing S 42° 54' 05'' W for a distance of 52.18 feet, more or less, to a point; thence,
90. Bearing S 41° 22' 15'' W for a distance of 45.48 feet, more or less, to a point; thence,
91. Bearing S 31° 50' 53'' W for a distance of 46.60 feet, more or less, to a point; thence,
92. Bearing S 15° 39' 15'' W for a distance of 35.44 feet, more or less, to a point; thence,
93. Bearing S 07° 51' 31'' W for a distance of 39.96 feet, more or less, to a point; thence,
94. Bearing S 02° 36' 23'' W for a distance of 30.06 feet, more or less, to a point; thence,
95. Bearing S 04° 14' 29'' E for a distance of 36.96 feet, more or less, to a point; thence,
96. Bearing S 04° 34' 31'' E for a distance of 34.24 feet, more or less, to a point; thence,
97. Bearing S 15° 57' 34'' E for a distance of 49.69 feet, more or less, to a point; thence,
98. Bearing S 22° 56' 50'' E for a distance of 38.54 feet, more or less, to a point; thence,
99. Bearing S 26° 34' 57'' E for a distance of 39.69 feet, more or less, to a point; thence,
100. Bearing S 28° 30' 56'' E for a distance of 54.37 feet, more or less, to a point; thence,
101. Bearing S 41° 55' 45'' E for a distance of 71.56 feet, more or less, to a point; thence,
102. Bearing S 59° 26' 29'' E for a distance of 69.81 feet, more or less, to a point; thence,
103. Bearing S 75° 44' 12'' E for a distance of 57.29 feet, more or less, to a point; thence,
104. Bearing N 85° 36' 17'' E for a distance of 35.62 feet, more or less, to a point; thence,
105. Bearing N 81° 15' 40'' E for a distance of 53.91 feet, more or less, to a point; thence,
106. Bearing N 73° 05' 07'' E for a distance of 65.68 feet, more or less, to a point; thence,
107. Bearing N 69° 14' 34'' E for a distance of 42.37 feet, more or less, to a point; thence,
108. Bearing N 61° 12' 38'' E for a distance of 31.18 feet, more or less, to a point; thence,
109. Bearing N 74° 45' 17'' E for a distance of 31.15 feet, more or less, to a point; thence,
110. Bearing N 75° 58' 31'' E for a distance of 39.43 feet, more or less, to a point; thence,
111. Bearing N 61° 12' 29'' E for a distance of 31.18 feet, more or less, to a point; thence,
112. Bearing N 55° 11' 48'' E for a distance of 38.27 feet, more or less, to a point; thence,
113. Bearing N 14° 02' 58'' E for a distance of 16.89 feet, more or less, to a point; thence,
114. Bearing N 31° 37' 39'' W for a distance of 20.84 feet, more or less, to a point; thence,
115. Bearing N 14° 02' 52'' W for a distance of 22.51 feet, more or less, to a point; thence,
116. Bearing N 42° 32' 00'' E for a distance of 22.23 feet, more or less, to a point; thence,
117. Bearing N 67° 38' 10'' E for a distance of 25.11 feet, more or less, to a point; thence,
118. Bearing N 87° 30' 45'' E for a distance of 31.45 feet, more or less, to a point; thence,
119. Bearing N 77° 28' 47'' E for a distance of 37.78 feet, more or less, to a point; thence,
120. Bearing N 75° 04' 51'' E for a distance of 42.41 feet, more or less, to a point; thence,
121. Bearing N 78° 41' 52'' E for a distance of 41.79 feet, more or less, to a point; thence,
122. Bearing N 90° 00' 00'' E for a distance of 46.45 feet, more or less, to a point; thence,
123. Bearing S 78° 19' 08'' E for a distance of 40.46 feet, more or less, to a point; thence,

124. Bearing S 60° 16' 33" E for a distance of 33.04 feet, more or less, to a point; thence,
125. Bearing S 39° 49' 41" E for a distance of 32.00 feet, more or less, to a point; thence,
126. Bearing S 35° 00' 44" E for a distance of 33.33 feet, more or less, to a point; thence,
127. Bearing S 21° 49' 06" E for a distance of 36.76 feet, more or less, to a point; thence,
128. Bearing S 06° 50' 57" E for a distance of 34.37 feet, more or less, to a point; thence,
129. Bearing S 30° 58' 59" E for a distance of 23.88 feet, more or less, to a point; thence,
130. Bearing S 31° 20' 57" E for a distance of 36.76 feet, more or less, to a point; thence,
131. Bearing S 29° 22' 40" E for a distance of 50.13 feet, more or less, to a point; thence,
132. Bearing S 29° 39' 29" E for a distance of 91.11 feet, more or less, to a point; thence,
133. Bearing S 24° 38' 25" E for a distance of 36.05 feet, more or less, to a point; thence,
134. Bearing S 20° 58' 25" E for a distance of 60.90 feet, more or less, to a point; thence,
135. Bearing S 09° 52' 26" E for a distance of 31.87 feet, more or less, to a point; thence,
136. Bearing S 04° 05' 17" W for a distance of 19.16 feet, more or less, to a point; thence,
137. Bearing S 07° 07' 54" W for a distance of 33.02 feet, more or less, to a point; thence,
138. Bearing S 23° 58' 45" W for a distance of 26.89 feet, more or less, to a point; thence,
139. Bearing S 37° 35' 27" W for a distance of 22.40 feet, more or less, to a point; thence,
140. Bearing S 48° 08' 45" W for a distance of 53.19 feet, more or less, to a point; thence,
141. Bearing S 57° 17' 05" W for a distance of 45.46 feet, more or less, to a point; thence,
142. Bearing S 50° 12' 59" W for a distance of 42.67 feet, more or less, to a point; thence,
143. Bearing S 33° 42' 44" W for a distance of 39.38 feet, more or less, to a point; thence,
144. Bearing S 41° 39' 25" W for a distance of 32.89 feet, more or less, to a point; thence,
145. Bearing S 48° 23' 18" W for a distance of 32.89 feet, more or less, to a point; thence,
146. Bearing S 49° 25' 17" W for a distance of 37.77 feet, more or less, to a point; thence,
147. Bearing S 39° 49' 40" W for a distance of 31.99 feet, more or less, to a point; thence,
148. Bearing S 36° 53' 36" W for a distance of 34.14 feet, more or less, to a point; thence,
149. Bearing S 32° 29' 28" W for a distance of 35.61 feet, more or less, to a point; thence,
150. Bearing S 22° 29' 48" W for a distance of 42.85 feet, more or less, to a point; thence,
151. Bearing S 14° 28' 51" W for a distance of 43.71 feet, more or less, to a point; thence,
152. Bearing S 27° 25' 34" W for a distance of 41.52 feet, more or less, to a point; thence,
153. Bearing S 23° 24' 09" W for a distance of 55.03 feet, more or less, to a point; thence,
154. Bearing S 13° 08' 36" W for a distance of 54.58 feet, more or less, to a point; thence,
155. Bearing S 10° 26' 44" W for a distance of 52.75 feet, more or less, to a point; thence,
156. Bearing S 12° 12' 40" W for a distance of 51.68 feet, more or less, to a point; thence,
157. Bearing S 10° 11' 00" W for a distance of 54.09 feet, more or less, to a point; thence,
158. Bearing S 07° 54' 49" W for a distance of 49.61 feet, more or less, to a point; thence,
159. Bearing S 02° 00' 39" W for a distance of 77.86 feet, more or less, to a point; thence,
160. Bearing S 05° 49' 49" W for a distance of 67.24 feet, more or less, to a point; thence,
161. Bearing S 01° 14' 43" E for a distance of 62.81 feet, more or less, to a point; thence,
162. Bearing S 03° 54' 15" E for a distance of 60.20 feet, more or less, to a point; thence,
163. Bearing S 08° 08' 13" E for a distance of 38.61 feet, more or less, to a point; thence,
164. Bearing S 14° 02' 48" E for a distance of 56.28 feet, more or less, to a point; thence,
165. Bearing S 12° 41' 26" E for a distance of 55.97 feet, more or less, to a point; thence,
166. Bearing S 12° 25' 36" E for a distance of 51.58 feet, more or less, to a point; thence,
167. Bearing S 17° 45' 29" E for a distance of 35.83 feet, more or less, to a point; thence,
168. Bearing S 26° 34' 59" E for a distance of 33.58 feet, more or less, to a point; thence,
169. Bearing S 36° 16' 33" E for a distance of 25.40 feet, more or less, to a point; thence,

170. Bearing S 36° 02' 58" E for a distance of 37.14 feet, more or less, to a point; thence,
171. Bearing S 30° 40' 18" E for a distance of 42.85 feet, more or less, to a point; thence,
172. Bearing S 18° 26' 53" E for a distance of 30.22 feet, more or less, to a point; thence,
173. Bearing S 18° 02' 52" E for a distance of 61.73 feet, more or less, to a point; thence,
174. Bearing S 24° 19' 17" E for a distance of 46.44 feet, more or less, to a point; thence,
175. Bearing S 38° 10' 48" E for a distance of 24.31 feet, more or less, to a point; thence,
176. Bearing S 41° 50' 37" E for a distance of 34.81 feet, more or less, to a point; thence,
177. Bearing S 45° 01' 21" E for a distance of 28.97 feet, more or less, to a point; thence,
178. Bearing S 36° 53' 30" E for a distance of 34.14 feet, more or less, to a point; thence,
179. Bearing S 34° 05' 57" E for a distance of 56.05 feet, more or less, to a point; thence,
180. Bearing S 38° 10' 44" E for a distance of 48.62 feet, more or less, to a point; thence,
181. Bearing S 41° 47' 01" E for a distance of 51.26 feet, more or less, to a point; thence,
182. Bearing S 38° 58' 03" E for a distance of 59.29 feet, more or less, to a point; thence,
183. Bearing S 16° 42' 47" E for a distance of 28.50 feet, more or less, to a point; thence,
184. Bearing S 33° 42' 37" E for a distance of 34.46 feet, more or less, to a point; thence,
185. Bearing S 36° 02' 55" E for a distance of 37.14 feet, more or less, to a point; thence,
186. Bearing S 32° 01' 34" E for a distance of 51.52 feet, more or less, to a point; thence,
187. Bearing S 24° 09' 45" E for a distance of 43.39 feet, more or less, to a point; thence,
188. Bearing S 32° 14' 59" E for a distance of 74.25 feet, more or less, to a point; thence,
189. Bearing S 26° 35' 06" E for a distance of 42.74 feet, more or less, to a point; thence,
190. Bearing S 32° 01' 27" E for a distance of 25.76 feet, more or less, to a point; thence,
191. Bearing S 26° 35' 00" E for a distance of 39.69 feet, more or less, to a point; thence,
192. Bearing S 31° 50' 49" E for a distance of 46.60 feet, more or less, to a point; thence,
193. Bearing S 34° 43' 02" E for a distance of 43.18 feet, more or less, to a point; thence,
194. Bearing S 43° 10' 30" E for a distance of 29.95 feet, more or less, to a point; thence,
195. Bearing S 43° 10' 33" E for a distance of 29.95 feet, more or less, to a point; thence,
196. Bearing S 43° 33' 21" E for a distance of 37.67 feet, more or less, to a point; thence,
197. Bearing S 38° 10' 40" E for a distance of 48.62 feet, more or less, to a point; thence,
198. Bearing S 35° 00' 49" E for a distance of 33.33 feet, more or less, to a point; thence,
199. Bearing S 24° 19' 20" E for a distance of 46.44 feet, more or less, to a point; thence,
200. Bearing S 34° 02' 56" E for a distance of 93.66 feet, more or less, to a point; thence,
201. Bearing S 31° 14' 19" E for a distance of 52.69 feet, more or less, to a point; thence,
202. Bearing S 33° 17' 44" E for a distance of 52.26 feet, more or less, to a point; thence,
203. Bearing S 34° 53' 50" E for a distance of 54.92 feet, more or less, to a point; thence,
204. Bearing S 27° 14' 06" E for a distance of 53.73 feet, more or less, to a point; thence,
205. Bearing S 39° 34' 54" E for a distance of 40.74 feet, more or less, to a point; thence,
206. Bearing S 31° 20' 57" E for a distance of 36.76 feet, more or less, to a point; thence,
207. Bearing S 36° 53' 30" E for a distance of 40.96 feet, more or less, to a point; thence,
208. Bearing S 26° 34' 55" E for a distance of 27.48 feet, more or less, to a point; thence,
209. Bearing S 30° 05' 20" E for a distance of 59.95 feet, more or less, to a point; thence,
210. Bearing S 37° 15' 26" E for a distance of 42.88 feet, more or less, to a point; thence,
211. Bearing S 27° 19' 07" E for a distance of 47.63 feet, more or less, to a point; thence,
212. Bearing S 22° 23' 48" E for a distance of 25.10 feet, more or less, to a point; thence,
213. Bearing S 14° 02' 48" E for a distance of 33.77 feet, more or less, to a point; thence,
214. Bearing S 12° 16' 30" E for a distance of 32.13 feet, more or less, to a point; thence,
215. Bearing S 23° 12' 44" E for a distance of 20.79 feet, more or less, to a point; thence,

216. Bearing S 42° 43' 58" E for a distance of 24.16 feet, more or less, to a point; thence,
217. Bearing S 37° 35' 35" E for a distance of 22.40 feet, more or less, to a point; thence,
218. Bearing S 34° 18' 26" E for a distance of 36.36 feet, more or less, to a point; thence,
219. Bearing S 28° 16' 39" E for a distance of 32.38 feet, more or less, to a point; thence,
220. Bearing S 22° 56' 58" E for a distance of 38.54 feet, more or less, to a point; thence,
221. Bearing S 04° 58' 23" E for a distance of 31.52 feet, more or less, to a point; thence,
222. Bearing S 10° 07' 59" E for a distance of 38.83 feet, more or less, to a point; thence,
223. Bearing S 12° 06' 11" E for a distance of 19.55 feet, more or less, to a point; thence,
224. Bearing S 25° 21' 54" E for a distance of 28.70 feet, more or less, to a point; thence,
225. Bearing S 30° 58' 59" E for a distance of 23.88 feet, more or less, to a point; thence,
226. Bearing S 30° 29' 11" E for a distance of 26.93 feet, more or less, to a point; thence,
227. Bearing S 42° 17' 45" E for a distance of 40.60 feet, more or less, to a point; thence,
228. Bearing S 32° 22' 08" E for a distance of 48.48 feet, more or less, to a point; thence,
229. Bearing S 20° 47' 11" E for a distance of 42.34 feet, more or less, to a point; thence,
230. Bearing S 25° 43' 40" E for a distance of 40.91 feet, more or less, to a point; thence,
231. Bearing S 24° 07' 11" E for a distance of 56.83 feet, more or less, to a point; thence,
232. Bearing S 05° 11' 53" E for a distance of 30.16 feet, more or less, to a point; thence,
233. Bearing S 00° 00' 00" E for a distance of 21.84 feet, more or less, to a point; thence,
234. Bearing S 30° 16' 33" W for a distance of 18.97 feet, more or less, to a point; thence,
235. Bearing S 36° 16' 34" W for a distance of 25.40 feet, more or less, to a point; thence,
236. Bearing S 20° 54' 37" W for a distance of 28.78 feet, more or less, to a point; thence,
237. Bearing S 15° 32' 20" W for a distance of 25.50 feet, more or less, to a point; thence,
238. Bearing S 29° 04' 23" W for a distance of 28.11 feet, more or less, to a point; thence,
239. Bearing S 52° 27' 16" W for a distance of 22.40 feet, more or less, to a point; thence,
240. Bearing S 51° 51' 53" W for a distance of 24.31 feet, more or less, to a point; thence,
241. Bearing S 55° 01' 49" W for a distance of 33.34 feet, more or less, to a point; thence,
242. Bearing S 68° 12' 45" W for a distance of 29.42 feet, more or less, to a point; thence,
243. Bearing N 87° 23' 58" W for a distance of 30.09 feet, more or less, to a point; thence,
244. Bearing N 80° 08' 34" W for a distance of 31.89 feet, more or less, to a point; thence,
245. Bearing N 81° 52' 29" W for a distance of 28.98 feet, more or less, to a point; thence,
246. Bearing N 69° 09' 40" W for a distance of 30.70 feet, more or less, to a point; thence,
247. Bearing N 70° 55' 08" W for a distance of 37.58 feet, more or less, to a point; thence,
248. Bearing N 80° 55' 08" W for a distance of 34.59 feet, more or less, to a point; thence,
249. Bearing N 83° 25' 25" W for a distance of 35.76 feet, more or less, to a point; thence,
250. Bearing N 70° 55' 13" W for a distance of 37.59 feet, more or less, to a point; thence,
251. Bearing S 87° 30' 45" W for a distance of 31.45 feet, more or less, to a point; thence,
252. Bearing S 78° 41' 58" W for a distance of 34.83 feet, more or less, to a point; thence,
253. Bearing S 67° 10' 54" W for a distance of 28.16 feet, more or less, to a point; thence,
254. Bearing S 54° 10' 56" W for a distance of 30.32 feet, more or less, to a point; thence,
255. Bearing S 75° 58' 31" W for a distance of 33.80 feet, more or less, to a point; thence,
256. Bearing S 59° 33' 15" W for a distance of 26.94 feet, more or less, to a point; thence,
257. Bearing S 51° 43' 56" W for a distance of 33.06 feet, more or less, to a point; thence,
258. Bearing S 45° 01' 20" W for a distance of 34.76 feet, more or less, to a point; thence,
259. Bearing S 45° 54' 18" W for a distance of 62.77 feet, more or less, to a point; thence,
260. Bearing S 37° 15' 27" W for a distance of 42.88 feet, more or less, to a point; thence,
261. Bearing S 36° 33' 02" W for a distance of 45.88 feet, more or less, to a point; thence,

262. Bearing S 23° 12' 52" W for a distance of 41.59 feet, more or less, to a point; thence,
263. Bearing S 14° 02' 49" W for a distance of 33.77 feet, more or less, to a point; thence,
264. Bearing S 16° 16' 21" W for a distance of 34.13 feet, more or less, to a point; thence,
265. Bearing S 27° 55' 03" W for a distance of 26.26 feet, more or less, to a point; thence,
266. Bearing S 32° 38' 21" W for a distance of 40.53 feet, more or less, to a point; thence,
267. Bearing S 40° 37' 28" W for a distance of 37.77 feet, more or less, to a point; thence,
268. Bearing S 39° 18' 45" W for a distance of 38.81 feet, more or less, to a point; thence,
269. Bearing S 18° 43' 28" W for a distance of 64.52 feet, more or less, to a point; thence,
270. Bearing S 19° 18' 19" W for a distance of 28.93 feet, more or less, to a point; thence,
271. Bearing S 31° 20' 59" W for a distance of 36.76 feet, more or less, to a point; thence,
272. Bearing S 33° 07' 57" W for a distance of 37.49 feet, more or less, to a point; thence,
273. Bearing S 27° 29' 35" W for a distance of 38.47 feet, more or less, to a point; thence,
274. Bearing S 29° 33' 34" W for a distance of 47.08 feet, more or less, to a point; thence,
275. Bearing S 20° 14' 20" W for a distance of 27.64 feet, more or less, to a point; thence,
276. Bearing S 16° 56' 31" W for a distance of 32.82 feet, more or less, to a point; thence,
277. Bearing S 17° 27' 34" W for a distance of 50.08 feet, more or less, to a point; thence,
278. Bearing S 25° 28' 48" W for a distance of 31.76 feet, more or less, to a point; thence,
279. Bearing S 30° 59' 02" W for a distance of 39.81 feet, more or less, to a point; thence,
280. Bearing S 24° 52' 54" W for a distance of 61.69 feet, more or less, to a point; thence,
281. Bearing S 27° 16' 27" W for a distance of 50.68 feet, more or less, to a point; thence,
282. Bearing S 21° 37' 49" W for a distance of 77.83 feet, more or less, to a point; thence,
283. Bearing S 16° 50' 10" W for a distance of 62.44 feet, more or less, to a point; thence,
284. Bearing S 11° 53' 52" W for a distance of 53.01 feet, more or less, to a point; thence,
285. Bearing S 14° 16' 05" W for a distance of 171.84 feet, more or less, to a point; thence,
286. Bearing S 14° 02' 53" W for a distance of 33.77 feet, more or less, to a point; thence,
287. Bearing S 02° 17' 30" W for a distance of 34.16 feet, more or less, to a point; thence,
288. Bearing S 00° 00' 00" W for a distance of 38.22 feet, more or less, to a point; thence,
289. Bearing S 02° 23' 15" E for a distance of 32.79 feet, more or less, to a point; thence,
290. Bearing S 08° 32' 11" W for a distance of 27.61 feet, more or less, to a point; thence,
291. Bearing S 14° 02' 51" W for a distance of 33.77 feet, more or less, to a point; thence,
292. Bearing S 17° 00' 13" W for a distance of 51.39 feet, more or less, to a point; thence,
293. Bearing S 20° 52' 10" W for a distance of 30.68 feet, more or less, to a point; thence,
294. Bearing S 04° 24' 08" W for a distance of 17.80 feet, more or less, to a point; thence,
295. Bearing S 03° 41' 40" E for a distance of 42.40 feet, more or less, to a point; thence,
296. Bearing S 06° 10' 31" E for a distance of 50.80 feet, more or less, to a point; thence,
297. Bearing S 07° 43' 15" E for a distance of 34.25 feet, more or less, to a point; thence,
298. Bearing S 06° 55' 02" E for a distance of 45.38 feet, more or less, to a point; thence,
299. Bearing S 18° 26' 57" E for a distance of 25.90 feet, more or less, to a point; thence,
300. Bearing S 20° 09' 00" E for a distance of 43.62 feet, more or less, to a point; thence,
301. Bearing S 26° 35' 02" E for a distance of 36.63 feet, more or less, to a point; thence,
302. Bearing S 24° 27' 43" E for a distance of 49.49 feet, more or less, to a point; thence,
303. Bearing S 29° 16' 06" E for a distance of 39.12 feet, more or less, to a point; thence,
304. Bearing S 35° 19' 54" E for a distance of 40.16 feet, more or less, to a point; thence,
305. Bearing S 55° 54' 26" E for a distance of 51.14 feet, more or less, to a point; thence,
306. Bearing S 67° 15' 55" E for a distance of 45.92 feet, more or less, to a point; thence,

307. Bearing S 71° 34' 46" E for a distance of 25.92 feet, more or less, to a point; thence,
308. Bearing S 80° 08' 26" E for a distance of 31.89 feet, more or less, to a point; thence,
309. Bearing S 87° 16' 35" E for a distance of 28.72 feet, more or less, to a point; thence,
310. Bearing S 70° 21' 41" E for a distance of 20.31 feet, more or less, to a point; thence,
311. Bearing S 67° 46' 03" E for a distance of 32.47 feet, more or less, to a point; thence,
312. Bearing S 69° 27' 31" E for a distance of 35.01 feet, more or less, to a point; thence,
313. Bearing S 74° 04' 02" E for a distance of 29.84 feet, more or less, to a point; thence,
314. Bearing S 73° 27' 19" E for a distance of 52.73 feet, more or less, to a point; thence,
315. Bearing S 84° 24' 20" E for a distance of 70.01 feet, more or less, to a point; thence,
316. Bearing N 86° 38' 11" E for a distance of 46.53 feet, more or less, to a point; thence,
317. Bearing N 71° 09' 37" E for a distance of 59.18 feet, more or less, to a point; thence,
318. Bearing N 66° 49' 07" E for a distance of 41.61 feet, more or less, to a point; thence,
319. Bearing N 60° 39' 44" E for a distance of 50.15 feet, more or less, to a point; thence,
320. Bearing N 62° 40' 13" E for a distance of 44.60 feet, more or less, to a point; thence,
321. Bearing N 52° 47' 11" E for a distance of 42.89 feet, more or less, to a point; thence,
322. Bearing N 40° 26' 53" E for a distance of 48.43 feet, more or less, to a point; thence,
323. Bearing N 27° 16' 28" E for a distance of 50.68 feet, more or less, to a point; thence,
324. Bearing N 43° 45' 10" E for a distance of 27.16 feet, more or less, to a point; thence,
325. Bearing N 42° 32' 01" E for a distance of 22.23 feet, more or less, to a point; thence,
326. Bearing N 31° 27' 01" E for a distance of 28.80 feet, more or less, to a point; thence,
327. Bearing N 03° 00' 55" E for a distance of 25.97 feet, more or less, to a point; thence,
328. Bearing N 23° 12' 55" E for a distance of 20.79 feet, more or less, to a point; thence,
329. Bearing N 15° 32' 03" E for a distance of 25.50 feet, more or less, to a point; thence,
330. Bearing N 30° 05' 22" E for a distance of 29.98 feet, more or less, to a point; thence,
331. Bearing N 29° 45' 49" E for a distance of 22.02 feet, more or less, to a point; thence,
332. Bearing N 25° 34' 43" E for a distance of 34.81 feet, more or less, to a point; thence,
333. Bearing N 45° 01' 25" E for a distance of 30.90 feet, more or less, to a point; thence,
334. Bearing N 55° 38' 28" E for a distance of 31.44 feet, more or less, to a point; thence,
335. Bearing N 59° 45' 43" E for a distance of 37.95 feet, more or less, to a point; thence,
336. Bearing N 82° 34' 31" E for a distance of 31.69 feet, more or less, to a point; thence,
337. Bearing N 82° 52' 51" E for a distance of 44.06 feet, more or less, to a point; thence,
338. Bearing N 83° 25' 24" E for a distance of 35.76 feet, more or less, to a point; thence,
339. Bearing N 75° 15' 58" E for a distance of 26.84 feet, more or less, to a point; thence,
340. Bearing N 74° 18' 15" E for a distance of 45.41 feet, more or less, to a point; thence,
341. Bearing N 80° 32' 38" E for a distance of 41.55 feet, more or less, to a point; thence,
342. Bearing N 87° 52' 45" E for a distance of 36.91 feet, more or less, to a point; thence,
343. Bearing S 86° 03' 24" E for a distance of 39.71 feet, more or less, to a point; thence,
344. Bearing N 83° 29' 08" E for a distance of 48.13 feet, more or less, to a point; thence,
345. Bearing N 87° 23' 56" E for a distance of 60.17 feet, more or less, to a point; thence,
346. Bearing S 88° 36' 11" E for a distance of 56.03 feet, more or less, to a point; thence,
347. Bearing N 86° 11' 21" E for a distance of 41.08 feet, more or less, to a point; thence,
348. Bearing S 84° 48' 36" E for a distance of 30.18 feet, more or less, to a point; thence,
349. Bearing S 74° 45' 27" E for a distance of 31.15 feet, more or less, to a point; thence,
350. Bearing S 68° 12' 48" E for a distance of 29.42 feet, more or less, to a point; thence,
351. Bearing S 59° 03' 23" E for a distance of 39.82 feet, more or less, to a point; thence,
352. Bearing S 46° 25' 15" E for a distance of 39.60 feet, more or less, to a point; thence,

353. Bearing S 33° 11' 49" E for a distance of 42.42 feet, more or less, to a point; thence,
354. Bearing S 21° 03' 16" E for a distance of 38.03 feet, more or less, to a point; thence,
355. Bearing S 13° 34' 56" E for a distance of 40.73 feet, more or less, to a point; thence,
356. Bearing S 10° 18' 43" E for a distance of 45.79 feet, more or less, to a point; thence,
357. Bearing S 06° 29' 18" E for a distance of 60.45 feet, more or less, to a point; thence,
358. Bearing S 09° 00' 28" E for a distance of 78.36 feet, more or less, to a point; thence,
359. Bearing S 05° 42' 59" E for a distance of 27.44 feet, more or less, to a point; thence,
360. Bearing S 11° 19' 12" W for a distance of 27.84 feet, more or less, to a point; thence,
361. Bearing S 06° 50' 49" W for a distance of 34.37 feet, more or less, to a point; thence,
362. Bearing S 04° 46' 08" W for a distance of 32.87 feet, more or less, to a point; thence,
363. Bearing S 02° 12' 14" E for a distance of 35.52 feet, more or less, to a point; thence,
364. Bearing S 09° 10' 06" W for a distance of 42.86 feet, more or less, to a point; thence,
365. Bearing S 21° 15' 58" W for a distance of 26.37 feet, more or less, to a point; thence,
366. Bearing S 33° 02' 44" W for a distance of 32.57 feet, more or less, to a point; thence,
367. Bearing S 52° 36' 55" W for a distance of 29.23 feet, more or less, to a point; thence,
368. Bearing S 64° 27' 33" W for a distance of 34.83 feet, more or less, to a point; thence,
369. Bearing S 61° 34' 32" W for a distance of 37.28 feet, more or less, to a point; thence,
370. Bearing S 51° 58' 33" W for a distance of 39.89 feet, more or less, to a point; thence,
371. Bearing S 42° 31' 57" W for a distance of 44.46 feet, more or less, to a point; thence,
372. Bearing S 56° 50' 33" W for a distance of 42.43 feet, more or less, to a point; thence,
373. Bearing S 53° 59' 42" W for a distance of 37.15 feet, more or less, to a point; thence,
374. Bearing S 72° 54' 39" W for a distance of 37.16 feet, more or less, to a point; thence,
375. Bearing S 67° 32' 11" W for a distance of 42.87 feet, more or less, to a point; thence,
376. Bearing S 63° 57' 53" W for a distance of 68.42 feet, more or less, to a point; thence,
377. Bearing S 63° 27' 16" W for a distance of 76.36 feet, more or less, to a point; thence,
378. Bearing S 51° 55' 57" W for a distance of 64.21 feet, more or less, to a point; thence,
379. Bearing S 68° 01' 02" W for a distance of 46.55 feet, more or less, to a point; thence,
380. Bearing S 62° 02' 21" W for a distance of 49.49 feet, more or less, to a point; thence,
381. Bearing S 69° 14' 34" W for a distance of 42.37 feet, more or less, to a point; thence,
382. Bearing S 62° 07' 20" W for a distance of 52.55 feet, more or less, to a point; thence,
383. Bearing S 67° 29' 44" W for a distance of 60.63 feet, more or less, to a point; thence,
384. Bearing S 66° 59' 28" W for a distance of 59.37 feet, more or less, to a point; thence,
385. Bearing S 66° 37' 53" W for a distance of 55.06 feet, more or less, to a point; thence,
386. Bearing S 57° 52' 08" W for a distance of 56.46 feet, more or less, to a point; thence,
387. Bearing S 53° 09' 03" W for a distance of 61.46 feet, more or less, to a point; thence,
388. Bearing S 51° 34' 09" W for a distance of 59.29 feet, more or less, to a point; thence,
389. Bearing S 46° 55' 58" W for a distance of 57.97 feet, more or less, to a point; thence,
390. Bearing S 48° 50' 12" W for a distance of 58.07 feet, more or less, to a point; thence,
391. Bearing S 42° 43' 56" W for a distance of 48.32 feet, more or less, to a point; thence,
392. Bearing S 31° 26' 59" W for a distance of 57.60 feet, more or less, to a point; thence,
393. Bearing S 21° 49' 04" W for a distance of 66.17 feet, more or less, to a point; thence,
394. Bearing S 27° 50' 35" W for a distance of 55.58 feet, more or less, to a point; thence,
395. Bearing S 23° 43' 07" W for a distance of 61.13 feet, more or less, to a point; thence,
396. Bearing S 28° 19' 14" W for a distance of 60.48 feet, more or less, to a point; thence,
397. Bearing S 14° 59' 09" W for a distance of 53.56 feet, more or less, to a point; thence,
398. Bearing S 04° 46' 06" W for a distance of 49.31 feet, more or less, to a point; thence,

399. Bearing S 05° 11' 52" W for a distance of 45.23 feet, more or less, to a point; thence,
400. Bearing S 16° 16' 15" W for a distance of 34.13 feet, more or less, to a point; thence,
401. Bearing S 17° 50' 05" W for a distance of 40.15 feet, more or less, to a point; thence,
402. Bearing S 14° 02' 50" W for a distance of 33.77 feet, more or less, to a point; thence,
403. Bearing S 06° 43' 01" E for a distance of 23.37 feet, more or less, to a point; thence,
404. Bearing S 05° 42' 52" E for a distance of 41.16 feet, more or less, to a point; thence,
405. Bearing S 01° 54' 38" E for a distance of 40.97 feet, more or less, to a point; thence,
406. Bearing S 05° 42' 52" E for a distance of 41.16 feet, more or less, to a point; thence,
407. Bearing S 11° 19' 17" E for a distance of 41.76 feet, more or less, to a point; thence,
408. Bearing S 14° 02' 45" E for a distance of 45.03 feet, more or less, to a point; thence,
409. Bearing S 17° 00' 13" E for a distance of 51.39 feet, more or less, to a point; thence,
410. Bearing S 21° 23' 09" E for a distance of 67.44 feet, more or less, to a point; thence,
411. Bearing S 28° 56' 32" E for a distance of 69.75 feet, more or less, to a point; thence,
412. Bearing S 46° 56' 06" E for a distance of 42.90 feet, more or less, to a point; thence,
413. Bearing S 50° 32' 59" E for a distance of 39.18 feet, more or less, to a point; thence,
414. Bearing S 52° 40' 22" E for a distance of 42.53 feet, more or less, to a point; thence,
415. Bearing S 62° 52' 09" E for a distance of 39.00 feet, more or less, to a point; thence,
416. Bearing S 69° 05' 18" E for a distance of 32.39 feet, more or less, to a point; thence,
417. Bearing S 82° 52' 56" E for a distance of 35.87 feet, more or less, to a point; thence,
418. Bearing N 87° 08' 23" E for a distance of 53.46 feet, more or less, to a point; thence,
419. Bearing N 71° 34' 44" E for a distance of 42.21 feet, more or less, to a point; thence,
420. Bearing N 72° 48' 51" E for a distance of 39.12 feet, more or less, to a point; thence,
421. Bearing N 72° 00' 39" E for a distance of 37.43 feet, more or less, to a point; thence,
422. Bearing N 60° 16' 23" E for a distance of 28.69 feet, more or less, to a point; thence,
423. Bearing N 71° 51' 38" E for a distance of 57.12 feet, more or less, to a point; thence,
424. Bearing N 56° 57' 05" E for a distance of 45.65 feet, more or less, to a point; thence,
425. Bearing N 60° 16' 30" E for a distance of 43.04 feet, more or less, to a point; thence,
426. Bearing N 59° 24' 05" E for a distance of 50.66 feet, more or less, to a point; thence,
427. Bearing N 55° 23' 49" E for a distance of 45.41 feet, more or less, to a point; thence,
428. Bearing N 52° 07' 47" E for a distance of 61.96 feet, more or less, to a point; thence,
429. Bearing N 43° 35' 20" E for a distance of 50.34 feet, more or less, to a point; thence,
430. Bearing N 43° 17' 16" E for a distance of 41.53 feet, more or less, to a point; thence,
431. Bearing N 34° 02' 28" E for a distance of 42.92 feet, more or less, to a point; thence,
432. Bearing N 25° 45' 28" E for a distance of 55.29 feet, more or less, to a point; thence,
433. Bearing N 37° 02' 01" E for a distance of 72.40 feet, more or less, to a point; thence,
434. Bearing N 36° 16' 32" E for a distance of 49.63 feet, more or less, to a point; thence,
435. Bearing N 29° 33' 29" E for a distance of 61.34 feet, more or less, to a point; thence,
436. Bearing N 43° 28' 32" E for a distance of 23.28 feet, more or less, to a point; thence,
437. Bearing N 42° 58' 40" E for a distance of 35.25 feet, more or less, to a point; thence,
438. Bearing N 61° 43' 06" E for a distance of 26.27 feet, more or less, to a point; thence,
439. Bearing N 76° 49' 10" E for a distance of 58.49 feet, more or less, to a point; thence,
440. Bearing S 89° 25' 37" E for a distance of 89.00 feet, more or less, to a point; thence,
441. Bearing S 68° 24' 05" E for a distance of 50.73 feet, more or less, to a point; thence,
442. Bearing S 65° 14' 34" E for a distance of 76.44 feet, more or less, to a point; thence,
443. Bearing S 54° 22' 55" E for a distance of 58.02 feet, more or less, to a point; thence,
444. Bearing S 46° 36' 51" E for a distance of 45.31 feet, more or less, to a point; thence,

445. Bearing S 57° 21' 30" E for a distance of 41.22 feet, more or less, to a point; thence,
446. Bearing S 55° 51' 42" E for a distance of 30.11 feet, more or less, to a point; thence,
447. Bearing S 27° 32' 39" E for a distance of 71.20 feet, more or less, to a point; thence,
448. Bearing S 19° 30' 01" E for a distance of 61.32 feet, more or less, to a point; thence,
449. Bearing S 17° 06' 58" E for a distance of 48.38 feet, more or less, to a point; thence,
450. Bearing S 16° 58' 50" E for a distance of 54.85 feet, more or less, to a point; thence,
451. Bearing S 11° 39' 49" E for a distance of 54.41 feet, more or less, to a point; thence,
452. Bearing S 03° 14' 33" E for a distance of 47.20 feet, more or less, to a point; thence,
453. Bearing S 16° 50' 03" E for a distance of 39.95 feet, more or less, to a point; thence,
454. Bearing S 11° 32' 36" E for a distance of 44.47 feet, more or less, to a point; thence,
455. Bearing S 13° 15' 04" E for a distance of 62.12 feet, more or less, to a point; thence,
456. Bearing S 12° 14' 09" E for a distance of 54.59 feet, more or less, to a point; thence,
457. Bearing S 08° 28' 33" E for a distance of 42.25 feet, more or less, to a point; thence,
458. Bearing S 02° 51' 54" W for a distance of 53.42 feet, more or less, to a point; thence,
459. Bearing S 07° 43' 43" E for a distance of 52.94 feet, more or less, to a point; thence,
460. Bearing S 14° 05' 03" E for a distance of 33.61 feet, more or less, to a point; thence,
461. Bearing S 14° 21' 37" E for a distance of 39.47 feet, more or less, to a point; thence,
462. Bearing S 01° 06' 10" E for a distance of 46.25 feet, more or less, to a point; thence,
463. Bearing S 01° 56' 36" W for a distance of 52.49 feet, more or less, to a point; thence,
464. Bearing S 05° 04' 58" E for a distance of 40.17 feet, more or less, to a point; thence,
465. Bearing S 16° 48' 41" E for a distance of 49.23 feet, more or less, to a point; thence,
466. Bearing S 35° 41' 52" E for a distance of 42.70 feet, more or less, to a point; thence,
467. Bearing S 13° 44' 49" E for a distance of 41.19 feet, more or less, to a point; thence,
468. Bearing S 13° 24' 22" E for a distance of 57.53 feet, more or less, to a point; thence,
469. Bearing S 05° 57' 05" E for a distance of 85.83 feet, more or less, to a point; thence,
470. Bearing S 01° 19' 58" W for a distance of 76.49 feet, more or less, to a point; thence,
471. Bearing S 06° 35' 16" W for a distance of 69.82 feet, more or less, to a point; thence,
472. Bearing S 09° 05' 49" W for a distance of 45.03 feet, more or less, to a point; thence,
473. Bearing S 18° 26' 55" W for a distance of 42.18 feet, more or less, to a point; thence,
474. Bearing S 29° 04' 30" W for a distance of 27.47 feet, more or less, to a point; thence,
475. Bearing S 17° 00' 13" W for a distance of 33.47 feet, more or less, to a point; thence,
476. Bearing S 22° 29' 37" W for a distance of 27.91 feet, more or less, to a point; thence,
477. Bearing S 25° 52' 57" W for a distance of 35.55 feet, more or less, to a point; thence,
478. Bearing S 43° 30' 56" W for a distance of 47.82 feet, more or less, to a point; thence,
479. Bearing S 45° 01' 24" W for a distance of 41.52 feet, more or less, to a point; thence,
480. Bearing S 31° 43' 15" W for a distance of 35.54 feet, more or less, to a point; thence,
481. Bearing S 14° 02' 49" W for a distance of 40.33 feet, more or less, to a point; thence,
482. Bearing S 18° 56' 22" W for a distance of 32.90 feet, more or less, to a point; thence,
483. Bearing S 28° 24' 46" W for a distance of 37.41 feet, more or less, to a point; thence,
484. Bearing S 35° 40' 40" W for a distance of 50.35 feet, more or less, to a point; thence,
485. Bearing S 50° 22' 42" W for a distance of 40.44 feet, more or less, to a point; thence,
486. Bearing S 62° 27' 53" W for a distance of 46.17 feet, more or less, to a point; thence,
487. Bearing S 62° 43' 06" W for a distance of 31.04 feet, more or less, to a point; thence,
488. Bearing S 69° 47' 24" W for a distance of 36.04 feet, more or less, to a point; thence,
489. Bearing S 77° 49' 51" W for a distance of 38.23 feet, more or less, to a point; thence,
490. Bearing S 68° 53' 28" W for a distance of 41.97 feet, more or less, to a point; thence,

491. Bearing S 69° 14' 34" W for a distance of 55.20 feet, more or less, to a point; thence,
492. Bearing S 74° 29' 16" W for a distance of 66.50 feet, more or less, to a point; thence,
493. Bearing S 84° 13' 49" W for a distance of 79.61 feet, more or less, to a point; thence,
494. Bearing S 88° 25' 53" W for a distance of 64.99 feet, more or less, to a point; thence,
495. Bearing N 83° 57' 00" W for a distance of 59.06 feet, more or less, to a point; thence,
496. Bearing N 79° 16' 11" W for a distance of 52.53 feet, more or less, to a point; thence,
497. Bearing N 74° 19' 54" W for a distance of 52.68 feet, more or less, to a point; thence,
498. Bearing N 59° 26' 07" W for a distance of 38.87 feet, more or less, to a point; thence,
499. Bearing N 54° 04' 45" W for a distance of 43.96 feet, more or less, to a point; thence,
500. Bearing N 23° 58' 46" W for a distance of 52.55 feet, more or less, to a point; thence,
501. Bearing N 03° 54' 09" W for a distance of 39.22 feet, more or less, to a point; thence,
502. Bearing N 04° 05' 27" W for a distance of 37.44 feet, more or less, to a point; thence,
503. Bearing N 11° 36' 02" E for a distance of 35.40 feet, more or less, to a point; thence,
504. Bearing N 10° 05' 22" E for a distance of 40.64 feet, more or less, to a point; thence,
505. Bearing N 26° 35' 01" E for a distance of 31.82 feet, more or less, to a point; thence,
506. Bearing N 25° 45' 28" E for a distance of 55.29 feet, more or less, to a point; thence,
507. Bearing N 33° 17' 51" E for a distance of 34.04 feet, more or less, to a point; thence,
508. Bearing N 40° 29' 03" E for a distance of 39.75 feet, more or less, to a point; thence,
509. Bearing N 30° 59' 07" E for a distance of 36.30 feet, more or less, to a point; thence,
510. Bearing N 41° 12' 29" E for a distance of 28.37 feet, more or less, to a point; thence,
511. Bearing N 31° 17' 04" E for a distance of 29.13 feet, more or less, to a point; thence,
512. Bearing N 25° 48' 43" E for a distance of 20.65 feet, more or less, to a point; thence,
513. Bearing N 14° 17' 32" E for a distance of 50.47 feet, more or less, to a point; thence,
514. Bearing N 05° 42' 51" E for a distance of 35.75 feet, more or less, to a point; thence,
515. Bearing N 00° 00' 00" E for a distance of 41.79 feet, more or less, to a point; thence,
516. Bearing N 07° 07' 48" W for a distance of 43.01 feet, more or less, to a point; thence,
517. Bearing N 08° 49' 41" W for a distance of 52.19 feet, more or less, to a point; thence,
518. Bearing N 06° 12' 27" W for a distance of 41.14 feet, more or less, to a point; thence,
519. Bearing N 11° 04' 42" W for a distance of 41.68 feet, more or less, to a point; thence,
520. Bearing N 19° 33' 11" W for a distance of 29.25 feet, more or less, to a point; thence,
521. Bearing N 20° 20' 14" W for a distance of 25.61 feet, more or less, to a point; thence,
522. Bearing N 40° 50' 16" W for a distance of 25.86 feet, more or less, to a point; thence,
523. Bearing N 53° 23' 17" W for a distance of 43.24 feet, more or less, to a point; thence,
524. Bearing N 42° 09' 43" W for a distance of 25.19 feet, more or less, to a point; thence,
525. Bearing N 41° 38' 34" W for a distance of 81.82 feet, more or less, to a point; thence,
526. Bearing N 36° 22' 10" W for a distance of 58.53 feet, more or less, to a point; thence,
527. Bearing N 51° 56' 01" W for a distance of 41.82 feet, more or less, to a point; thence,
528. Bearing N 55° 51' 42" W for a distance of 60.21 feet, more or less, to a point; thence,
529. Bearing N 66° 49' 12" W for a distance of 40.66 feet, more or less, to a point; thence,
530. Bearing N 72° 13' 40" W for a distance of 49.53 feet, more or less, to a point; thence,
531. Bearing N 84° 17' 38" W for a distance of 44.72 feet, more or less, to a point; thence,
532. Bearing S 87° 33' 57" W for a distance of 41.86 feet, more or less, to a point; thence,
533. Bearing S 64° 33' 15" W for a distance of 20.70 feet, more or less, to a point; thence,
534. Bearing S 47° 30' 47" W for a distance of 28.96 feet, more or less, to a point; thence,
535. Bearing S 11° 38' 31" W for a distance of 30.87 feet, more or less, to a point; thence,
536. Bearing S 14° 55' 20" W for a distance of 40.35 feet, more or less, to a point; thence,

537. Bearing S 21° 35' 19" W for a distance of 16.80 feet, more or less, to a point; thence,
538. Bearing S 47° 11' 01" W for a distance of 27.26 feet, more or less, to a point; thence,
539. Bearing S 48° 26' 52" W for a distance of 29.75 feet, more or less, to a point; thence,
540. Bearing S 49° 53' 23" W for a distance of 18.43 feet, more or less, to a point; thence,
541. Bearing S 25° 39' 35" W for a distance of 20.15 feet, more or less, to a point; thence,
542. Bearing S 00° 00' 01" W for a distance of 22.52 feet, more or less, to a point; thence,
543. Bearing S 24° 04' 26" E for a distance of 22.28 feet, more or less, to a point; thence,
544. Bearing S 48° 23' 41" E for a distance of 8.75 feet, more or less, to a point; thence,
545. Bearing S 45° 23' 26" E for a distance of 34.85 feet, more or less, to a point; thence,
546. Bearing S 61° 31' 22" E for a distance of 29.89 feet, more or less, to a point; thence,
547. Bearing S 44° 05' 02" E for a distance of 32.37 feet, more or less, to a point; thence,
548. Bearing S 21° 31' 06" E for a distance of 26.61 feet, more or less, to a point; thence,
549. Bearing S 04° 31' 02" E for a distance of 28.59 feet, more or less, to a point; thence,
550. Bearing S 02° 17' 30" W for a distance of 37.53 feet, more or less, to a point; thence,
551. Bearing S 03° 59' 39" E for a distance of 32.33 feet, more or less, to a point; thence,
552. Bearing S 07° 15' 28" E for a distance of 41.59 feet, more or less, to a point; thence,
553. Bearing S 14° 20' 01" E for a distance of 36.39 feet, more or less, to a point; thence,
554. Bearing S 07° 03' 28" W for a distance of 73.31 feet, more or less, to a point; thence,
555. Bearing S 03° 44' 03" W for a distance of 34.58 feet, more or less, to a point; thence,
556. Bearing S 02° 47' 03" E for a distance of 30.74 feet, more or less, to a point; thence,
557. Bearing S 02° 10' 35" W for a distance of 59.30 feet, more or less, to a point; thence,
558. Bearing S 07° 54' 45" E for a distance of 54.53 feet, more or less, to a point; thence,
559. Bearing S 03° 10' 51" W for a distance of 40.57 feet, more or less, to a point; thence,
560. Bearing S 13° 00' 31" W for a distance of 20.01 feet, more or less, to a point; thence,
561. Bearing S 10° 37' 39" W for a distance of 36.63 feet, more or less, to a point; thence,
562. Bearing S 13° 38' 12" W for a distance of 25.47 feet, more or less, to a point; thence,
563. Bearing S 05° 23' 30" E for a distance of 39.93 feet, more or less, to a point; thence,
564. Bearing S 07° 36' 08" E for a distance of 34.05 feet, more or less, to a point; thence,
565. Bearing S 07° 30' 12" E for a distance of 28.75 feet, more or less, to a point; thence,
566. Bearing S 03° 14' 32" W for a distance of 54.03 feet, more or less, to a point; thence,
567. Bearing S 09° 28' 12" W for a distance of 31.94 feet, more or less, to a point; thence,
568. Bearing S 14° 02' 51" E for a distance of 52.58 feet, more or less, to a point; thence,
569. Bearing S 16° 20' 53" E for a distance of 45.34 feet, more or less, to a point; thence,
570. Bearing S 07° 30' 10" E for a distance of 28.75 feet, more or less, to a point; thence,
571. Bearing S 01° 20' 02" W for a distance of 32.26 feet, more or less, to a point; thence,
572. Bearing S 04° 31' 03" E for a distance of 28.59 feet, more or less, to a point; thence,
573. Bearing S 04° 45' 59" W for a distance of 18.06 feet, more or less, to a point; thence,
574. Bearing S 70° 55' 22" W for a distance of 20.65 feet, more or less, to a point; thence,
575. Bearing N 67° 54' 25" W for a distance of 25.93 feet, more or less, to a point; thence,
576. Bearing N 51° 43' 52" W for a distance of 18.17 feet, more or less, to a point; thence,
577. Bearing N 29° 04' 31" W for a distance of 15.45 feet, more or less, to a point; thence,
578. Bearing N 17° 15' 14" W for a distance of 22.78 feet, more or less, to a point; thence,
579. Bearing N 12° 32' 20" W for a distance of 20.75 feet, more or less, to a point; thence,
580. Bearing N 15° 26' 17" W for a distance of 22.57 feet, more or less, to a point; thence,
581. Bearing N 11° 41' 42" W for a distance of 22.21 feet, more or less, to a point; thence,
582. Bearing N 19° 40' 14" W for a distance of 22.30 feet, more or less, to a point; thence,

583. Bearing N 13° 08' 30" W for a distance of 23.11 feet, more or less, to a point; thence,
584. Bearing N 18° 59' 09" W for a distance of 25.38 feet, more or less, to a point; thence,
585. Bearing N 19° 59' 49" W for a distance of 17.56 feet, more or less, to a point; thence,
586. Bearing N 22° 11' 01" W for a distance of 21.87 feet, more or less, to a point; thence,
587. Bearing N 24° 55' 14" W for a distance of 23.16 feet, more or less, to a point; thence,
588. Bearing N 42° 54' 09" W for a distance of 14.34 feet, more or less, to a point; thence,
589. Bearing N 67° 50' 56" W for a distance of 21.88 feet, more or less, to a point; thence,
590. Bearing N 74° 04' 06" W for a distance of 21.86 feet, more or less, to a point; thence,
591. Bearing N 85° 31' 10" W for a distance of 38.40 feet, more or less, to a point; thence,
592. Bearing S 78° 28' 32" W for a distance of 37.54 feet, more or less, to a point; thence,
593. Bearing S 84° 23' 11" W for a distance of 46.01 feet, more or less, to a point; thence,
594. Bearing N 86° 48' 48" W for a distance of 17.75 feet, more or less, to a point; thence,
595. Bearing N 90° 00' 00" W for a distance of 40.54 feet, more or less, to a point; thence,
596. Bearing N 88° 31' 57" W for a distance of 29.29 feet, more or less, to a point; thence,
597. Bearing S 85° 42' 53" W for a distance of 30.11 feet, more or less, to a point; thence,
598. Bearing S 71° 07' 41" W for a distance of 30.15 feet, more or less, to a point; thence,
599. Bearing S 62° 48' 09" W for a distance of 29.54 feet, more or less, to a point; thence,
600. Bearing S 61° 05' 34" W for a distance of 32.59 feet, more or less, to a point; thence,
601. Bearing S 64° 33' 17" W for a distance of 34.91 feet, more or less, to a point; thence,
602. Bearing S 53° 38' 16" W for a distance of 35.42 feet, more or less, to a point; thence,
603. Bearing S 51° 51' 53" W for a distance of 26.72 feet, more or less, to a point; thence,
604. Bearing S 43° 10' 32" W for a distance of 32.91 feet, more or less, to a point; thence,
605. Bearing S 56° 19' 52" W for a distance of 35.18 feet, more or less, to a point; thence,
606. Bearing S 55° 23' 52" W for a distance of 38.30 feet, more or less, to a point; thence,
607. Bearing S 52° 08' 49" W for a distance of 34.23 feet, more or less, to a point; thence,
608. Bearing S 41° 12' 29" W for a distance of 31.91 feet, more or less, to a point; thence,
609. Bearing S 49° 44' 40" W for a distance of 69.36 feet, more or less, to a point; thence,
610. Bearing S 61° 39' 01" W for a distance of 42.65 feet, more or less, to a point; thence,
611. Bearing S 51° 34' 04" W for a distance of 32.58 feet, more or less, to a point; thence,
612. Bearing S 44° 08' 34" W for a distance of 34.49 feet, more or less, to a point; thence,
613. Bearing S 30° 35' 57" W for a distance of 38.34 feet, more or less, to a point; thence,
614. Bearing S 30° 45' 21" W for a distance of 32.30 feet, more or less, to a point; thence,
615. Bearing S 35° 46' 29" W for a distance of 23.11 feet, more or less, to a point; thence,
616. Bearing S 46° 08' 47" W for a distance of 27.07 feet, more or less, to a point; thence,
617. Bearing S 43° 25' 56" W for a distance of 38.22 feet, more or less, to a point; thence,
618. Bearing S 32° 38' 22" W for a distance of 22.27 feet, more or less, to a point; thence,
619. Bearing S 32° 29' 35" W for a distance of 29.35 feet, more or less, to a point; thence,
620. Bearing S 42° 54' 09" W for a distance of 28.67 feet, more or less, to a point; thence,
621. Bearing S 46° 08' 43" W for a distance of 27.07 feet, more or less, to a point; thence,
622. Bearing S 44° 29' 38" W for a distance of 34.67 feet, more or less, to a point; thence,
623. Bearing S 48° 50' 15" W for a distance of 23.93 feet, more or less, to a point; thence,
624. Bearing S 58° 24' 46" W for a distance of 22.91 feet, more or less, to a point; thence,
625. Bearing S 43° 41' 23" W for a distance of 22.82 feet, more or less, to a point; thence,
626. Bearing S 19° 33' 08" W for a distance of 24.67 feet, more or less, to a point; thence,
627. Bearing S 03° 45' 11" W for a distance of 45.85 feet, more or less, to a point; thence,
628. Bearing S 08° 53' 09" E for a distance of 48.59 feet, more or less, to a point; thence,

629. Bearing S 20° 14' 24" E for a distance of 45.57 feet, more or less, to a point; thence,
630. Bearing S 33° 21' 46" E for a distance of 34.13 feet, more or less, to a point; thence,
631. Bearing S 66° 49' 11" E for a distance of 34.30 feet, more or less, to a point; thence,
632. Bearing S 47° 50' 07" E for a distance of 32.41 feet, more or less, to a point; thence,
633. Bearing S 52° 43' 12" E for a distance of 39.63 feet, more or less, to a point; thence,
634. Bearing S 42° 12' 21" E for a distance of 32.40 feet, more or less, to a point; thence,
635. Bearing S 22° 51' 01" E for a distance of 30.93 feet, more or less, to a point; thence,
636. Bearing S 10° 18' 48" E for a distance of 25.16 feet, more or less, to a point; thence,
637. Bearing S 04° 03' 32" W for a distance of 52.50 feet, more or less, to a point; thence,
638. Bearing S 13° 00' 17" W for a distance of 30.02 feet, more or less, to a point; thence,
639. Bearing S 04° 24' 08" W for a distance of 29.34 feet, more or less, to a point; thence,
640. Bearing S 00° 00' 00" E for a distance of 33.75 feet, more or less, to a point; thence,
641. Bearing S 00° 00' 00" W for a distance of 30.00 feet, more or less, to a point; thence,
642. Bearing S 00° 00' 00" W for a distance of 18.75 feet, more or less, to a point; thence,
643. Bearing S 07° 16' 49" W for a distance of 15.68 feet, more or less, to a point; thence,
644. Bearing S 07° 16' 51" W for a distance of 19.86 feet, more or less, to a point; thence,
645. Bearing S 88° 36' 03" W for a distance of 142.48 feet, more or less, to a point;
thence,
646. Bearing S 02° 02' 51" E for a distance of 27.62 feet, more or less, to a point; thence,
647. Bearing S 87° 50' 26" W for a distance of 52.33 feet, more or less, to a point; thence,
648. Bearing N 79° 45' 42" W for a distance of 4.25 feet, more or less, to a point; thence,
649. Bearing N 69° 54' 00" W for a distance of 4.25 feet, more or less, to a point; thence,
650. Bearing N 60° 02' 18" W for a distance of 4.25 feet, more or less, to a point; thence,
651. Bearing N 50° 10' 36" W for a distance of 4.25 feet, more or less, to a point; thence,
652. Bearing N 40° 18' 54" W for a distance of 4.25 feet, more or less, to a point; thence,
653. Bearing N 30° 27' 12" W for a distance of 4.25 feet, more or less, to a point; thence,
654. Bearing N 20° 35' 30" W for a distance of 4.25 feet, more or less, to a point; thence,
655. Bearing N 10° 43' 48" W for a distance of 4.25 feet, more or less, to a point; thence,
656. Bearing N 00° 52' 06" W for a distance of 4.25 feet, more or less, to a point; thence,
657. Bearing N 08° 59' 36" E for a distance of 4.25 feet, more or less, to a point; thence,
658. Bearing N 01° 44' 45" W for a distance of 25.03 feet, more or less, to a point; thence,
659. Bearing N 89° 15' 39" W for a distance of 241.27 feet, more or less, to a point;
thence,
660. Bearing S 00° 00' 00" W for a distance of 78.87 feet, more or less, to a point; thence,
661. Bearing S 88° 17' 48" W for a distance of 174.57 feet, more or less, to a point;
thence,
662. Bearing S 88° 27' 21" W for a distance of 38.44 feet, more or less, to a point; thence,
663. Bearing N 87° 08' 28" W for a distance of 62.39 feet, more or less, to a point; thence,
664. Bearing N 87° 21' 36" W for a distance of 67.58 feet, more or less, to a point; thence,
665. Bearing S 88° 40' 09" W for a distance of 89.35 feet, more or less, to a point; thence,
666. Bearing S 87° 05' 27" W for a distance of 61.36 feet, more or less, to a point; thence,
667. Bearing S 87° 59' 33" W for a distance of 59.24 feet, more or less, to a point; thence,
668. Bearing S 88° 11' 32" W for a distance of 98.72 feet, more or less, to a point; thence,
669. Bearing N 88° 25' 59" W for a distance of 78.19 feet, more or less, to a point; thence,
670. Bearing N 89° 21' 24" W for a distance of 63.67 feet, more or less, to a point; thence,
671. Bearing S 88° 44' 30" W for a distance of 32.56 feet, more or less, to a point; thence,

672. Bearing S 88° 41' 02" W for a distance of 31.13 feet, more or less, to a point; thence,
673. Bearing S 81° 19' 16" W for a distance of 26.05 feet, more or less, to a point; thence,
674. Bearing S 79° 25' 35" W for a distance of 33.11 feet, more or less, to a point; thence,
675. Bearing S 81° 18' 42" W for a distance of 30.76 feet, more or less, to a point; thence,
676. Bearing S 75° 41' 51" W for a distance of 22.91 feet, more or less, to a point; thence,
677. Bearing S 43° 49' 44" W for a distance of 14.94 feet, more or less, to a point; thence,
678. Bearing S 45° 56' 00" W for a distance of 15.93 feet, more or less, to a point; thence,
679. Bearing S 47° 36' 52" W for a distance of 25.39 feet, more or less, to a point; thence,
680. Bearing S 40° 56' 17" W for a distance of 41.35 feet, more or less, to a point; thence,
681. Bearing S 60° 57' 52" W for a distance of 42.90 feet, more or less, to a point; thence,
682. Bearing S 70° 49' 42" W for a distance of 33.89 feet, more or less, to a point; thence,
683. Bearing S 01° 38' 32" E for a distance of 68.78 feet, more or less, to a point; thence,
684. Bearing S 00° 36' 37" E for a distance of 2552.09 feet, more or less, to a point;
thence,
685. Bearing S 89° 12' 08" W for a distance of 2592.23 feet, more or less, to a point;
thence,
686. Bearing N 79° 50' 10" W for a distance of 156.73 feet, more or less, to a point;
thence,
687. Bearing S 89° 30' 26" W for a distance of 684.49 feet, more or less, to a point;
thence,
688. Bearing S 89° 20' 11" W for a distance of 655.20 feet, more or less, to a point;
thence,
689. Bearing S 89° 23' 45" W for a distance of 564.10 feet, more or less, to a point;
thence,
690. Bearing S 89° 28' 56" W for a distance of 825.40 feet, more or less, to a point;
thence,
691. Bearing N 00° 28' 08" W for a distance of 1016.77 feet, more or less, to a point;
thence,
692. Bearing N 00° 29' 39" W for a distance of 1732.19 feet, more or less, to a point;
thence,
693. Bearing N 87° 28' 30" W for a distance of 63.62 feet, more or less, to a point; thence,
694. Bearing N 00° 29' 59" E for a distance of 886.56 feet, more or less, to a point;
thence,
695. Bearing N 00° 24' 38" E for a distance of 401.15 feet, more or less, to a point;
thence,
696. Bearing N 00° 15' 39" E for a distance of 101.31 feet, more or less, to a point;
thence,
697. Bearing N 00° 15' 39" E for a distance of 702.78 feet, more or less, to a point;
thence,
698. Bearing N 00° 11' 08" W for a distance of 117.69 feet, more or less, to a point;
thence,
699. Bearing N 00° 11' 08" W for a distance of 502.58 feet, more or less, to a point;
thence,
700. Bearing N 89° 28' 57" E for a distance of 280.85 feet, more or less, to a point;
thence,

701. Bearing N 89° 28' 57" E for a distance of 265.50 feet, more or less, to a point;
thence,
702. Bearing N 00° 00' 00" E for a distance of 621.29 feet, more or less, to a point;
thence,
703. Bearing S 89° 36' 26" E for a distance of 1058.36 feet, more or less, to a point;
thence,
704. Bearing N 00° 49' 51" W for a distance of 221.55 feet, more or less, to a point;
thence,
705. Bearing N 00° 49' 45" W for a distance of 477.01 feet, more or less, to a point;
thence,
706. Bearing S 89° 11' 36" W for a distance of 228.16 feet, more or less, to a point;
thence,
707. Bearing N 00° 47' 45" W for a distance of 1016.72 feet, more or less, to a point;
thence,
708. Bearing N 89° 02' 45" E for a distance of 192.82 feet, more or less, to a point;
thence,
709. Bearing N 00° 53' 10" W for a distance of 563.72 feet, more or less, to the Point of
Beginning.

Lima Water District No. 5, as described above, contains approximately 4,705.59 acres of land.

All as shown on a map prepared by CPL, entitled "Town of Lima Proposed Water District No. 5", dated November 26, 2024.