

Official Minutes

A Special Meeting of the Town Board of the Town of Lima, County of Livingston and the State of New York was held at the Town Hall, 7329 East Main Street, Lima, New York, on the 9th day of January 2025 at 8AM. Notice was printed in the Mendon-Honeoye Falls-Lima Sentinel.

Present: Supervisor, Michael Falk
Councilperson, Bill Carey
Councilperson, Mark Petroski
Councilperson, Ron Blodgett
Councilperson, Steve Werner
Town Clerk, Jennifer Heim
Town Attorney, Jim Campbell

Guest(s):

Supervisor Falk called the meeting to order at 8:00AM, with the Pledge to the Flag.

Approval of the Agenda

Upon motion by Councilperson Carey to approve the agenda as distributed, seconded by Councilperson Petroski, the vote was unanimous.

Set the Public Hearing

Upon motion by councilperson Werner to set the public hearing for February 11th at 6:30PM, to receive comment on the formation of the Town of Lima Water District No. 5, pursuant to the Resolution and Order prepared by Attorney Campbell pursuant to New York State Town Law §209-d (see attached for complete document text) seconded by Councilperson Petroski, the vote went as follows:

CARRIED Ayes: 5 Falk, Carey, Petroski, Blodgett, Werner
Nays: 0

Motion by Councilperson Werner to adjourn at 8:02AM, seconded by Councilperson Petroski, the vote was unanimous.

Respectfully Submitted by:

Jennifer Heim, Town Clerk

TOWN OF LIMA

7329 East Main Street, Lima NY 14485

RESOLUTION AND ORDER for Legal Notice of Public Hearing to Receive Comment on the Formation of the Town of Lima Water District No. 5 pursuant to New York State Town Law §209 – d

WHEREAS, the Town Board of the Town of Lima desires under Article 12-A of the New York State Town Law to create the Town of Lima Water District No. 5, which would include certain real property located wholly in the Town of Lima, County of Livingston and State of New York; and

WHEREAS, the Town requested that the Town Engineer produce a Map, Plan and Report to provide the details of the improvements and the costs of such improvements to take place within the Town of Lima Water District No. 5; and

WHEREAS, the Town Engineer has caused such Map, Plan and Report to be prepared and delivered to the Town Board and the Town Clerk of the Town of Lima; and

WHEREAS, by resolution dated and approved on January 7, 2025, such Map, Plan and Report was accepted by the Town Board of the Town of Lima and the Map, Plan and Report was filed in the Town Clerk's Office on January 7, 2025; and

WHEREAS, the real property that will be located in the district is described in the Map, Plan and Report attached hereto and filed in the Lima Town Clerk's Office and bounds of the proposed district are more particularly described as follows:

TOWN OF LIMA WATER DISTRICT NO. 5

All that tract or parcel of land situate in the Town of Lima, County of Livingston, State of New York, being described as follows:

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1070575.0980' and whose Easting is 1407673.7616'; thence,

- 1. Bearing S 76° 38' 20" W for a distance of 137.05 feet, more or less, to a point; thence,**
- 2. Bearing S 76° 38' 20" W for a distance of 67.09 feet, more or less, to a point; thence,**
- 3. Bearing S 74° 38' 10" W for a distance of 173.88 feet, more or less, to a point; thence,**

4. Bearing S 72° 48' 44" W for a distance of 106.73 feet, more or less, to a point; thence,
5. Bearing S 01° 00' 04" W for a distance of 26.42 feet, more or less, to a point; thence,
6. Bearing S 01° 00' 03" W for a distance of 400.84 feet, more or less, to a point; thence,
7. Bearing S 01° 18' 07" W for a distance of 1080.42 feet, more or less, to a point; thence,
8. Bearing S 90° 00' 00" W for a distance of 233.93 feet, more or less, to a point; thence,
9. Bearing S 89° 52' 18" W for a distance of 411.56 feet, more or less, to a point; thence,
10. Bearing S 00° 40' 18" E for a distance of 323.95 feet, more or less, to a point; thence,
11. Bearing S 00° 33' 05" E for a distance of 192.76 feet, more or less, to a point; thence,
12. Bearing S 00° 41' 58" E for a distance of 151.99 feet, more or less, to a point; thence,
13. Bearing S 00° 29' 10" W for a distance of 218.70 feet, more or less, to a point; thence,
14. Bearing S 01° 12' 35" E for a distance of 179.50 feet, more or less, to a point; thence,
15. Bearing S 02° 19' 25" E for a distance of 137.26 feet, more or less, to a point; thence,
16. Bearing S 00° 44' 41" E for a distance of 142.72 feet, more or less, to a point; thence,
17. Bearing S 89° 35' 18" W for a distance of 102.29 feet, more or less, to a point; thence,
18. Bearing S 35° 52' 10" W for a distance of 478.00 feet, more or less, to a point; thence,
19. Bearing S 25° 26' 44" W for a distance of 22.89 feet, more or less, to a point; thence,
20. Bearing S 25° 26' 39" W for a distance of 102.31 feet, more or less, to a point; thence,
21. Bearing S 15° 45' 09" W for a distance of 282.18 feet, more or less, to a point; thence,
22. Bearing S 01° 00' 07" W for a distance of 353.32 feet, more or less, to a point; thence,
23. Bearing S 88° 57' 08" E for a distance of 124.77 feet, more or less, to a point; thence,
24. Bearing S 88° 52' 24" E for a distance of 123.99 feet, more or less, to a point; thence,
25. Bearing S 00° 07' 49" E for a distance of 204.68 feet, more or less, to a point; thence,
26. Bearing S 00° 00' 00" W for a distance of 71.73 feet, more or less, to a point; thence,
27. Bearing S 00° 21' 20" E for a distance of 199.12 feet, more or less, to a point; thence,
28. Bearing S 00° 49' 22" E for a distance of 201.70 feet, more or less, to a point; thence,
29. Bearing N 88° 40' 14" W for a distance of 488.78 feet, more or less, to a point; thence,
30. Bearing S 12° 54' 31" E for a distance of 389.68 feet, more or less, to a point; thence,
31. Bearing S 71° 05' 00" W for a distance of 119.00 feet, more or less, to a point; thence,
32. Bearing S 87° 39' 07" W for a distance of 106.01 feet, more or less, to a point; thence,
33. Bearing S 00° 12' 05" E for a distance of 72.77 feet, more or less, to a point; thence,
34. Bearing N 88° 52' 17" W for a distance of 745.88 feet, more or less, to a point; thence,
35. Bearing N 88° 46' 08" W for a distance of 453.19 feet, more or less, to a point; thence,
36. Bearing N 88° 26' 07" W for a distance of 421.05 feet, more or less, to a point; thence,
37. Bearing N 88° 35' 23" W for a distance of 154.87 feet, more or less, to a point; thence,
38. Bearing S 00° 26' 10" W for a distance of 328.04 feet, more or less, to a point; thence,
39. Bearing S 89° 19' 13" W for a distance of 391.70 feet, more or less, to a point; thence,
40. Bearing N 00° 49' 18" E for a distance of 564.26 feet, more or less, to a point; thence,
41. Bearing N 00° 49' 18" E for a distance of 268.74 feet, more or less, to a point; thence,
42. Bearing S 89° 44' 59" W for a distance of 19.41 feet, more or less, to a point; thence,
43. Bearing S 89° 44' 59" W for a distance of 149.67 feet, more or less, to a point; thence,
44. Bearing S 89° 15' 41" W for a distance of 168.84 feet, more or less, to a point; thence,
45. Bearing N 00° 23' 09" E for a distance of 513.46 feet, more or less, to a point; thence,
46. Bearing S 88° 45' 52" W for a distance of 352.91 feet, more or less, to a point; thence,
47. Bearing N 01° 02' 24" W for a distance of 1081.10 feet, more or less, to a point; thence,
48. Bearing S 88° 47' 46" E for a distance of 2027.87 feet, more or less, to a point; thence,
49. Bearing N 00° 18' 35" E for a distance of 343.82 feet, more or less, to a point; thence,

50. Bearing N 00° 20' 07" E for a distance of 159.21 feet, more or less, to a point; thence,
51. Bearing N 64° 14' 50" E for a distance of 30.00 feet, more or less, to a point; thence,
52. Bearing N 00° 16' 30" E for a distance of 118.71 feet, more or less, to a point; thence,
53. Bearing N 00° 23' 44" W for a distance of 277.30 feet, more or less, to a point; thence,
54. Bearing N 00° 25' 22" W for a distance of 269.73 feet, more or less, to a point; thence,
55. Bearing N 00° 23' 21" W for a distance of 30.03 feet, more or less, to a point; thence,
56. Bearing N 89° 02' 11" E for a distance of 318.76 feet, more or less, to a point; thence,
57. Bearing N 00° 07' 25" E for a distance of 169.58 feet, more or less, to a point; thence,
58. Bearing N 00° 15' 42" W for a distance of 228.16 feet, more or less, to a point; thence,
59. Bearing N 00° 06' 20" E for a distance of 255.04 feet, more or less, to a point; thence,
60. Bearing N 00° 20' 41" E for a distance of 428.30 feet, more or less, to a point; thence,
61. Bearing N 00° 32' 40" E for a distance of 60.54 feet, more or less, to a point; thence,
62. Bearing N 00° 32' 40" E for a distance of 227.04 feet, more or less, to a point; thence,
63. Bearing N 02° 32' 51" E for a distance of 173.92 feet, more or less, to a point; thence,
64. Bearing N 01° 08' 39" E for a distance of 569.14 feet, more or less, to a point; thence,
65. Bearing N 00° 48' 36" E for a distance of 322.25 feet, more or less, to a point; thence,
66. Bearing S 78° 42' 44" W for a distance of 256.71 feet, more or less, to a point; thence,
67. Bearing N 00° 20' 25" W for a distance of 227.60 feet, more or less, to a point; thence,
68. Bearing N 83° 54' 30" W for a distance of 26.69 feet, more or less, to a point; thence,
69. Bearing N 01° 12' 25" W for a distance of 243.12 feet, more or less, to a point; thence,
70. Bearing N 00° 01' 51" W for a distance of 33.40 feet, more or less, to a point; thence,
71. Bearing N 01° 12' 53" W for a distance of 356.08 feet, more or less, to a point; thence,
72. Bearing S 89° 30' 27" E for a distance of 432.20 feet, more or less, to a point; thence,
73. Bearing S 89° 43' 55" E for a distance of 372.45 feet, more or less, to a point; thence,
74. Bearing S 01° 04' 30" W for a distance of 118.79 feet, more or less, to a point; thence,
75. Bearing S 00° 53' 19" W for a distance of 125.01 feet, more or less, to a point; thence,
76. Bearing N 88° 57' 46" E for a distance of 1359.48 feet, more or less, to a point; thence,
77. Bearing N 89° 13' 16" E for a distance of 600.91 feet, more or less, to a point; thence,
78. Bearing S 00° 44' 31" E for a distance of 148.43 feet, more or less, to a point; thence,
79. Bearing S 03° 30' 24" E for a distance of 43.77 feet, more or less, to a point; thence,
80. Bearing S 00° 00' 00" W for a distance of 13.37 feet, more or less, to a point; thence,
81. Bearing S 00° 18' 57" W for a distance of 92.67 feet, more or less, to a point; thence,
82. Bearing S 00° 46' 30" E for a distance of 302.26 feet, more or less, to a point; thence,
83. Bearing S 00° 05' 18" W for a distance of 210.69 feet, more or less, to a point; thence,
84. Bearing S 00° 10' 18" E for a distance of 245.35 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1070267.9902' and whose Easting is 1415285.3672'; thence,

1. Bearing S 85° 37' 21" E for a distance of 167.06 feet, more or less, to a point; thence,
2. Bearing S 85° 55' 36" E for a distance of 169.47 feet, more or less, to a point; thence,
3. Bearing S 05° 18' 56" W for a distance of 448.45 feet, more or less, to a point; thence,
4. Bearing N 89° 43' 22" W for a distance of 405.42 feet, more or less, to a point; thence,
5. Bearing S 88° 06' 41" W for a distance of 199.95 feet, more or less, to a point; thence,
6. Bearing S 01° 47' 27" W for a distance of 21.47 feet, more or less, to a point; thence,
7. Bearing S 00° 10' 04" W for a distance of 204.39 feet, more or less, to a point; thence,

8. Bearing S 00° 43' 17" E for a distance of 426.59 feet, more or less, to a point; thence,
9. Bearing S 89° 53' 21" W for a distance of 390.67 feet, more or less, to a point; thence,
10. Bearing S 89° 45' 18" W for a distance of 381.80 feet, more or less, to a point; thence,
11. Bearing S 00° 28' 58" W for a distance of 234.27 feet, more or less, to a point; thence,
12. Bearing S 00° 16' 15" W for a distance of 64.27 feet, more or less, to a point; thence,
13. Bearing S 89° 14' 35" W for a distance of 462.61 feet, more or less, to a point; thence,
14. Bearing S 00° 16' 19" E for a distance of 149.17 feet, more or less, to a point; thence,
15. Bearing S 55° 02' 06" W for a distance of 996.35 feet, more or less, to a point; thence,
16. Bearing N 83° 49' 59" W for a distance of 616.89 feet, more or less, to a point; thence,
17. Bearing N 04° 57' 44" W for a distance of 956.96 feet, more or less, to a point; thence,
18. Bearing N 04° 44' 50" W for a distance of 1328.84 feet, more or less, to a point; thence,
19. Bearing S 86° 06' 58" E for a distance of 46.84 feet, more or less, to a point; thence,
20. Bearing S 86° 37' 10" E for a distance of 387.07 feet, more or less, to a point; thence,
21. Bearing S 86° 14' 13" E for a distance of 242.36 feet, more or less, to a point; thence,
22. Bearing N 00° 15' 46" E for a distance of 349.19 feet, more or less, to a point; thence,
23. Bearing S 87° 28' 20" E for a distance of 224.39 feet, more or less, to a point; thence,
24. Bearing S 87° 28' 20" E for a distance of 306.68 feet, more or less, to a point; thence,
25. Bearing S 88° 20' 57" E for a distance of 535.40 feet, more or less, to a point; thence,
26. Bearing N 00° 00' 00" E for a distance of 77.13 feet, more or less, to a point; thence,
27. Bearing N 87° 23' 38" E for a distance of 294.79 feet, more or less, to a point; thence,
28. Bearing N 13° 04' 56" W for a distance of 289.09 feet, more or less, to a point; thence,
29. Bearing N 13° 00' 23" W for a distance of 289.86 feet, more or less, to a point; thence,
30. Bearing N 88° 39' 19" E for a distance of 227.73 feet, more or less, to a point; thence,
31. Bearing N 88° 41' 03" E for a distance of 92.62 feet, more or less, to a point; thence,
32. Bearing S 88° 53' 18" E for a distance of 109.64 feet, more or less, to a point; thence,
33. Bearing N 89° 20' 30" E for a distance of 92.60 feet, more or less, to a point; thence,
34. Bearing N 90° 00' 00" E for a distance of 103.23 feet, more or less, to a point; thence,
35. Bearing N 89° 32' 58" E for a distance of 135.17 feet, more or less, to a point; thence,
36. Bearing N 90° 00' 00" E for a distance of 106.43 feet, more or less, to a point; thence,
37. Bearing N 89° 21' 08" E for a distance of 97.73 feet, more or less, to a point; thence,
38. Bearing N 90° 00' 00" E for a distance of 104.30 feet, more or less, to a point; thence,
39. Bearing N 89° 29' 51" E for a distance of 121.33 feet, more or less, to a point; thence,
40. Bearing N 88° 36' 16" E for a distance of 87.30 feet, more or less, to a point; thence,
41. Bearing S 00° 54' 18" W for a distance of 1123.27 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1049574.1632' and whose Easting is 1403626.4165'; thence,

1. Bearing S 05° 14' 44" W for a distance of 314.00 feet, more or less, to a point; thence,
2. Bearing S 89° 42' 12" E for a distance of 701.87 feet, more or less, to a point; thence,
3. Bearing S 01° 10' 48" W for a distance of 905.77 feet, more or less, to a point; thence,
4. Bearing S 00° 42' 23" W for a distance of 1348.79 feet, more or less, to a point; thence,
5. Bearing S 89° 49' 24" W for a distance of 1550.25 feet, more or less, to a point; thence,
6. Bearing N 01° 29' 35" E for a distance of 2023.09 feet, more or less, to a point; thence,
7. Bearing S 88° 19' 28" W for a distance of 125.42 feet, more or less, to a point; thence,

8. Bearing S 89° 55' 13" W for a distance of 1281.75 feet, more or less, to a point; thence,
9. Bearing S 37° 34' 36" W for a distance of 3.27 feet, more or less, to a point; thence,
10. Bearing N 89° 34' 11" W for a distance of 1416.40 feet, more or less, to a point; thence,
11. Bearing S 00° 23' 34" E for a distance of 424.99 feet, more or less, to a point; thence,
12. Bearing S 00° 39' 20" E for a distance of 425.85 feet, more or less, to a point; thence,
13. Bearing S 00° 24' 38" E for a distance of 677.56 feet, more or less, to a point; thence,
14. Bearing S 00° 12' 48" E for a distance of 498.02 feet, more or less, to a point; thence,
15. Bearing S 01° 51' 44" E for a distance of 133.55 feet, more or less, to a point; thence,
16. Bearing S 00° 10' 41" W for a distance of 2088.54 feet, more or less, to a point; thence,
17. Bearing S 88° 54' 00" W for a distance of 831.00 feet, more or less, to a point; thence,
18. Bearing S 88° 37' 44" W for a distance of 264.98 feet, more or less, to a point; thence,
19. Bearing S 89° 06' 19" W for a distance of 304.60 feet, more or less, to a point; thence,
20. Bearing N 00° 08' 13" W for a distance of 647.31 feet, more or less, to a point; thence,
21. Bearing N 00° 00' 00" E for a distance of 527.80 feet, more or less, to a point; thence,
22. Bearing N 89° 53' 11" W for a distance of 183.53 feet, more or less, to a point; thence,
23. Bearing N 89° 45' 20" W for a distance of 39.75 feet, more or less, to a point; thence,
24. Bearing S 23° 58' 29" W for a distance of 397.61 feet, more or less, to a point; thence,
25. Bearing S 23° 39' 01" W for a distance of 344.94 feet, more or less, to a point; thence,
26. Bearing S 23° 52' 40" W for a distance of 260.83 feet, more or less, to a point; thence,
27. Bearing S 23° 49' 06" W for a distance of 286.05 feet, more or less, to a point; thence,
28. Bearing S 22° 35' 07" W for a distance of 269.68 feet, more or less, to a point; thence,
29. Bearing S 19° 41' 52" W for a distance of 253.39 feet, more or less, to a point; thence,
30. Bearing S 17° 53' 44" W for a distance of 9.31 feet, more or less, to a point; thence,
31. Bearing N 89° 55' 02" W for a distance of 165.70 feet, more or less, to a point; thence,
32. Bearing S 01° 14' 56" E for a distance of 279.83 feet, more or less, to a point; thence,
33. Bearing S 00° 14' 13" E for a distance of 1160.55 feet, more or less, to a point; thence,
34. Bearing N 86° 38' 03" W for a distance of 27.01 feet, more or less, to a point; thence,
35. Bearing S 00° 22' 43" E for a distance of 480.26 feet, more or less, to a point; thence,
36. Bearing S 00° 01' 30" W for a distance of 801.39 feet, more or less, to a point; thence,
37. Bearing N 88° 41' 57" W for a distance of 214.19 feet, more or less, to a point; thence,
38. Bearing N 00° 37' 56" E for a distance of 723.34 feet, more or less, to a point; thence,
39. Bearing N 87° 51' 21" W for a distance of 457.26 feet, more or less, to a point; thence,
40. Bearing S 09° 34' 39" W for a distance of 490.00 feet, more or less, to a point; thence,
41. Bearing N 85° 37' 05" W for a distance of 1131.28 feet, more or less, to a point; thence,
42. Bearing N 12° 03' 05" W for a distance of 219.59 feet, more or less, to a point; thence,
43. Bearing N 89° 23' 37" W for a distance of 87.72 feet, more or less, to a point; thence,
44. Bearing S 17° 42' 30" W for a distance of 155.14 feet, more or less, to a point; thence,
45. Bearing S 17° 53' 32" W for a distance of 126.40 feet, more or less, to a point; thence,
46. Bearing N 72° 19' 17" W for a distance of 386.49 feet, more or less, to a point; thence,
47. Bearing N 17° 28' 35" E for a distance of 283.84 feet, more or less, to a point; thence,
48. Bearing N 16° 59' 11" E for a distance of 342.14 feet, more or less, to a point; thence,
49. Bearing N 15° 54' 12" E for a distance of 350.69 feet, more or less, to a point; thence,
50. Bearing N 52° 08' 47" W for a distance of 36.81 feet, more or less, to a point; thence,
51. Bearing S 88° 40' 18" W for a distance of 428.53 feet, more or less, to a point; thence,
52. Bearing N 89° 16' 50" W for a distance of 213.32 feet, more or less, to a point; thence,
53. Bearing N 00° 53' 40" E for a distance of 1336.78 feet, more or less, to a point; thence,

54. Bearing S 89° 25' 04" E for a distance of 141.38 feet, more or less, to a point; thence,
55. Bearing N 07° 00' 58" E for a distance of 1005.91 feet, more or less, to a point; thence,
56. Bearing N 06° 56' 18" E for a distance of 423.00 feet, more or less, to a point; thence,
57. Bearing N 01° 27' 16" E for a distance of 91.60 feet, more or less, to a point; thence,
58. Bearing N 87° 57' 21" E for a distance of 51.41 feet, more or less, to a point; thence,
59. Bearing N 00° 01' 39" W for a distance of 189.59 feet, more or less, to a point; thence,
60. Bearing N 89° 38' 11" W for a distance of 440.70 feet, more or less, to a point; thence,
61. Bearing N 02° 12' 21" W for a distance of 910.88 feet, more or less, to a point; thence,
62. Bearing N 03° 37' 39" W for a distance of 110.60 feet, more or less, to a point; thence,
63. Bearing N 89° 52' 04" W for a distance of 21.22 feet, more or less, to a point; thence,
64. Bearing N 00° 00' 00" E for a distance of 30.10 feet, more or less, to a point; thence,
65. Bearing N 00° 47' 14" W for a distance of 128.11 feet, more or less, to a point; thence,
66. Bearing N 00° 57' 15" W for a distance of 624.31 feet, more or less, to a point; thence,
67. Bearing N 00° 50' 51" W for a distance of 247.42 feet, more or less, to a point; thence,
68. Bearing N 01° 00' 45" W for a distance of 288.25 feet, more or less, to a point; thence,
69. Bearing N 00° 31' 16" W for a distance of 1194.38 feet, more or less, to a point; thence,
70. Bearing N 00° 35' 02" W for a distance of 591.98 feet, more or less, to a point; thence,
71. Bearing N 84° 17' 37" W for a distance of 20.86 feet, more or less, to a point; thence,
72. Bearing N 00° 29' 03" W for a distance of 388.54 feet, more or less, to a point; thence,
73. Bearing N 00° 18' 47" E for a distance of 585.54 feet, more or less, to a point; thence,
74. Bearing N 89° 58' 19" W for a distance of 373.17 feet, more or less, to a point; thence,
75. Bearing N 25° 13' 07" W for a distance of 34.97 feet, more or less, to a point; thence,
76. Bearing N 19° 40' 06" W for a distance of 27.66 feet, more or less, to a point; thence,
77. Bearing N 18° 26' 57" W for a distance of 47.08 feet, more or less, to a point; thence,
78. Bearing N 16° 16' 22" W for a distance of 46.52 feet, more or less, to a point; thence,
79. Bearing N 10° 53' 38" W for a distance of 49.27 feet, more or less, to a point; thence,
80. Bearing N 28° 37' 45" W for a distance of 46.64 feet, more or less, to a point; thence,
81. Bearing N 36° 53' 35" W for a distance of 46.53 feet, more or less, to a point; thence,
82. Bearing N 31° 26' 56" W for a distance of 39.26 feet, more or less, to a point; thence,
83. Bearing N 17° 22' 02" W for a distance of 31.19 feet, more or less, to a point; thence,
84. Bearing N 14° 02' 52" W for a distance of 23.02 feet, more or less, to a point; thence,
85. Bearing N 33° 42' 41" W for a distance of 26.84 feet, more or less, to a point; thence,
86. Bearing N 05° 42' 52" W for a distance of 37.40 feet, more or less, to a point; thence,
87. Bearing N 00° 00' 00" E for a distance of 31.63 feet, more or less, to a point; thence,
88. Bearing N 17° 22' 01" W for a distance of 62.39 feet, more or less, to a point; thence,
89. Bearing S 89° 38' 55" E for a distance of 556.07 feet, more or less, to a point; thence,
90. Bearing S 02° 43' 22" E for a distance of 212.44 feet, more or less, to a point; thence,
91. Bearing N 89° 43' 41" E for a distance of 761.17 feet, more or less, to a point; thence,
92. Bearing N 89° 43' 41" E for a distance of 521.48 feet, more or less, to a point; thence,
93. Bearing N 00° 10' 25" W for a distance of 861.03 feet, more or less, to a point; thence,
94. Bearing S 85° 22' 04" E for a distance of 40.55 feet, more or less, to a point; thence,
95. Bearing N 89° 43' 21" E for a distance of 848.42 feet, more or less, to a point; thence,
96. Bearing N 89° 54' 24" E for a distance of 1211.24 feet, more or less, to a point; thence,
97. Bearing N 06° 35' 01" E for a distance of 99.73 feet, more or less, to a point; thence,
98. Bearing N 08° 35' 21" E for a distance of 135.71 feet, more or less, to a point; thence,
99. Bearing N 12° 43' 23" E for a distance of 97.35 feet, more or less, to a point; thence,

100. Bearing N 13° 45' 08" E for a distance of 102.95 feet, more or less, to a point; thence,
101. Bearing N 15° 03' 56" E for a distance of 259.22 feet, more or less, to a point; thence,
102. Bearing N 14° 58' 00" E for a distance of 383.19 feet, more or less, to a point; thence,
103. Bearing N 15° 32' 55" E for a distance of 462.18 feet, more or less, to a point; thence,
104. Bearing N 15° 25' 34" E for a distance of 369.51 feet, more or less, to a point; thence,
105. Bearing N 15° 43' 50" E for a distance of 215.53 feet, more or less, to a point; thence,
106. Bearing N 15° 22' 37" E for a distance of 241.08 feet, more or less, to a point; thence,
107. Bearing N 15° 06' 10" E for a distance of 167.47 feet, more or less, to a point; thence,
108. Bearing N 09° 33' 17" E for a distance of 86.18 feet, more or less, to a point; thence,
109. Bearing N 08° 57' 26" E for a distance of 10.94 feet, more or less, to a point; thence,
110. Bearing N 29° 28' 07" W for a distance of 28.96 feet, more or less, to a point; thence,
111. Bearing N 26° 37' 36" W for a distance of 173.67 feet, more or less, to a point; thence,
112. Bearing N 33° 34' 34" W for a distance of 195.73 feet, more or less, to a point; thence,
113. Bearing N 32° 59' 14" W for a distance of 283.72 feet, more or less, to a point; thence,
114. Bearing N 29° 59' 32" W for a distance of 245.84 feet, more or less, to a point; thence,
115. Bearing N 27° 16' 34" W for a distance of 189.31 feet, more or less, to a point; thence,
116. Bearing N 24° 11' 37" W for a distance of 144.10 feet, more or less, to a point; thence,
117. Bearing N 21° 02' 23" W for a distance of 110.42 feet, more or less, to a point; thence,
118. Bearing N 19° 01' 06" W for a distance of 114.61 feet, more or less, to a point; thence,
119. Bearing N 15° 44' 29" W for a distance of 141.00 feet, more or less, to a point; thence,
120. Bearing N 12° 22' 20" W for a distance of 186.20 feet, more or less, to a point; thence,
121. Bearing N 09° 42' 56" W for a distance of 165.21 feet, more or less, to a point; thence,
122. Bearing N 07° 56' 52" W for a distance of 142.75 feet, more or less, to a point; thence,
123. Bearing N 05° 03' 05" W for a distance of 297.96 feet, more or less, to a point; thence,
124. Bearing N 03° 19' 31" W for a distance of 360.10 feet, more or less, to a point; thence,
125. Bearing N 02° 46' 59" W for a distance of 482.94 feet, more or less, to a point; thence,
126. Bearing N 02° 46' 11" W for a distance of 647.69 feet, more or less, to a point; thence,
127. Bearing N 31° 28' 47" E for a distance of 77.56 feet, more or less, to a point; thence,
128. Bearing S 67° 09' 28" E for a distance of 39.64 feet, more or less, to a point; thence,
129. Bearing S 76° 17' 35" E for a distance of 162.97 feet, more or less, to a point; thence,
130. Bearing S 88° 20' 32" E for a distance of 195.10 feet, more or less, to a point; thence,
131. Bearing N 83° 49' 22" E for a distance of 69.93 feet, more or less, to a point; thence,
132. Bearing N 83° 49' 22" E for a distance of 198.48 feet, more or less, to a point; thence,
133. Bearing N 83° 28' 20" E for a distance of 243.62 feet, more or less, to a point; thence,
134. Bearing N 83° 52' 13" W for a distance of 272.93 feet, more or less, to a point; thence,
135. Bearing N 76° 29' 55" W for a distance of 163.21 feet, more or less, to a point; thence,
136. Bearing N 00° 10' 19" W for a distance of 498.44 feet, more or less, to a point; thence,
137. Bearing N 00° 38' 40" W for a distance of 230.32 feet, more or less, to a point; thence,
138. Bearing N 00° 00' 00" E for a distance of 230.30 feet, more or less, to a point; thence,
139. Bearing N 00° 00' 00" E for a distance of 222.54 feet, more or less, to a point; thence,
140. Bearing N 89° 26' 51" E for a distance of 499.09 feet, more or less, to a point; thence,
141. Bearing N 00° 15' 52" E for a distance of 182.30 feet, more or less, to a point; thence,
142. Bearing N 00° 18' 04" W for a distance of 195.18 feet, more or less, to a point; thence,
143. Bearing S 66° 46' 09" E for a distance of 906.85 feet, more or less, to a point; thence,
144. Bearing S 00° 00' 00" W for a distance of 90.57 feet, more or less, to a point; thence,
145. Bearing S 01° 31' 21" E for a distance of 193.15 feet, more or less, to a point; thence,

146. Bearing S 01° 28' 11" W for a distance of 201.90 feet, more or less, to a point; thence,
147. Bearing S 00° 25' 41" E for a distance of 346.76 feet, more or less, to a point; thence,
148. Bearing S 83° 26' 08" W for a distance of 615.28 feet, more or less, to a point; thence,
149. Bearing S 00° 39' 05" W for a distance of 84.19 feet, more or less, to a point; thence,
150. Bearing N 90° 00' 00" W for a distance of 22.98 feet, more or less, to a point; thence,
151. Bearing S 06° 53' 40" E for a distance of 257.71 feet, more or less, to a point; thence,
152. Bearing S 82° 54' 26" W for a distance of 115.32 feet, more or less, to a point; thence,
153. Bearing S 84° 47' 24" W for a distance of 121.10 feet, more or less, to a point; thence,
154. Bearing S 84° 47' 24" W for a distance of 2.72 feet, more or less, to a point; thence,
155. Bearing S 02° 46' 11" E for a distance of 667.57 feet, more or less, to a point; thence,
156. Bearing S 02° 46' 59" E for a distance of 478.21 feet, more or less, to a point; thence,
157. Bearing S 03° 19' 31" E for a distance of 340.31 feet, more or less, to a point; thence,
158. Bearing S 05° 03' 05" E for a distance of 251.21 feet, more or less, to a point; thence,
159. Bearing S 80° 16' 37" E for a distance of 76.84 feet, more or less, to a point; thence,
160. Bearing N 11° 22' 18" E for a distance of 341.52 feet, more or less, to a point; thence,
161. Bearing S 78° 47' 38" E for a distance of 202.66 feet, more or less, to a point; thence,
162. Bearing S 11° 16' 12" W for a distance of 394.61 feet, more or less, to a point; thence,
163. Bearing N 80° 37' 38" W for a distance of 259.86 feet, more or less, to a point; thence,
164. Bearing S 07° 56' 52" E for a distance of 45.66 feet, more or less, to a point; thence,
165. Bearing S 09° 42' 56" E for a distance of 126.60 feet, more or less, to a point; thence,
166. Bearing S 12° 22' 20" E for a distance of 133.60 feet, more or less, to a point; thence,
167. Bearing S 15° 44' 29" E for a distance of 82.99 feet, more or less, to a point; thence,
168. Bearing S 19° 01' 06" E for a distance of 68.36 feet, more or less, to a point; thence,
169. Bearing S 21° 02' 23" E for a distance of 65.25 feet, more or less, to a point; thence,
170. Bearing S 24° 11' 37" E for a distance of 89.66 feet, more or less, to a point; thence,
171. Bearing S 27° 16' 34" E for a distance of 138.70 feet, more or less, to a point; thence,
172. Bearing S 29° 59' 32" E for a distance of 195.99 feet, more or less, to a point; thence,
173. Bearing S 32° 59' 14" E for a distance of 252.44 feet, more or less, to a point; thence,
174. Bearing S 33° 34' 34" E for a distance of 251.31 feet, more or less, to a point; thence,
175. Bearing S 26° 37' 36" E for a distance of 159.70 feet, more or less, to a point; thence,
176. Bearing S 00° 18' 07" E for a distance of 347.52 feet, more or less, to a point; thence,
177. Bearing S 00° 03' 04" E for a distance of 82.80 feet, more or less, to a point; thence,
178. Bearing N 89° 36' 27" E for a distance of 128.00 feet, more or less, to a point; thence,
179. Bearing N 89° 36' 29" E for a distance of 484.90 feet, more or less, to a point; thence,
180. Bearing N 83° 39' 49" E for a distance of 57.02 feet, more or less, to a point; thence,
181. Bearing S 00° 20' 47" E for a distance of 229.84 feet, more or less, to a point; thence,
182. Bearing S 04° 40' 14" W for a distance of 701.36 feet, more or less, to a point; thence,
183. Bearing S 00° 20' 26" E for a distance of 620.53 feet, more or less, to a point; thence,
184. Bearing S 00° 29' 42" E for a distance of 399.51 feet, more or less, to a point; thence,
185. Bearing S 00° 58' 05" W for a distance of 178.38 feet, more or less, to a point; thence,
186. Bearing S 16° 05' 56" W for a distance of 2.03 feet, more or less, to a point; thence,
187. Bearing S 14° 58' 00" W for a distance of 375.02 feet, more or less, to a point; thence,
188. Bearing S 15° 03' 56" W for a distance of 238.68 feet, more or less, to a point; thence,
189. Bearing S 13° 45' 08" W for a distance of 63.33 feet, more or less, to a point; thence,
190. Bearing S 12° 43' 23" W for a distance of 10.00 feet, more or less, to a point; thence,
191. Bearing S 08° 35' 21" W for a distance of 31.84 feet, more or less, to a point; thence,

192. Bearing S 06° 35' 01" W for a distance of 30.19 feet, more or less, to a point; thence,
193. Bearing S 02° 32' 05" W for a distance of 33.62 feet, more or less, to a point; thence,
194. Bearing S 00° 30' 03" E for a distance of 249.36 feet, more or less, to a point; thence,
195. Bearing S 00° 31' 00" E for a distance of 709.52 feet, more or less, to a point; thence,
196. Bearing S 00° 43' 08" E for a distance of 576.80 feet, more or less, to a point; thence,
197. Bearing S 00° 31' 58" E for a distance of 87.84 feet, more or less, to a point; thence,
198. Bearing N 89° 58' 34" E for a distance of 2526.89 feet, more or less, to a point; thence,
199. Bearing S 11° 55' 08" W for a distance of 5.32 feet, more or less, to a point; thence,
200. Bearing N 89° 35' 20" E for a distance of 505.65 feet, more or less, to a point; thence,
201. Bearing N 86° 10' 31" E for a distance of 9.76 feet, more or less, to a point; thence,
202. Bearing N 84° 13' 27" E for a distance of 296.08 feet, more or less, to a point; thence,
203. Bearing N 85° 15' 37" E for a distance of 346.26 feet, more or less, to a point; thence,
204. Bearing S 88° 10' 25" E for a distance of 154.50 feet, more or less, to a point; thence,
205. Bearing S 89° 35' 16" E for a distance of 130.41 feet, more or less, to a point; thence,
206. Bearing N 90° 00' 00" E for a distance of 115.24 feet, more or less, to a point; thence,
207. Bearing S 04° 22' 01" W for a distance of 633.74 feet, more or less, to a point; thence,
208. Bearing S 86° 49' 21" W for a distance of 197.64 feet, more or less, to a point; thence,
209. Bearing S 01° 32' 24" E for a distance of 188.33 feet, more or less, to a point; thence,
210. Bearing S 89° 35' 16" E for a distance of 38.91 feet, more or less, to the Point of Beginning.

Using the New York State Plane NAD 83, west zone, U.S. Survey foot coordinate system, beginning at a point, whose Northing is 1049842.8393' and whose Easting is 1418560.4806'; thence,

1. Bearing N 89° 11' 20" E for a distance of 141.46 feet, more or less, to a point; thence,
2. Bearing N 89° 06' 58" E for a distance of 471.84 feet, more or less, to a point; thence,
3. Bearing N 89° 09' 29" E for a distance of 111.96 feet, more or less, to a point; thence,
4. Bearing N 01° 30' 58" W for a distance of 628.87 feet, more or less, to a point; thence,
5. Bearing N 88° 09' 06" W for a distance of 656.12 feet, more or less, to a point; thence,
6. Bearing N 00° 18' 34" W for a distance of 1297.45 feet, more or less, to a point; thence,
7. Bearing N 00° 18' 34" W for a distance of 813.66 feet, more or less, to a point; thence,
8. Bearing S 89° 24' 52" W for a distance of 796.58 feet, more or less, to a point; thence,
9. Bearing S 89° 24' 53" W for a distance of 309.90 feet, more or less, to a point; thence,
10. Bearing N 01° 02' 33" W for a distance of 646.63 feet, more or less, to a point; thence,
11. Bearing N 85° 14' 25" E for a distance of 283.32 feet, more or less, to a point; thence,
12. Bearing N 02° 06' 12" W for a distance of 641.08 feet, more or less, to a point; thence,
13. Bearing N 05° 43' 52" W for a distance of 70.92 feet, more or less, to a point; thence,
14. Bearing N 00° 23' 44" W for a distance of 256.00 feet, more or less, to a point; thence,
15. Bearing N 00° 51' 49" W for a distance of 1043.49 feet, more or less, to a point; thence,
16. Bearing N 87° 26' 04" W for a distance of 738.62 feet, more or less, to a point; thence,
17. Bearing S 88° 55' 19" W for a distance of 1307.13 feet, more or less, to a point; thence,
18. Bearing N 00° 48' 40" W for a distance of 646.14 feet, more or less, to a point; thence,
19. Bearing N 00° 40' 43" W for a distance of 763.93 feet, more or less, to a point; thence,
20. Bearing N 01° 04' 06" W for a distance of 740.38 feet, more or less, to a point; thence,
21. Bearing S 89° 47' 29" E for a distance of 1328.74 feet, more or less, to a point; thence,
22. Bearing N 00° 44' 07" W for a distance of 485.25 feet, more or less, to a point; thence,
23. Bearing N 01° 07' 42" E for a distance of 81.41 feet, more or less, to a point; thence,

24. Bearing N 00° 04' 53" W for a distance of 1179.03 feet, more or less, to a point; thence,
25. Bearing N 03° 29' 51" W for a distance of 816.42 feet, more or less, to a point; thence,
26. Bearing N 00° 38' 51" E for a distance of 78.71 feet, more or less, to a point; thence,
27. Bearing S 88° 55' 19" E for a distance of 701.37 feet, more or less, to a point; thence,
28. Bearing S 88° 55' 19" E for a distance of 1283.57 feet, more or less, to a point; thence,
29. Bearing N 01° 25' 59" E for a distance of 199.75 feet, more or less, to a point; thence,
30. Bearing N 00° 48' 48" E for a distance of 199.74 feet, more or less, to a point; thence,
31. Bearing N 88° 17' 42" W for a distance of 162.17 feet, more or less, to a point; thence,
32. Bearing N 01° 12' 45" E for a distance of 228.19 feet, more or less, to a point; thence,
33. Bearing N 22° 05' 27" E for a distance of 282.28 feet, more or less, to a point; thence,
34. Bearing N 22° 00' 13" E for a distance of 424.78 feet, more or less, to a point; thence,
35. Bearing N 89° 46' 01" E for a distance of 547.59 feet, more or less, to a point; thence,
36. Bearing S 08° 09' 14" E for a distance of 61.43 feet, more or less, to a point; thence,
37. Bearing S 07° 19' 28" E for a distance of 77.14 feet, more or less, to a point; thence,
38. Bearing S 10° 56' 00" E for a distance of 51.38 feet, more or less, to a point; thence,
39. Bearing S 03° 55' 44" E for a distance of 85.05 feet, more or less, to a point; thence,
40. Bearing S 01° 48' 42" E for a distance of 21.49 feet, more or less, to a point; thence,
41. Bearing S 89° 39' 27" E for a distance of 334.98 feet, more or less, to a point; thence,
42. Bearing S 87° 36' 55" E for a distance of 929.74 feet, more or less, to a point; thence,
43. Bearing S 00° 33' 45" E for a distance of 65.59 feet, more or less, to a point; thence,
44. Bearing S 00° 33' 45" E for a distance of 158.83 feet, more or less, to a point; thence,
45. Bearing S 00° 41' 50" E for a distance of 1258.81 feet, more or less, to a point; thence,
46. Bearing S 00° 45' 35" E for a distance of 672.25 feet, more or less, to a point; thence,
47. Bearing N 89° 25' 53" E for a distance of 1321.65 feet, more or less, to a point; thence,
48. Bearing S 01° 07' 41" E for a distance of 510.57 feet, more or less, to a point; thence,
49. Bearing S 01° 42' 38" E for a distance of 453.60 feet, more or less, to a point; thence,
50. Bearing S 01° 47' 28" E for a distance of 791.88 feet, more or less, to a point; thence,
51. Bearing N 89° 47' 28" W for a distance of 408.88 feet, more or less, to a point; thence,
52. Bearing N 00° 00' 00" E for a distance of 101.32 feet, more or less, to a point; thence,
53. Bearing N 89° 55' 43" W for a distance of 866.91 feet, more or less, to a point; thence,
54. Bearing S 01° 29' 44" E for a distance of 635.66 feet, more or less, to a point; thence,
55. Bearing S 89° 19' 52" W for a distance of 163.94 feet, more or less, to a point; thence,
56. Bearing S 07° 00' 43" E for a distance of 657.77 feet, more or less, to a point; thence,
57. Bearing N 90° 00' 00" E for a distance of 408.00 feet, more or less, to a point; thence,
58. Bearing N 90° 00' 00" E for a distance of 319.79 feet, more or less, to a point; thence,
59. Bearing N 26° 27' 43" E for a distance of 411.34 feet, more or less, to a point; thence,
60. Bearing S 86° 59' 25" E for a distance of 37.10 feet, more or less, to a point; thence,
61. Bearing N 01° 47' 27" W for a distance of 68.00 feet, more or less, to a point; thence,
62. Bearing N 32° 21' 32" E for a distance of 56.08 feet, more or less, to a point; thence,
63. Bearing N 42° 26' 20" E for a distance of 272.00 feet, more or less, to a point; thence,
64. Bearing N 88° 12' 32" E for a distance of 198.90 feet, more or less, to a point; thence,
65. Bearing N 88° 12' 22" E for a distance of 88.84 feet, more or less, to a point; thence,
66. Bearing N 04° 47' 47" E for a distance of 22.72 feet, more or less, to a point; thence,
67. Bearing S 84° 59' 34" E for a distance of 571.35 feet, more or less, to a point; thence,
68. Bearing S 17° 36' 49" E for a distance of 1147.80 feet, more or less, to a point; thence,
69. Bearing S 18° 02' 52" E for a distance of 229.82 feet, more or less, to a point; thence,

70. Bearing N 73° 27' 19" E for a distance of 294.46 feet, more or less, to a point; thence,
71. Bearing N 80° 57' 23" E for a distance of 290.97 feet, more or less, to a point; thence,
72. Bearing N 87° 02' 29" E for a distance of 295.37 feet, more or less, to a point; thence,
73. Bearing S 02° 54' 47" W for a distance of 130.52 feet, more or less, to a point; thence,
74. Bearing N 83° 00' 26" W for a distance of 22.79 feet, more or less, to a point; thence,
75. Bearing N 85° 02' 03" W for a distance of 31.54 feet, more or less, to a point; thence,
76. Bearing N 80° 11' 17" W for a distance of 72.09 feet, more or less, to a point; thence,
77. Bearing N 85° 14' 38" W for a distance of 19.26 feet, more or less, to a point; thence,
78. Bearing S 75° 04' 46" W for a distance of 42.42 feet, more or less, to a point; thence,
79. Bearing S 88° 29' 38" W for a distance of 51.93 feet, more or less, to a point; thence,
80. Bearing S 87° 52' 50" W for a distance of 73.82 feet, more or less, to a point; thence,
81. Bearing S 83° 50' 06" W for a distance of 50.84 feet, more or less, to a point; thence,
82. Bearing S 74° 38' 06" W for a distance of 56.67 feet, more or less, to a point; thence,
83. Bearing S 65° 56' 30" W for a distance of 70.32 feet, more or less, to a point; thence,
84. Bearing S 64° 49' 01" W for a distance of 51.33 feet, more or less, to a point; thence,
85. Bearing S 62° 43' 07" W for a distance of 47.65 feet, more or less, to a point; thence,
86. Bearing S 57° 48' 40" W for a distance of 86.34 feet, more or less, to a point; thence,
87. Bearing S 55° 08' 48" W for a distance of 54.94 feet, more or less, to a point; thence,
88. Bearing S 49° 25' 17" W for a distance of 50.37 feet, more or less, to a point; thence,
89. Bearing S 42° 54' 05" W for a distance of 52.18 feet, more or less, to a point; thence,
90. Bearing S 41° 22' 15" W for a distance of 45.48 feet, more or less, to a point; thence,
91. Bearing S 31° 50' 53" W for a distance of 46.60 feet, more or less, to a point; thence,
92. Bearing S 15° 39' 15" W for a distance of 35.44 feet, more or less, to a point; thence,
93. Bearing S 07° 51' 31" W for a distance of 39.96 feet, more or less, to a point; thence,
94. Bearing S 02° 36' 23" W for a distance of 30.06 feet, more or less, to a point; thence,
95. Bearing S 04° 14' 29" E for a distance of 36.96 feet, more or less, to a point; thence,
96. Bearing S 04° 34' 31" E for a distance of 34.24 feet, more or less, to a point; thence,
97. Bearing S 15° 57' 34" E for a distance of 49.69 feet, more or less, to a point; thence,
98. Bearing S 22° 56' 50" E for a distance of 38.54 feet, more or less, to a point; thence,
99. Bearing S 26° 34' 57" E for a distance of 39.69 feet, more or less, to a point; thence,
100. Bearing S 28° 30' 56" E for a distance of 54.37 feet, more or less, to a point; thence,
101. Bearing S 41° 55' 45" E for a distance of 71.56 feet, more or less, to a point; thence,
102. Bearing S 59° 26' 29" E for a distance of 69.81 feet, more or less, to a point; thence,
103. Bearing S 75° 44' 12" E for a distance of 57.29 feet, more or less, to a point; thence,
104. Bearing N 85° 36' 17" E for a distance of 35.62 feet, more or less, to a point; thence,
105. Bearing N 81° 15' 40" E for a distance of 53.91 feet, more or less, to a point; thence,
106. Bearing N 73° 05' 07" E for a distance of 65.68 feet, more or less, to a point; thence,
107. Bearing N 69° 14' 34" E for a distance of 42.37 feet, more or less, to a point; thence,
108. Bearing N 61° 12' 38" E for a distance of 31.18 feet, more or less, to a point; thence,
109. Bearing N 74° 45' 17" E for a distance of 31.15 feet, more or less, to a point; thence,
110. Bearing N 75° 58' 31" E for a distance of 39.43 feet, more or less, to a point; thence,
111. Bearing N 61° 12' 29" E for a distance of 31.18 feet, more or less, to a point; thence,
112. Bearing N 55° 11' 48" E for a distance of 38.27 feet, more or less, to a point; thence,
113. Bearing N 14° 02' 58" E for a distance of 16.89 feet, more or less, to a point; thence,
114. Bearing N 31° 37' 39" W for a distance of 20.84 feet, more or less, to a point; thence,
115. Bearing N 14° 02' 52" W for a distance of 22.51 feet, more or less, to a point; thence,

116. Bearing N 42° 32' 00" E for a distance of 22.23 feet, more or less, to a point; thence,
117. Bearing N 67° 38' 10" E for a distance of 25.11 feet, more or less, to a point; thence,
118. Bearing N 87° 30' 45" E for a distance of 31.45 feet, more or less, to a point; thence,
119. Bearing N 77° 28' 47" E for a distance of 37.78 feet, more or less, to a point; thence,
120. Bearing N 75° 04' 51" E for a distance of 42.41 feet, more or less, to a point; thence,
121. Bearing N 78° 41' 52" E for a distance of 41.79 feet, more or less, to a point; thence,
122. Bearing N 90° 00' 00" E for a distance of 46.45 feet, more or less, to a point; thence,
123. Bearing S 78° 19' 08" E for a distance of 40.46 feet, more or less, to a point; thence,
124. Bearing S 60° 16' 33" E for a distance of 33.04 feet, more or less, to a point; thence,
125. Bearing S 39° 49' 41" E for a distance of 32.00 feet, more or less, to a point; thence,
126. Bearing S 35° 00' 44" E for a distance of 33.33 feet, more or less, to a point; thence,
127. Bearing S 21° 49' 06" E for a distance of 36.76 feet, more or less, to a point; thence,
128. Bearing S 06° 50' 57" E for a distance of 34.37 feet, more or less, to a point; thence,
129. Bearing S 30° 58' 59" E for a distance of 23.88 feet, more or less, to a point; thence,
130. Bearing S 31° 20' 57" E for a distance of 36.76 feet, more or less, to a point; thence,
131. Bearing S 29° 22' 40" E for a distance of 50.13 feet, more or less, to a point; thence,
132. Bearing S 29° 39' 29" E for a distance of 91.11 feet, more or less, to a point; thence,
133. Bearing S 24° 38' 25" E for a distance of 36.05 feet, more or less, to a point; thence,
134. Bearing S 20° 58' 25" E for a distance of 60.90 feet, more or less, to a point; thence,
135. Bearing S 09° 52' 26" E for a distance of 31.87 feet, more or less, to a point; thence,
136. Bearing S 04° 05' 17" W for a distance of 19.16 feet, more or less, to a point; thence,
137. Bearing S 07° 07' 54" W for a distance of 33.02 feet, more or less, to a point; thence,
138. Bearing S 23° 58' 45" W for a distance of 26.89 feet, more or less, to a point; thence,
139. Bearing S 37° 35' 27" W for a distance of 22.40 feet, more or less, to a point; thence,
140. Bearing S 48° 08' 45" W for a distance of 53.19 feet, more or less, to a point; thence,
141. Bearing S 57° 17' 05" W for a distance of 45.46 feet, more or less, to a point; thence,
142. Bearing S 50° 12' 59" W for a distance of 42.67 feet, more or less, to a point; thence,
143. Bearing S 33° 42' 44" W for a distance of 39.38 feet, more or less, to a point; thence,
144. Bearing S 41° 39' 25" W for a distance of 32.89 feet, more or less, to a point; thence,
145. Bearing S 48° 23' 18" W for a distance of 32.89 feet, more or less, to a point; thence,
146. Bearing S 49° 25' 17" W for a distance of 37.77 feet, more or less, to a point; thence,
147. Bearing S 39° 49' 40" W for a distance of 31.99 feet, more or less, to a point; thence,
148. Bearing S 36° 53' 36" W for a distance of 34.14 feet, more or less, to a point; thence,
149. Bearing S 32° 29' 28" W for a distance of 35.61 feet, more or less, to a point; thence,
150. Bearing S 22° 29' 48" W for a distance of 42.85 feet, more or less, to a point; thence,
151. Bearing S 14° 28' 51" W for a distance of 43.71 feet, more or less, to a point; thence,
152. Bearing S 27° 25' 34" W for a distance of 41.52 feet, more or less, to a point; thence,
153. Bearing S 23° 24' 09" W for a distance of 55.03 feet, more or less, to a point; thence,
154. Bearing S 13° 08' 36" W for a distance of 54.58 feet, more or less, to a point; thence,
155. Bearing S 10° 26' 44" W for a distance of 52.75 feet, more or less, to a point; thence,
156. Bearing S 12° 12' 40" W for a distance of 51.68 feet, more or less, to a point; thence,
157. Bearing S 10° 11' 00" W for a distance of 54.09 feet, more or less, to a point; thence,
158. Bearing S 07° 54' 49" W for a distance of 49.61 feet, more or less, to a point; thence,
159. Bearing S 02° 00' 39" W for a distance of 77.86 feet, more or less, to a point; thence,
160. Bearing S 05° 49' 49" W for a distance of 67.24 feet, more or less, to a point; thence,
161. Bearing S 01° 14' 43" E for a distance of 62.81 feet, more or less, to a point; thence,

162. Bearing S 03° 54' 15" E for a distance of 60.20 feet, more or less, to a point; thence,
163. Bearing S 08° 08' 13" E for a distance of 38.61 feet, more or less, to a point; thence,
164. Bearing S 14° 02' 48" E for a distance of 56.28 feet, more or less, to a point; thence,
165. Bearing S 12° 41' 26" E for a distance of 55.97 feet, more or less, to a point; thence,
166. Bearing S 12° 25' 36" E for a distance of 51.58 feet, more or less, to a point; thence,
167. Bearing S 17° 45' 29" E for a distance of 35.83 feet, more or less, to a point; thence,
168. Bearing S 26° 34' 59" E for a distance of 33.58 feet, more or less, to a point; thence,
169. Bearing S 36° 16' 33" E for a distance of 25.40 feet, more or less, to a point; thence,
170. Bearing S 36° 02' 58" E for a distance of 37.14 feet, more or less, to a point; thence,
171. Bearing S 30° 40' 18" E for a distance of 42.85 feet, more or less, to a point; thence,
172. Bearing S 18° 26' 53" E for a distance of 30.22 feet, more or less, to a point; thence,
173. Bearing S 18° 02' 52" E for a distance of 61.73 feet, more or less, to a point; thence,
174. Bearing S 24° 19' 17" E for a distance of 46.44 feet, more or less, to a point; thence,
175. Bearing S 38° 10' 48" E for a distance of 24.31 feet, more or less, to a point; thence,
176. Bearing S 41° 50' 37" E for a distance of 34.81 feet, more or less, to a point; thence,
177. Bearing S 45° 01' 21" E for a distance of 28.97 feet, more or less, to a point; thence,
178. Bearing S 36° 53' 30" E for a distance of 34.14 feet, more or less, to a point; thence,
179. Bearing S 34° 05' 57" E for a distance of 56.05 feet, more or less, to a point; thence,
180. Bearing S 38° 10' 44" E for a distance of 48.62 feet, more or less, to a point; thence,
181. Bearing S 41° 47' 01" E for a distance of 51.26 feet, more or less, to a point; thence,
182. Bearing S 38° 58' 03" E for a distance of 59.29 feet, more or less, to a point; thence,
183. Bearing S 16° 42' 47" E for a distance of 28.50 feet, more or less, to a point; thence,
184. Bearing S 33° 42' 37" E for a distance of 34.46 feet, more or less, to a point; thence,
185. Bearing S 36° 02' 55" E for a distance of 37.14 feet, more or less, to a point; thence,
186. Bearing S 32° 01' 34" E for a distance of 51.52 feet, more or less, to a point; thence,
187. Bearing S 24° 09' 45" E for a distance of 43.39 feet, more or less, to a point; thence,
188. Bearing S 32° 14' 59" E for a distance of 74.25 feet, more or less, to a point; thence,
189. Bearing S 26° 35' 06" E for a distance of 42.74 feet, more or less, to a point; thence,
190. Bearing S 32° 01' 27" E for a distance of 25.76 feet, more or less, to a point; thence,
191. Bearing S 26° 35' 00" E for a distance of 39.69 feet, more or less, to a point; thence,
192. Bearing S 31° 50' 49" E for a distance of 46.60 feet, more or less, to a point; thence,
193. Bearing S 34° 43' 02" E for a distance of 43.18 feet, more or less, to a point; thence,
194. Bearing S 43° 10' 30" E for a distance of 29.95 feet, more or less, to a point; thence,
195. Bearing S 43° 10' 33" E for a distance of 29.95 feet, more or less, to a point; thence,
196. Bearing S 43° 33' 21" E for a distance of 37.67 feet, more or less, to a point; thence,
197. Bearing S 38° 10' 40" E for a distance of 48.62 feet, more or less, to a point; thence,
198. Bearing S 35° 00' 49" E for a distance of 33.33 feet, more or less, to a point; thence,
199. Bearing S 24° 19' 20" E for a distance of 46.44 feet, more or less, to a point; thence,
200. Bearing S 34° 02' 56" E for a distance of 93.66 feet, more or less, to a point; thence,
201. Bearing S 31° 14' 19" E for a distance of 52.69 feet, more or less, to a point; thence,
202. Bearing S 33° 17' 44" E for a distance of 52.26 feet, more or less, to a point; thence,
203. Bearing S 34° 53' 50" E for a distance of 54.92 feet, more or less, to a point; thence,
204. Bearing S 27° 14' 06" E for a distance of 53.73 feet, more or less, to a point; thence,
205. Bearing S 39° 34' 54" E for a distance of 40.74 feet, more or less, to a point; thence,
206. Bearing S 31° 20' 57" E for a distance of 36.76 feet, more or less, to a point; thence,
207. Bearing S 36° 53' 30" E for a distance of 40.96 feet, more or less, to a point; thence,

208. Bearing S 26° 34' 55" E for a distance of 27.48 feet, more or less, to a point; thence,
209. Bearing S 30° 05' 20" E for a distance of 59.95 feet, more or less, to a point; thence,
210. Bearing S 37° 15' 26" E for a distance of 42.88 feet, more or less, to a point; thence,
211. Bearing S 27° 19' 07" E for a distance of 47.63 feet, more or less, to a point; thence,
212. Bearing S 22° 23' 48" E for a distance of 25.10 feet, more or less, to a point; thence,
213. Bearing S 14° 02' 48" E for a distance of 33.77 feet, more or less, to a point; thence,
214. Bearing S 12° 16' 30" E for a distance of 32.13 feet, more or less, to a point; thence,
215. Bearing S 23° 12' 44" E for a distance of 20.79 feet, more or less, to a point; thence,
216. Bearing S 42° 43' 58" E for a distance of 24.16 feet, more or less, to a point; thence,
217. Bearing S 37° 35' 35" E for a distance of 22.40 feet, more or less, to a point; thence,
218. Bearing S 34° 18' 26" E for a distance of 36.36 feet, more or less, to a point; thence,
219. Bearing S 28° 16' 39" E for a distance of 32.38 feet, more or less, to a point; thence,
220. Bearing S 22° 56' 58" E for a distance of 38.54 feet, more or less, to a point; thence,
221. Bearing S 04° 58' 23" E for a distance of 31.52 feet, more or less, to a point; thence,
222. Bearing S 10° 07' 59" E for a distance of 38.83 feet, more or less, to a point; thence,
223. Bearing S 12° 06' 11" E for a distance of 19.55 feet, more or less, to a point; thence,
224. Bearing S 25° 21' 54" E for a distance of 28.70 feet, more or less, to a point; thence,
225. Bearing S 30° 58' 59" E for a distance of 23.88 feet, more or less, to a point; thence,
226. Bearing S 30° 29' 11" E for a distance of 26.93 feet, more or less, to a point; thence,
227. Bearing S 42° 17' 45" E for a distance of 40.60 feet, more or less, to a point; thence,
228. Bearing S 32° 22' 08" E for a distance of 48.48 feet, more or less, to a point; thence,
229. Bearing S 20° 47' 11" E for a distance of 42.34 feet, more or less, to a point; thence,
230. Bearing S 25° 43' 40" E for a distance of 40.91 feet, more or less, to a point; thence,
231. Bearing S 24° 07' 11" E for a distance of 56.83 feet, more or less, to a point; thence,
232. Bearing S 05° 11' 53" E for a distance of 30.16 feet, more or less, to a point; thence,
233. Bearing S 00° 00' 00" E for a distance of 21.84 feet, more or less, to a point; thence,
234. Bearing S 30° 16' 33" W for a distance of 18.97 feet, more or less, to a point; thence,
235. Bearing S 36° 16' 34" W for a distance of 25.40 feet, more or less, to a point; thence,
236. Bearing S 20° 54' 37" W for a distance of 28.78 feet, more or less, to a point; thence,
237. Bearing S 15° 32' 20" W for a distance of 25.50 feet, more or less, to a point; thence,
238. Bearing S 29° 04' 23" W for a distance of 28.11 feet, more or less, to a point; thence,
239. Bearing S 52° 27' 16" W for a distance of 22.40 feet, more or less, to a point; thence,
240. Bearing S 51° 51' 53" W for a distance of 24.31 feet, more or less, to a point; thence,
241. Bearing S 55° 01' 49" W for a distance of 33.34 feet, more or less, to a point; thence,
242. Bearing S 68° 12' 45" W for a distance of 29.42 feet, more or less, to a point; thence,
243. Bearing N 87° 23' 58" W for a distance of 30.09 feet, more or less, to a point; thence,
244. Bearing N 80° 08' 34" W for a distance of 31.89 feet, more or less, to a point; thence,
245. Bearing N 81° 52' 29" W for a distance of 28.98 feet, more or less, to a point; thence,
246. Bearing N 69° 09' 40" W for a distance of 30.70 feet, more or less, to a point; thence,
247. Bearing N 70° 55' 08" W for a distance of 37.58 feet, more or less, to a point; thence,
248. Bearing N 80° 55' 08" W for a distance of 34.59 feet, more or less, to a point; thence,
249. Bearing N 83° 25' 25" W for a distance of 35.76 feet, more or less, to a point; thence,
250. Bearing N 70° 55' 13" W for a distance of 37.59 feet, more or less, to a point; thence,
251. Bearing S 87° 30' 45" W for a distance of 31.45 feet, more or less, to a point; thence,
252. Bearing S 78° 41' 58" W for a distance of 34.83 feet, more or less, to a point; thence,
253. Bearing S 67° 10' 54" W for a distance of 28.16 feet, more or less, to a point; thence,

254. Bearing S 54° 10' 56" W for a distance of 30.32 feet, more or less, to a point; thence,
255. Bearing S 75° 58' 31" W for a distance of 33.80 feet, more or less, to a point; thence,
256. Bearing S 59° 33' 15" W for a distance of 26.94 feet, more or less, to a point; thence,
257. Bearing S 51° 43' 56" W for a distance of 33.06 feet, more or less, to a point; thence,
258. Bearing S 45° 01' 20" W for a distance of 34.76 feet, more or less, to a point; thence,
259. Bearing S 45° 54' 18" W for a distance of 62.77 feet, more or less, to a point; thence,
260. Bearing S 37° 15' 27" W for a distance of 42.88 feet, more or less, to a point; thence,
261. Bearing S 36° 33' 02" W for a distance of 45.88 feet, more or less, to a point; thence,
262. Bearing S 23° 12' 52" W for a distance of 41.59 feet, more or less, to a point; thence,
263. Bearing S 14° 02' 49" W for a distance of 33.77 feet, more or less, to a point; thence,
264. Bearing S 16° 16' 21" W for a distance of 34.13 feet, more or less, to a point; thence,
265. Bearing S 27° 55' 03" W for a distance of 26.26 feet, more or less, to a point; thence,
266. Bearing S 32° 38' 21" W for a distance of 40.53 feet, more or less, to a point; thence,
267. Bearing S 40° 37' 28" W for a distance of 37.77 feet, more or less, to a point; thence,
268. Bearing S 39° 18' 45" W for a distance of 38.81 feet, more or less, to a point; thence,
269. Bearing S 18° 43' 28" W for a distance of 64.52 feet, more or less, to a point; thence,
270. Bearing S 19° 18' 19" W for a distance of 28.93 feet, more or less, to a point; thence,
271. Bearing S 31° 20' 59" W for a distance of 36.76 feet, more or less, to a point; thence,
272. Bearing S 33° 07' 57" W for a distance of 37.49 feet, more or less, to a point; thence,
273. Bearing S 27° 29' 35" W for a distance of 38.47 feet, more or less, to a point; thence,
274. Bearing S 29° 33' 34" W for a distance of 47.08 feet, more or less, to a point; thence,
275. Bearing S 20° 14' 20" W for a distance of 27.64 feet, more or less, to a point; thence,
276. Bearing S 16° 56' 31" W for a distance of 32.82 feet, more or less, to a point; thence,
277. Bearing S 17° 27' 34" W for a distance of 50.08 feet, more or less, to a point; thence,
278. Bearing S 25° 28' 48" W for a distance of 31.76 feet, more or less, to a point; thence,
279. Bearing S 30° 59' 02" W for a distance of 39.81 feet, more or less, to a point; thence,
280. Bearing S 24° 52' 54" W for a distance of 61.69 feet, more or less, to a point; thence,
281. Bearing S 27° 16' 27" W for a distance of 50.68 feet, more or less, to a point; thence,
282. Bearing S 21° 37' 49" W for a distance of 77.83 feet, more or less, to a point; thence,
283. Bearing S 16° 50' 10" W for a distance of 62.44 feet, more or less, to a point; thence,
284. Bearing S 11° 53' 52" W for a distance of 53.01 feet, more or less, to a point; thence,
285. Bearing S 14° 16' 05" W for a distance of 171.84 feet, more or less, to a point; thence,
286. Bearing S 14° 02' 53" W for a distance of 33.77 feet, more or less, to a point; thence,
287. Bearing S 02° 17' 30" W for a distance of 34.16 feet, more or less, to a point; thence,
288. Bearing S 00° 00' 00" W for a distance of 38.22 feet, more or less, to a point; thence,
289. Bearing S 02° 23' 15" E for a distance of 32.79 feet, more or less, to a point; thence,
290. Bearing S 08° 32' 11" W for a distance of 27.61 feet, more or less, to a point; thence,
291. Bearing S 14° 02' 51" W for a distance of 33.77 feet, more or less, to a point; thence,
292. Bearing S 17° 00' 13" W for a distance of 51.39 feet, more or less, to a point; thence,
293. Bearing S 20° 52' 10" W for a distance of 30.68 feet, more or less, to a point; thence,
294. Bearing S 04° 24' 08" W for a distance of 17.80 feet, more or less, to a point; thence,
295. Bearing S 03° 41' 40" E for a distance of 42.40 feet, more or less, to a point; thence,
296. Bearing S 06° 10' 31" E for a distance of 50.80 feet, more or less, to a point; thence,
297. Bearing S 07° 43' 15" E for a distance of 34.25 feet, more or less, to a point; thence,
298. Bearing S 06° 55' 02" E for a distance of 45.38 feet, more or less, to a point; thence,
299. Bearing S 18° 26' 57" E for a distance of 25.90 feet, more or less, to a point; thence,

300. Bearing S 20° 09' 00" E for a distance of 43.62 feet, more or less, to a point; thence,
301. Bearing S 26° 35' 02" E for a distance of 36.63 feet, more or less, to a point; thence,
302. Bearing S 24° 27' 43" E for a distance of 49.49 feet, more or less, to a point; thence,
303. Bearing S 29° 16' 06" E for a distance of 39.12 feet, more or less, to a point; thence,
304. Bearing S 35° 19' 54" E for a distance of 40.16 feet, more or less, to a point; thence,
305. Bearing S 55° 54' 26" E for a distance of 51.14 feet, more or less, to a point; thence,
306. Bearing S 67° 15' 55" E for a distance of 45.92 feet, more or less, to a point; thence,
307. Bearing S 71° 34' 46" E for a distance of 25.92 feet, more or less, to a point; thence,
308. Bearing S 80° 08' 26" E for a distance of 31.89 feet, more or less, to a point; thence,
309. Bearing S 87° 16' 35" E for a distance of 28.72 feet, more or less, to a point; thence,
310. Bearing S 70° 21' 41" E for a distance of 20.31 feet, more or less, to a point; thence,
311. Bearing S 67° 46' 03" E for a distance of 32.47 feet, more or less, to a point; thence,
312. Bearing S 69° 27' 31" E for a distance of 35.01 feet, more or less, to a point; thence,
313. Bearing S 74° 04' 02" E for a distance of 29.84 feet, more or less, to a point; thence,
314. Bearing S 73° 27' 19" E for a distance of 52.73 feet, more or less, to a point; thence,
315. Bearing S 84° 24' 20" E for a distance of 70.01 feet, more or less, to a point; thence,
316. Bearing N 86° 38' 11" E for a distance of 46.53 feet, more or less, to a point; thence,
317. Bearing N 71° 09' 37" E for a distance of 59.18 feet, more or less, to a point; thence,
318. Bearing N 66° 49' 07" E for a distance of 41.61 feet, more or less, to a point; thence,
319. Bearing N 60° 39' 44" E for a distance of 50.15 feet, more or less, to a point; thence,
320. Bearing N 62° 40' 13" E for a distance of 44.60 feet, more or less, to a point; thence,
321. Bearing N 52° 47' 11" E for a distance of 42.89 feet, more or less, to a point; thence,
322. Bearing N 40° 26' 53" E for a distance of 48.43 feet, more or less, to a point; thence,
323. Bearing N 27° 16' 28" E for a distance of 50.68 feet, more or less, to a point; thence,
324. Bearing N 43° 45' 10" E for a distance of 27.16 feet, more or less, to a point; thence,
325. Bearing N 42° 32' 01" E for a distance of 22.23 feet, more or less, to a point; thence,
326. Bearing N 31° 27' 01" E for a distance of 28.80 feet, more or less, to a point; thence,
327. Bearing N 03° 00' 55" E for a distance of 25.97 feet, more or less, to a point; thence,
328. Bearing N 23° 12' 55" E for a distance of 20.79 feet, more or less, to a point; thence,
329. Bearing N 15° 32' 03" E for a distance of 25.50 feet, more or less, to a point; thence,
330. Bearing N 30° 05' 22" E for a distance of 29.98 feet, more or less, to a point; thence,
331. Bearing N 29° 45' 49" E for a distance of 22.02 feet, more or less, to a point; thence,
332. Bearing N 25° 34' 43" E for a distance of 34.81 feet, more or less, to a point; thence,
333. Bearing N 45° 01' 25" E for a distance of 30.90 feet, more or less, to a point; thence,
334. Bearing N 55° 38' 28" E for a distance of 31.44 feet, more or less, to a point; thence,
335. Bearing N 59° 45' 43" E for a distance of 37.95 feet, more or less, to a point; thence,
336. Bearing N 82° 34' 31" E for a distance of 31.69 feet, more or less, to a point; thence,
337. Bearing N 82° 52' 51" E for a distance of 44.06 feet, more or less, to a point; thence,
338. Bearing N 83° 25' 24" E for a distance of 35.76 feet, more or less, to a point; thence,
339. Bearing N 75° 15' 58" E for a distance of 26.84 feet, more or less, to a point; thence,
340. Bearing N 74° 18' 15" E for a distance of 45.41 feet, more or less, to a point; thence,
341. Bearing N 80° 32' 38" E for a distance of 41.55 feet, more or less, to a point; thence,
342. Bearing N 87° 52' 45" E for a distance of 36.91 feet, more or less, to a point; thence,
343. Bearing S 86° 03' 24" E for a distance of 39.71 feet, more or less, to a point; thence,
344. Bearing N 83° 29' 08" E for a distance of 48.13 feet, more or less, to a point; thence,
345. Bearing N 87° 23' 56" E for a distance of 60.17 feet, more or less, to a point; thence,

346. Bearing S 88° 36' 11" E for a distance of 56.03 feet, more or less, to a point; thence,
347. Bearing N 86° 11' 21" E for a distance of 41.08 feet, more or less, to a point; thence,
348. Bearing S 84° 48' 36" E for a distance of 30.18 feet, more or less, to a point; thence,
349. Bearing S 74° 45' 27" E for a distance of 31.15 feet, more or less, to a point; thence,
350. Bearing S 68° 12' 48" E for a distance of 29.42 feet, more or less, to a point; thence,
351. Bearing S 59° 03' 23" E for a distance of 39.82 feet, more or less, to a point; thence,
352. Bearing S 46° 25' 15" E for a distance of 39.60 feet, more or less, to a point; thence,
353. Bearing S 33° 11' 49" E for a distance of 42.42 feet, more or less, to a point; thence,
354. Bearing S 21° 03' 16" E for a distance of 38.03 feet, more or less, to a point; thence,
355. Bearing S 13° 34' 56" E for a distance of 40.73 feet, more or less, to a point; thence,
356. Bearing S 10° 18' 43" E for a distance of 45.79 feet, more or less, to a point; thence,
357. Bearing S 06° 29' 18" E for a distance of 60.45 feet, more or less, to a point; thence,
358. Bearing S 09° 00' 28" E for a distance of 78.36 feet, more or less, to a point; thence,
359. Bearing S 05° 42' 59" E for a distance of 27.44 feet, more or less, to a point; thence,
360. Bearing S 11° 19' 12" W for a distance of 27.84 feet, more or less, to a point; thence,
361. Bearing S 06° 50' 49" W for a distance of 34.37 feet, more or less, to a point; thence,
362. Bearing S 04° 46' 08" W for a distance of 32.87 feet, more or less, to a point; thence,
363. Bearing S 02° 12' 14" E for a distance of 35.52 feet, more or less, to a point; thence,
364. Bearing S 09° 10' 06" W for a distance of 42.86 feet, more or less, to a point; thence,
365. Bearing S 21° 15' 58" W for a distance of 26.37 feet, more or less, to a point; thence,
366. Bearing S 33° 02' 44" W for a distance of 32.57 feet, more or less, to a point; thence,
367. Bearing S 52° 36' 55" W for a distance of 29.23 feet, more or less, to a point; thence,
368. Bearing S 64° 27' 33" W for a distance of 34.83 feet, more or less, to a point; thence,
369. Bearing S 61° 34' 32" W for a distance of 37.28 feet, more or less, to a point; thence,
370. Bearing S 51° 58' 33" W for a distance of 39.89 feet, more or less, to a point; thence,
371. Bearing S 42° 31' 57" W for a distance of 44.46 feet, more or less, to a point; thence,
372. Bearing S 56° 50' 33" W for a distance of 42.43 feet, more or less, to a point; thence,
373. Bearing S 53° 59' 42" W for a distance of 37.15 feet, more or less, to a point; thence,
374. Bearing S 72° 54' 39" W for a distance of 37.16 feet, more or less, to a point; thence,
375. Bearing S 67° 32' 11" W for a distance of 42.87 feet, more or less, to a point; thence,
376. Bearing S 63° 57' 53" W for a distance of 68.42 feet, more or less, to a point; thence,
377. Bearing S 63° 27' 16" W for a distance of 76.36 feet, more or less, to a point; thence,
378. Bearing S 51° 55' 57" W for a distance of 64.21 feet, more or less, to a point; thence,
379. Bearing S 68° 01' 02" W for a distance of 46.55 feet, more or less, to a point; thence,
380. Bearing S 62° 02' 21" W for a distance of 49.49 feet, more or less, to a point; thence,
381. Bearing S 69° 14' 34" W for a distance of 42.37 feet, more or less, to a point; thence,
382. Bearing S 62° 07' 20" W for a distance of 52.55 feet, more or less, to a point; thence,
383. Bearing S 67° 29' 44" W for a distance of 60.63 feet, more or less, to a point; thence,
384. Bearing S 66° 59' 28" W for a distance of 59.37 feet, more or less, to a point; thence,
385. Bearing S 66° 37' 53" W for a distance of 55.06 feet, more or less, to a point; thence,
386. Bearing S 57° 52' 08" W for a distance of 56.46 feet, more or less, to a point; thence,
387. Bearing S 53° 09' 03" W for a distance of 61.46 feet, more or less, to a point; thence,
388. Bearing S 51° 34' 09" W for a distance of 59.29 feet, more or less, to a point; thence,
389. Bearing S 46° 55' 58" W for a distance of 57.97 feet, more or less, to a point; thence,
390. Bearing S 48° 50' 12" W for a distance of 58.07 feet, more or less, to a point; thence,
391. Bearing S 42° 43' 56" W for a distance of 48.32 feet, more or less, to a point; thence,

392. Bearing S 31° 26' 59" W for a distance of 57.60 feet, more or less, to a point; thence,
393. Bearing S 21° 49' 04" W for a distance of 66.17 feet, more or less, to a point; thence,
394. Bearing S 27° 50' 35" W for a distance of 55.58 feet, more or less, to a point; thence,
395. Bearing S 23° 43' 07" W for a distance of 61.13 feet, more or less, to a point; thence,
396. Bearing S 28° 19' 14" W for a distance of 60.48 feet, more or less, to a point; thence,
397. Bearing S 14° 59' 09" W for a distance of 53.56 feet, more or less, to a point; thence,
398. Bearing S 04° 46' 06" W for a distance of 49.31 feet, more or less, to a point; thence,
399. Bearing S 05° 11' 52" W for a distance of 45.23 feet, more or less, to a point; thence,
400. Bearing S 16° 16' 15" W for a distance of 34.13 feet, more or less, to a point; thence,
401. Bearing S 17° 50' 05" W for a distance of 40.15 feet, more or less, to a point; thence,
402. Bearing S 14° 02' 50" W for a distance of 33.77 feet, more or less, to a point; thence,
403. Bearing S 06° 43' 01" E for a distance of 23.37 feet, more or less, to a point; thence,
404. Bearing S 05° 42' 52" E for a distance of 41.16 feet, more or less, to a point; thence,
405. Bearing S 01° 54' 38" E for a distance of 40.97 feet, more or less, to a point; thence,
406. Bearing S 05° 42' 52" E for a distance of 41.16 feet, more or less, to a point; thence,
407. Bearing S 11° 19' 17" E for a distance of 41.76 feet, more or less, to a point; thence,
408. Bearing S 14° 02' 45" E for a distance of 45.03 feet, more or less, to a point; thence,
409. Bearing S 17° 00' 13" E for a distance of 51.39 feet, more or less, to a point; thence,
410. Bearing S 21° 23' 09" E for a distance of 67.44 feet, more or less, to a point; thence,
411. Bearing S 28° 56' 32" E for a distance of 69.75 feet, more or less, to a point; thence,
412. Bearing S 46° 56' 06" E for a distance of 42.90 feet, more or less, to a point; thence,
413. Bearing S 50° 32' 59" E for a distance of 39.18 feet, more or less, to a point; thence,
414. Bearing S 52° 40' 22" E for a distance of 42.53 feet, more or less, to a point; thence,
415. Bearing S 62° 52' 09" E for a distance of 39.00 feet, more or less, to a point; thence,
416. Bearing S 69° 05' 18" E for a distance of 32.39 feet, more or less, to a point; thence,
417. Bearing S 82° 52' 56" E for a distance of 35.87 feet, more or less, to a point; thence,
418. Bearing N 87° 08' 23" E for a distance of 53.46 feet, more or less, to a point; thence,
419. Bearing N 71° 34' 44" E for a distance of 42.21 feet, more or less, to a point; thence,
420. Bearing N 72° 48' 51" E for a distance of 39.12 feet, more or less, to a point; thence,
421. Bearing N 72° 00' 39" E for a distance of 37.43 feet, more or less, to a point; thence,
422. Bearing N 60° 16' 23" E for a distance of 28.69 feet, more or less, to a point; thence,
423. Bearing N 71° 51' 38" E for a distance of 57.12 feet, more or less, to a point; thence,
424. Bearing N 56° 57' 05" E for a distance of 45.65 feet, more or less, to a point; thence,
425. Bearing N 60° 16' 30" E for a distance of 43.04 feet, more or less, to a point; thence,
426. Bearing N 59° 24' 05" E for a distance of 50.66 feet, more or less, to a point; thence,
427. Bearing N 55° 23' 49" E for a distance of 45.41 feet, more or less, to a point; thence,
428. Bearing N 52° 07' 47" E for a distance of 61.96 feet, more or less, to a point; thence,
429. Bearing N 43° 35' 20" E for a distance of 50.34 feet, more or less, to a point; thence,
430. Bearing N 43° 17' 16" E for a distance of 41.53 feet, more or less, to a point; thence,
431. Bearing N 34° 02' 28" E for a distance of 42.92 feet, more or less, to a point; thence,
432. Bearing N 25° 45' 28" E for a distance of 55.29 feet, more or less, to a point; thence,
433. Bearing N 37° 02' 01" E for a distance of 72.40 feet, more or less, to a point; thence,
434. Bearing N 36° 16' 32" E for a distance of 49.63 feet, more or less, to a point; thence,
435. Bearing N 29° 33' 29" E for a distance of 61.34 feet, more or less, to a point; thence,
436. Bearing N 43° 28' 32" E for a distance of 23.28 feet, more or less, to a point; thence,
437. Bearing N 42° 58' 40" E for a distance of 35.25 feet, more or less, to a point; thence,

438. Bearing N 61° 43' 06" E for a distance of 26.27 feet, more or less, to a point; thence,
439. Bearing N 76° 49' 10" E for a distance of 58.49 feet, more or less, to a point; thence,
440. Bearing S 89° 25' 37" E for a distance of 89.00 feet, more or less, to a point; thence,
441. Bearing S 68° 24' 05" E for a distance of 50.73 feet, more or less, to a point; thence,
442. Bearing S 65° 14' 34" E for a distance of 76.44 feet, more or less, to a point; thence,
443. Bearing S 54° 22' 55" E for a distance of 58.02 feet, more or less, to a point; thence,
444. Bearing S 46° 36' 51" E for a distance of 45.31 feet, more or less, to a point; thence,
445. Bearing S 57° 21' 30" E for a distance of 41.22 feet, more or less, to a point; thence,
446. Bearing S 55° 51' 42" E for a distance of 30.11 feet, more or less, to a point; thence,
447. Bearing S 27° 32' 39" E for a distance of 71.20 feet, more or less, to a point; thence,
448. Bearing S 19° 30' 01" E for a distance of 61.32 feet, more or less, to a point; thence,
449. Bearing S 17° 06' 58" E for a distance of 48.38 feet, more or less, to a point; thence,
450. Bearing S 16° 58' 50" E for a distance of 54.85 feet, more or less, to a point; thence,
451. Bearing S 11° 39' 49" E for a distance of 54.41 feet, more or less, to a point; thence,
452. Bearing S 03° 14' 33" E for a distance of 47.20 feet, more or less, to a point; thence,
453. Bearing S 16° 50' 03" E for a distance of 39.95 feet, more or less, to a point; thence,
454. Bearing S 11° 32' 36" E for a distance of 44.47 feet, more or less, to a point; thence,
455. Bearing S 13° 15' 04" E for a distance of 62.12 feet, more or less, to a point; thence,
456. Bearing S 12° 14' 09" E for a distance of 54.59 feet, more or less, to a point; thence,
457. Bearing S 08° 28' 33" E for a distance of 42.25 feet, more or less, to a point; thence,
458. Bearing S 02° 51' 54" W for a distance of 53.42 feet, more or less, to a point; thence,
459. Bearing S 07° 43' 43" E for a distance of 52.94 feet, more or less, to a point; thence,
460. Bearing S 14° 05' 03" E for a distance of 33.61 feet, more or less, to a point; thence,
461. Bearing S 14° 21' 37" E for a distance of 39.47 feet, more or less, to a point; thence,
462. Bearing S 01° 06' 10" E for a distance of 46.25 feet, more or less, to a point; thence,
463. Bearing S 01° 56' 36" W for a distance of 52.49 feet, more or less, to a point; thence,
464. Bearing S 05° 04' 58" E for a distance of 40.17 feet, more or less, to a point; thence,
465. Bearing S 16° 48' 41" E for a distance of 49.23 feet, more or less, to a point; thence,
466. Bearing S 35° 41' 52" E for a distance of 42.70 feet, more or less, to a point; thence,
467. Bearing S 13° 44' 49" E for a distance of 41.19 feet, more or less, to a point; thence,
468. Bearing S 13° 24' 22" E for a distance of 57.53 feet, more or less, to a point; thence,
469. Bearing S 05° 57' 05" E for a distance of 85.83 feet, more or less, to a point; thence,
470. Bearing S 01° 19' 58" W for a distance of 76.49 feet, more or less, to a point; thence,
471. Bearing S 06° 35' 16" W for a distance of 69.82 feet, more or less, to a point; thence,
472. Bearing S 09° 05' 49" W for a distance of 45.03 feet, more or less, to a point; thence,
473. Bearing S 18° 26' 55" W for a distance of 42.18 feet, more or less, to a point; thence,
474. Bearing S 29° 04' 30" W for a distance of 27.47 feet, more or less, to a point; thence,
475. Bearing S 17° 00' 13" W for a distance of 33.47 feet, more or less, to a point; thence,
476. Bearing S 22° 29' 37" W for a distance of 27.91 feet, more or less, to a point; thence,
477. Bearing S 25° 52' 57" W for a distance of 35.55 feet, more or less, to a point; thence,
478. Bearing S 43° 30' 56" W for a distance of 47.82 feet, more or less, to a point; thence,
479. Bearing S 45° 01' 24" W for a distance of 41.52 feet, more or less, to a point; thence,
480. Bearing S 31° 43' 15" W for a distance of 35.54 feet, more or less, to a point; thence,
481. Bearing S 14° 02' 49" W for a distance of 40.33 feet, more or less, to a point; thence,
482. Bearing S 18° 56' 22" W for a distance of 32.90 feet, more or less, to a point; thence,
483. Bearing S 28° 24' 46" W for a distance of 37.41 feet, more or less, to a point; thence,

- 484. Bearing S 35° 40' 40" W for a distance of 50.35 feet, more or less, to a point; thence,
- 485. Bearing S 50° 22' 42" W for a distance of 40.44 feet, more or less, to a point; thence,
- 486. Bearing S 62° 27' 53" W for a distance of 46.17 feet, more or less, to a point; thence,
- 487. Bearing S 62° 43' 06" W for a distance of 31.04 feet, more or less, to a point; thence,
- 488. Bearing S 69° 47' 24" W for a distance of 36.04 feet, more or less, to a point; thence,
- 489. Bearing S 77° 49' 51" W for a distance of 38.23 feet, more or less, to a point; thence,
- 490. Bearing S 68° 53' 28" W for a distance of 41.97 feet, more or less, to a point; thence,
- 491. Bearing S 69° 14' 34" W for a distance of 55.20 feet, more or less, to a point; thence,
- 492. Bearing S 74° 29' 16" W for a distance of 66.50 feet, more or less, to a point; thence,
- 493. Bearing S 84° 13' 49" W for a distance of 79.61 feet, more or less, to a point; thence,
- 494. Bearing S 88° 25' 53" W for a distance of 64.99 feet, more or less, to a point; thence,
- 495. Bearing N 83° 57' 00" W for a distance of 59.06 feet, more or less, to a point; thence,
- 496. Bearing N 79° 16' 11" W for a distance of 52.53 feet, more or less, to a point; thence,
- 497. Bearing N 74° 19' 54" W for a distance of 52.68 feet, more or less, to a point; thence,
- 498. Bearing N 59° 26' 07" W for a distance of 38.87 feet, more or less, to a point; thence,
- 499. Bearing N 54° 04' 45" W for a distance of 43.96 feet, more or less, to a point; thence,
- 500. Bearing N 23° 58' 46" W for a distance of 52.55 feet, more or less, to a point; thence,
- 501. Bearing N 03° 54' 09" W for a distance of 39.22 feet, more or less, to a point; thence,
- 502. Bearing N 04° 05' 27" W for a distance of 37.44 feet, more or less, to a point; thence,
- 503. Bearing N 11° 36' 02" E for a distance of 35.40 feet, more or less, to a point; thence,
- 504. Bearing N 10° 05' 22" E for a distance of 40.64 feet, more or less, to a point; thence,
- 505. Bearing N 26° 35' 01" E for a distance of 31.82 feet, more or less, to a point; thence,
- 506. Bearing N 25° 45' 28" E for a distance of 55.29 feet, more or less, to a point; thence,
- 507. Bearing N 33° 17' 51" E for a distance of 34.04 feet, more or less, to a point; thence,
- 508. Bearing N 40° 29' 03" E for a distance of 39.75 feet, more or less, to a point; thence,
- 509. Bearing N 30° 59' 07" E for a distance of 36.30 feet, more or less, to a point; thence,
- 510. Bearing N 41° 12' 29" E for a distance of 28.37 feet, more or less, to a point; thence,
- 511. Bearing N 31° 17' 04" E for a distance of 29.13 feet, more or less, to a point; thence,
- 512. Bearing N 25° 48' 43" E for a distance of 20.65 feet, more or less, to a point; thence,
- 513. Bearing N 14° 17' 32" E for a distance of 50.47 feet, more or less, to a point; thence,
- 514. Bearing N 05° 42' 51" E for a distance of 35.75 feet, more or less, to a point; thence,
- 515. Bearing N 00° 00' 00" E for a distance of 41.79 feet, more or less, to a point; thence,
- 516. Bearing N 07° 07' 48" W for a distance of 43.01 feet, more or less, to a point; thence,
- 517. Bearing N 08° 49' 41" W for a distance of 52.19 feet, more or less, to a point; thence,
- 518. Bearing N 06° 12' 27" W for a distance of 41.14 feet, more or less, to a point; thence,
- 519. Bearing N 11° 04' 42" W for a distance of 41.68 feet, more or less, to a point; thence,
- 520. Bearing N 19° 33' 11" W for a distance of 29.25 feet, more or less, to a point; thence,
- 521. Bearing N 20° 20' 14" W for a distance of 25.61 feet, more or less, to a point; thence,
- 522. Bearing N 40° 50' 16" W for a distance of 25.86 feet, more or less, to a point; thence,
- 523. Bearing N 53° 23' 17" W for a distance of 43.24 feet, more or less, to a point; thence,
- 524. Bearing N 42° 09' 43" W for a distance of 25.19 feet, more or less, to a point; thence,
- 525. Bearing N 41° 38' 34" W for a distance of 81.82 feet, more or less, to a point; thence,
- 526. Bearing N 36° 22' 10" W for a distance of 58.53 feet, more or less, to a point; thence,
- 527. Bearing N 51° 56' 01" W for a distance of 41.82 feet, more or less, to a point; thence,
- 528. Bearing N 55° 51' 42" W for a distance of 60.21 feet, more or less, to a point; thence,
- 529. Bearing N 66° 49' 12" W for a distance of 40.66 feet, more or less, to a point; thence,

530. Bearing N 72° 13' 40" W for a distance of 49.53 feet, more or less, to a point; thence,
531. Bearing N 84° 17' 38" W for a distance of 44.72 feet, more or less, to a point; thence,
532. Bearing S 87° 33' 57" W for a distance of 41.86 feet, more or less, to a point; thence,
533. Bearing S 64° 33' 15" W for a distance of 20.70 feet, more or less, to a point; thence,
534. Bearing S 47° 30' 47" W for a distance of 28.96 feet, more or less, to a point; thence,
535. Bearing S 11° 38' 31" W for a distance of 30.87 feet, more or less, to a point; thence,
536. Bearing S 14° 55' 20" W for a distance of 40.35 feet, more or less, to a point; thence,
537. Bearing S 21° 35' 19" W for a distance of 16.80 feet, more or less, to a point; thence,
538. Bearing S 47° 11' 01" W for a distance of 27.26 feet, more or less, to a point; thence,
539. Bearing S 48° 26' 52" W for a distance of 29.75 feet, more or less, to a point; thence,
540. Bearing S 49° 53' 23" W for a distance of 18.43 feet, more or less, to a point; thence,
541. Bearing S 25° 39' 35" W for a distance of 20.15 feet, more or less, to a point; thence,
542. Bearing S 00° 00' 01" W for a distance of 22.52 feet, more or less, to a point; thence,
543. Bearing S 24° 04' 26" E for a distance of 22.28 feet, more or less, to a point; thence,
544. Bearing S 48° 23' 41" E for a distance of 8.75 feet, more or less, to a point; thence,
545. Bearing S 45° 23' 26" E for a distance of 34.85 feet, more or less, to a point; thence,
546. Bearing S 61° 31' 22" E for a distance of 29.89 feet, more or less, to a point; thence,
547. Bearing S 44° 05' 02" E for a distance of 32.37 feet, more or less, to a point; thence,
548. Bearing S 21° 31' 06" E for a distance of 26.61 feet, more or less, to a point; thence,
549. Bearing S 04° 31' 02" E for a distance of 28.59 feet, more or less, to a point; thence,
550. Bearing S 02° 17' 30" W for a distance of 37.53 feet, more or less, to a point; thence,
551. Bearing S 03° 59' 39" E for a distance of 32.33 feet, more or less, to a point; thence,
552. Bearing S 07° 15' 28" E for a distance of 41.59 feet, more or less, to a point; thence,
553. Bearing S 14° 20' 01" E for a distance of 36.39 feet, more or less, to a point; thence,
554. Bearing S 07° 03' 28" W for a distance of 73.31 feet, more or less, to a point; thence,
555. Bearing S 03° 44' 03" W for a distance of 34.58 feet, more or less, to a point; thence,
556. Bearing S 02° 47' 03" E for a distance of 30.74 feet, more or less, to a point; thence,
557. Bearing S 02° 10' 35" W for a distance of 59.30 feet, more or less, to a point; thence,
558. Bearing S 07° 54' 45" E for a distance of 54.53 feet, more or less, to a point; thence,
559. Bearing S 03° 10' 51" W for a distance of 40.57 feet, more or less, to a point; thence,
560. Bearing S 13° 00' 31" W for a distance of 20.01 feet, more or less, to a point; thence,
561. Bearing S 10° 37' 39" W for a distance of 36.63 feet, more or less, to a point; thence,
562. Bearing S 13° 38' 12" W for a distance of 25.47 feet, more or less, to a point; thence,
563. Bearing S 05° 23' 30" E for a distance of 39.93 feet, more or less, to a point; thence,
564. Bearing S 07° 36' 08" E for a distance of 34.05 feet, more or less, to a point; thence,
565. Bearing S 07° 30' 12" E for a distance of 28.75 feet, more or less, to a point; thence,
566. Bearing S 03° 14' 32" W for a distance of 54.03 feet, more or less, to a point; thence,
567. Bearing S 09° 28' 12" W for a distance of 31.94 feet, more or less, to a point; thence,
568. Bearing S 14° 02' 51" E for a distance of 52.58 feet, more or less, to a point; thence,
569. Bearing S 16° 20' 53" E for a distance of 45.34 feet, more or less, to a point; thence,
570. Bearing S 07° 30' 10" E for a distance of 28.75 feet, more or less, to a point; thence,
571. Bearing S 01° 20' 02" W for a distance of 32.26 feet, more or less, to a point; thence,
572. Bearing S 04° 31' 03" E for a distance of 28.59 feet, more or less, to a point; thence,
573. Bearing S 04° 45' 59" W for a distance of 18.06 feet, more or less, to a point; thence,
574. Bearing S 70° 55' 22" W for a distance of 20.65 feet, more or less, to a point; thence,
575. Bearing N 67° 54' 25" W for a distance of 25.93 feet, more or less, to a point; thence,

576. Bearing N 51° 43' 52" W for a distance of 18.17 feet, more or less, to a point; thence,
577. Bearing N 29° 04' 31" W for a distance of 15.45 feet, more or less, to a point; thence,
578. Bearing N 17° 15' 14" W for a distance of 22.78 feet, more or less, to a point; thence,
579. Bearing N 12° 32' 20" W for a distance of 20.75 feet, more or less, to a point; thence,
580. Bearing N 15° 26' 17" W for a distance of 22.57 feet, more or less, to a point; thence,
581. Bearing N 11° 41' 42" W for a distance of 22.21 feet, more or less, to a point; thence,
582. Bearing N 19° 40' 14" W for a distance of 22.30 feet, more or less, to a point; thence,
583. Bearing N 13° 08' 30" W for a distance of 23.11 feet, more or less, to a point; thence,
584. Bearing N 18° 59' 09" W for a distance of 25.38 feet, more or less, to a point; thence,
585. Bearing N 19° 59' 49" W for a distance of 17.56 feet, more or less, to a point; thence,
586. Bearing N 22° 11' 01" W for a distance of 21.87 feet, more or less, to a point; thence,
587. Bearing N 24° 55' 14" W for a distance of 23.16 feet, more or less, to a point; thence,
588. Bearing N 42° 54' 09" W for a distance of 14.34 feet, more or less, to a point; thence,
589. Bearing N 67° 50' 56" W for a distance of 21.88 feet, more or less, to a point; thence,
590. Bearing N 74° 04' 06" W for a distance of 21.86 feet, more or less, to a point; thence,
591. Bearing N 85° 31' 10" W for a distance of 38.40 feet, more or less, to a point; thence,
592. Bearing S 78° 28' 32" W for a distance of 37.54 feet, more or less, to a point; thence,
593. Bearing S 84° 23' 11" W for a distance of 46.01 feet, more or less, to a point; thence,
594. Bearing N 86° 48' 48" W for a distance of 17.75 feet, more or less, to a point; thence,
595. Bearing N 90° 00' 00" W for a distance of 40.54 feet, more or less, to a point; thence,
596. Bearing N 88° 31' 57" W for a distance of 29.29 feet, more or less, to a point; thence,
597. Bearing S 85° 42' 53" W for a distance of 30.11 feet, more or less, to a point; thence,
598. Bearing S 71° 07' 41" W for a distance of 30.15 feet, more or less, to a point; thence,
599. Bearing S 62° 48' 09" W for a distance of 29.54 feet, more or less, to a point; thence,
600. Bearing S 61° 05' 34" W for a distance of 32.59 feet, more or less, to a point; thence,
601. Bearing S 64° 33' 17" W for a distance of 34.91 feet, more or less, to a point; thence,
602. Bearing S 53° 38' 16" W for a distance of 35.42 feet, more or less, to a point; thence,
603. Bearing S 51° 51' 53" W for a distance of 26.72 feet, more or less, to a point; thence,
604. Bearing S 43° 10' 32" W for a distance of 32.91 feet, more or less, to a point; thence,
605. Bearing S 56° 19' 52" W for a distance of 35.18 feet, more or less, to a point; thence,
606. Bearing S 55° 23' 52" W for a distance of 38.30 feet, more or less, to a point; thence,
607. Bearing S 52° 08' 49" W for a distance of 34.23 feet, more or less, to a point; thence,
608. Bearing S 41° 12' 29" W for a distance of 31.91 feet, more or less, to a point; thence,
609. Bearing S 49° 44' 40" W for a distance of 69.36 feet, more or less, to a point; thence,
610. Bearing S 61° 39' 01" W for a distance of 42.65 feet, more or less, to a point; thence,
611. Bearing S 51° 34' 04" W for a distance of 32.58 feet, more or less, to a point; thence,
612. Bearing S 44° 08' 34" W for a distance of 34.49 feet, more or less, to a point; thence,
613. Bearing S 30° 35' 57" W for a distance of 38.34 feet, more or less, to a point; thence,
614. Bearing S 30° 45' 21" W for a distance of 32.30 feet, more or less, to a point; thence,
615. Bearing S 35° 46' 29" W for a distance of 23.11 feet, more or less, to a point; thence,
616. Bearing S 46° 08' 47" W for a distance of 27.07 feet, more or less, to a point; thence,
617. Bearing S 43° 25' 56" W for a distance of 38.22 feet, more or less, to a point; thence,
618. Bearing S 32° 38' 22" W for a distance of 22.27 feet, more or less, to a point; thence,
619. Bearing S 32° 29' 35" W for a distance of 29.35 feet, more or less, to a point; thence,
620. Bearing S 42° 54' 09" W for a distance of 28.67 feet, more or less, to a point; thence,
621. Bearing S 46° 08' 43" W for a distance of 27.07 feet, more or less, to a point; thence,

622. Bearing S 44° 29' 38" W for a distance of 34.67 feet, more or less, to a point; thence,
623. Bearing S 48° 50' 15" W for a distance of 23.93 feet, more or less, to a point; thence,
624. Bearing S 58° 24' 46" W for a distance of 22.91 feet, more or less, to a point; thence,
625. Bearing S 43° 41' 23" W for a distance of 22.82 feet, more or less, to a point; thence,
626. Bearing S 19° 33' 08" W for a distance of 24.67 feet, more or less, to a point; thence,
627. Bearing S 03° 45' 11" W for a distance of 45.85 feet, more or less, to a point; thence,
628. Bearing S 08° 53' 09" E for a distance of 48.59 feet, more or less, to a point; thence,
629. Bearing S 20° 14' 24" E for a distance of 45.57 feet, more or less, to a point; thence,
630. Bearing S 33° 21' 46" E for a distance of 34.13 feet, more or less, to a point; thence,
631. Bearing S 66° 49' 11" E for a distance of 34.30 feet, more or less, to a point; thence,
632. Bearing S 47° 50' 07" E for a distance of 32.41 feet, more or less, to a point; thence,
633. Bearing S 52° 43' 12" E for a distance of 39.63 feet, more or less, to a point; thence,
634. Bearing S 42° 12' 21" E for a distance of 32.40 feet, more or less, to a point; thence,
635. Bearing S 22° 51' 01" E for a distance of 30.93 feet, more or less, to a point; thence,
636. Bearing S 10° 18' 48" E for a distance of 25.16 feet, more or less, to a point; thence,
637. Bearing S 04° 03' 32" W for a distance of 52.50 feet, more or less, to a point; thence,
638. Bearing S 13° 00' 17" W for a distance of 30.02 feet, more or less, to a point; thence,
639. Bearing S 04° 24' 08" W for a distance of 29.34 feet, more or less, to a point; thence,
640. Bearing S 00° 00' 00" E for a distance of 33.75 feet, more or less, to a point; thence,
641. Bearing S 00° 00' 00" W for a distance of 30.00 feet, more or less, to a point; thence,
642. Bearing S 00° 00' 00" W for a distance of 18.75 feet, more or less, to a point; thence,
643. Bearing S 07° 16' 49" W for a distance of 15.68 feet, more or less, to a point; thence,
644. Bearing S 07° 16' 51" W for a distance of 19.86 feet, more or less, to a point; thence,
645. Bearing S 88° 36' 03" W for a distance of 142.48 feet, more or less, to a point; thence,
646. Bearing S 02° 02' 51" E for a distance of 27.62 feet, more or less, to a point; thence,
647. Bearing S 87° 50' 26" W for a distance of 52.33 feet, more or less, to a point; thence,
648. Bearing N 79° 45' 42" W for a distance of 4.25 feet, more or less, to a point; thence,
649. Bearing N 69° 54' 00" W for a distance of 4.25 feet, more or less, to a point; thence,
650. Bearing N 60° 02' 18" W for a distance of 4.25 feet, more or less, to a point; thence,
651. Bearing N 50° 10' 36" W for a distance of 4.25 feet, more or less, to a point; thence,
652. Bearing N 40° 18' 54" W for a distance of 4.25 feet, more or less, to a point; thence,
653. Bearing N 30° 27' 12" W for a distance of 4.25 feet, more or less, to a point; thence,
654. Bearing N 20° 35' 30" W for a distance of 4.25 feet, more or less, to a point; thence,
655. Bearing N 10° 43' 48" W for a distance of 4.25 feet, more or less, to a point; thence,
656. Bearing N 00° 52' 06" W for a distance of 4.25 feet, more or less, to a point; thence,
657. Bearing N 08° 59' 36" E for a distance of 4.25 feet, more or less, to a point; thence,
658. Bearing N 01° 44' 45" W for a distance of 25.03 feet, more or less, to a point; thence,
659. Bearing N 89° 15' 39" W for a distance of 241.27 feet, more or less, to a point; thence,
660. Bearing S 00° 00' 00" W for a distance of 78.87 feet, more or less, to a point; thence,
661. Bearing S 88° 17' 48" W for a distance of 174.57 feet, more or less, to a point; thence,
662. Bearing S 88° 27' 21" W for a distance of 38.44 feet, more or less, to a point; thence,
663. Bearing N 87° 08' 28" W for a distance of 62.39 feet, more or less, to a point; thence,
664. Bearing N 87° 21' 36" W for a distance of 67.58 feet, more or less, to a point; thence,
665. Bearing S 88° 40' 09" W for a distance of 89.35 feet, more or less, to a point; thence,
666. Bearing S 87° 05' 27" W for a distance of 61.36 feet, more or less, to a point; thence,
667. Bearing S 87° 59' 33" W for a distance of 59.24 feet, more or less, to a point; thence,

- 668. Bearing S 88° 11' 32" W for a distance of 98.72 feet, more or less, to a point; thence,
- 669. Bearing N 88° 25' 59" W for a distance of 78.19 feet, more or less, to a point; thence,
- 670. Bearing N 89° 21' 24" W for a distance of 63.67 feet, more or less, to a point; thence,
- 671. Bearing S 88° 44' 30" W for a distance of 32.56 feet, more or less, to a point; thence,
- 672. Bearing S 88° 41' 02" W for a distance of 31.13 feet, more or less, to a point; thence,
- 673. Bearing S 81° 19' 16" W for a distance of 26.05 feet, more or less, to a point; thence,
- 674. Bearing S 79° 25' 35" W for a distance of 33.11 feet, more or less, to a point; thence,
- 675. Bearing S 81° 18' 42" W for a distance of 30.76 feet, more or less, to a point; thence,
- 676. Bearing S 75° 41' 51" W for a distance of 22.91 feet, more or less, to a point; thence,
- 677. Bearing S 43° 49' 44" W for a distance of 14.94 feet, more or less, to a point; thence,
- 678. Bearing S 45° 56' 00" W for a distance of 15.93 feet, more or less, to a point; thence,
- 679. Bearing S 47° 36' 52" W for a distance of 25.39 feet, more or less, to a point; thence,
- 680. Bearing S 40° 56' 17" W for a distance of 41.35 feet, more or less, to a point; thence,
- 681. Bearing S 60° 57' 52" W for a distance of 42.90 feet, more or less, to a point; thence,
- 682. Bearing S 70° 49' 42" W for a distance of 33.89 feet, more or less, to a point; thence,
- 683. Bearing S 01° 38' 32" E for a distance of 68.78 feet, more or less, to a point; thence,
- 684. Bearing S 00° 36' 37" E for a distance of 2552.09 feet, more or less, to a point; thence,
- 685. Bearing S 89° 12' 08" W for a distance of 2592.23 feet, more or less, to a point; thence,
- 686. Bearing N 79° 50' 10" W for a distance of 156.73 feet, more or less, to a point; thence,
- 687. Bearing S 89° 30' 26" W for a distance of 684.49 feet, more or less, to a point; thence,
- 688. Bearing S 89° 20' 11" W for a distance of 655.20 feet, more or less, to a point; thence,
- 689. Bearing S 89° 23' 45" W for a distance of 564.10 feet, more or less, to a point; thence,
- 690. Bearing S 89° 28' 56" W for a distance of 825.40 feet, more or less, to a point; thence,
- 691. Bearing N 00° 28' 08" W for a distance of 1016.77 feet, more or less, to a point; thence,
- 692. Bearing N 00° 29' 39" W for a distance of 1732.19 feet, more or less, to a point; thence,
- 693. Bearing N 87° 28' 30" W for a distance of 63.62 feet, more or less, to a point; thence,
- 694. Bearing N 00° 29' 59" E for a distance of 886.56 feet, more or less, to a point; thence,
- 695. Bearing N 00° 24' 38" E for a distance of 401.15 feet, more or less, to a point; thence,
- 696. Bearing N 00° 15' 39" E for a distance of 101.31 feet, more or less, to a point; thence,
- 697. Bearing N 00° 15' 39" E for a distance of 702.78 feet, more or less, to a point; thence,
- 698. Bearing N 00° 11' 08" W for a distance of 117.69 feet, more or less, to a point; thence,
- 699. Bearing N 00° 11' 08" W for a distance of 502.58 feet, more or less, to a point; thence,
- 700. Bearing N 89° 28' 57" E for a distance of 280.85 feet, more or less, to a point; thence,
- 701. Bearing N 89° 28' 57" E for a distance of 265.50 feet, more or less, to a point; thence,
- 702. Bearing N 00° 00' 00" E for a distance of 621.29 feet, more or less, to a point; thence,
- 703. Bearing S 89° 36' 26" E for a distance of 1058.36 feet, more or less, to a point; thence,
- 704. Bearing N 00° 49' 51" W for a distance of 221.55 feet, more or less, to a point; thence,
- 705. Bearing N 00° 49' 45" W for a distance of 477.01 feet, more or less, to a point; thence,
- 706. Bearing S 89° 11' 36" W for a distance of 228.16 feet, more or less, to a point; thence,
- 707. Bearing N 00° 47' 45" W for a distance of 1016.72 feet, more or less, to a point; thence,
- 708. Bearing N 89° 02' 45" E for a distance of 192.82 feet, more or less, to a point; thence,
- 709. Bearing N 00° 53' 10" W for a distance of 563.72 feet, more or less, to the Point of Beginning.

Lima Water District No. 5, as described above, contains approximately 4,705.59 acres of land.

All as shown on a map prepared by CPL, entitled “Town of Lima Proposed Water District No. 5”, dated November 26, 2024.

WHEREAS, the real properties that will be located in the district are set forth below:

<u>Tax Map Id</u>	<u>Property Address</u>		
		48.-1-2.112	Doran Rd
46.-1-22.11	Livonia Center Rd	27.-2-25	7619 Corby Rd
46.-1-32.1	Poplar Hill Rd	36.-2-44	2244 Poplar Hill Rd
46.-1-35	Cleary Rd	36.-2-52	6661 West Main Rd
46.-1-4.11	2266 Poplar Hill Rd	36.-2-57.111	Heath Markham Rd
46.-1-56	Livonia Center Rd	46.-1-17.3	Jenks Rd
56.-1-6.1	2679 Poplar Hill Rd	46.-1-22.21	2537 Livonia Center Rd
26.-2-13.11	Egan Rd	<u>Tax Map Id</u>	<u>Property Address</u>
26.-2-7.1	Heath Markham Rd	46.-1-22.22	Livonia Center Rd
27.-3-9.111	Dalton Rd	46.-1-27.6	2573 Poplar Hill Rd
26.-2-12.11	Dalton Rd	46.-1-27.7	2583 Poplar Hill Rd
26.-2-14.1	Dalton Rd	46.-1-30.111	Poplar Hill Rd
48.-1-40	Pond Rd	56.-1-22.118	Poplar Hill Rd
38.-1-11.111	Doran Rd	56.-1-26.1	2798 Poplar Hill Rd
38.-1-15.21	Doran Rd	56.-1-71.1	Woodruff Rd
38.-1-14.114	East Main Rd	26.-2-16.114	Egan Rd
58.-1-5.1	Pond Rd	27.-2-26.114	Corby Rd
58.-1-11.11	Doran Rd	58.-1-9.2	Doran Rd
37.-1-19.193	East Main Rd	37.-1-24.124	Doran Rd
38.-1-10.115	Gleason Rd	48.-1-19.11	2611 Doran Rd
58.-1-3.2	Doran Rd	48.-1-7.118	Doran Rd
38.-1-10.116	Gleason Rd	48.-1-3.211	2283 Doran Rd

38.-1-11.112	Doran Rd	46.-1-27.12	2570 Poplar Hill Rd
58.-1-4.11	Pond Rd	46.-1-27.13	2580 Poplar Hill Rd
48.-1-24.4	Doran Rd	46.-1-27.14	2600 Poplar Hill Rd
37.-1-24.125	2128 Doran Rd	46.-1-27.212	6680 Jenks Rd
58.-1-3.1	Doran Rd	46.-1-27.214	6658 Jenks Rd
26.-2-19	6909 Egan Road	46.-1-27.221	6670 Jenks Rd
36.-2-39	2097 Poplar Hill Rd	46.-1-27.3	6648 Jenks Rd
36.-2-40	2120 Poplar Hill Rd	46.-1-27.4	6652 Jenks Rd
36.-2-41	2112 Poplar Hill Rd	46.-1-27.5	2563 Poplar Hill Rd
36.-2-42	2095 Poplar Hill Rd	46.-1-28	2654 Poplar Hill Rd
36.-2-43	2109 Poplar Hill Rd	46.-1-29.21	2670 Poplar Hill Rd
36.-2-53	1883 Heath Markham Rd	46.-1-29.311	2632 Poplar Hill Rd
36.-2-54	1881 Heath Markham Rd	46.-1-29.32	2622 Poplar Hill Rd
36.-2-56.121	1863 Heath Markham Rd	46.-1-30.112	2643 Poplar Hill Rd
<u>Tax Map Id</u>	<u>Property Address</u>	46.-1-32.2	2400 Poplar Hill Rd
36.-2-56.2	1869 Heath Markham Rd	46.-1-32.3	2428 Poplar Hill Rd
36.-2-56.3	1877 Heath Markham Rd	46.-1-33	2378 Poplar Hill Rd
36.-2-57.13	1860 Heath Markham Rd	46.-1-34	2374 Poplar Hill Rd
36.-2-57.141	6659 West Main Rd	<u>Tax Map Id</u>	<u>Property Address</u>
36.-2-67.1	1882 Heath Markham Rd	46.-1-4.2	2245 Poplar Hill Rd
46.-1-22.12	2532 Livonia Center Rd	56.-1-22.115	2932 Poplar Hill Rd
46.-1-24	6679 Jenks Rd	56.-1-22.121	2963 Poplar Hill Rd
46.-1-25	2535 Poplar Hill Rd	56.-1-22.2	2972 Poplar Hill Rd
46.-1-26	6642 Jenks Rd	56.-1-23	6570 Woodruff Rd
46.-1-27.11	2550 Poplar Hill Rd	56.-1-24	6540 Woodruff Rd

56.-1-25	6577 Woodruff Rd	26.-2-13.21	6933 Egan Rd
56.-1-27	2924 Poplar Hill Rd	27.-3-36	1367 Dalton Rd
56.-1-4.21	2716 Poplar Hill Rd	26.-2-11	1370 Dalton Rd
56.-1-5	2675 Poplar Hill Rd	27.-3-35	1361 Dalton Rd
56.-1-6.2	2713 Poplar Hill Rd	26.-2-10	1344 Dalton Rd
56.-1-65.1	2790 Poplar Hill Rd	27.-3-37	1355 Dalton Rd
56.-1-66.2	2720 Poplar Hill Rd	27.-3-38	1349 Dalton Rd
46.-1-27.8	2603 Poplar Hill Rd	27.-3-39	1343 Dalton Rd
36.-2-72.111	1930 Poplar Hill Rd	26.-2-9	1340 Dalton Rd
46.-1-20.11	6790 Jenks Rd	27.-3-40	1331 Dalton Rd
46.-1-31	2504 Poplar Hill Rd	26.-2-8	1330 Dalton Rd
27.-3-52	1291 Dalton Rd	27.-3-41	1329 Dalton Rd
27.-3-42.32	1281 Dalton Rd	27.-3-42.1	1325 Dalton Rd
27.-3-42.4	7124 Heath Markham Rd	27.-3-53	1315 Dalton Rd
27.-3-29.1	7108 Gale Rd	27.-3-42.5	7130 Heath Markham Rd
27.-3-30	7105 Gale Rd	27.-3-42.21	7160 Heath Markham Rd
26.-2-15.1	6920 Egan Rd	27.-3-42.33	7111 Heath Markham Rd
27.-3-51.3	1469 Dalton Rd	27.-3-42.22	7200 Heath Markham Rd
27.-3-51.2	1465 Dalton Rd	27.-3-42.31	1227 Dalton Rd
26.-2-13.22	6931 Egan Rd	27.-3-43	7131 Heath Markham Rd
26.-2-13.12	6975 Egan Rd	27.-3-44	1207 Dalton Rd
26.-2-18	6913 Egan Rd	27.-3-45.1	1197 Dalton Rd
<u>Tax Map Id</u>	<u>Property Address</u>	27.-3-47	7227 Heath Markham Rd
26.-2-17	6923 Egan Rd	27.-3-48	7237 Heath Markham Rd
26.-2-30	1468 Dalton Rd	26.-2-6	1168 Dalton Rd

27.-3-9.112	1149 Dalton Rd	58.-1-11.2	2824 Doran Rd
<u>Tax Map Id</u>	<u>Property Address</u>	58.-1-6.2	2776 Pond Rd
26.-2-5.1	1148 Dalton Rd	58.-1-11.3	2804 Doran Rd
26.-2-5.2	1150 Dalton Rd	58.-1-10.21	2954 Doran Rd
26.-2-12.12	1403 Dalton Rd	58.-1-11.41	2780 Doran Rd
27.-3-46.111	7165 Heath Markham Rd	<u>Tax Map Id</u>	<u>Property Address</u>
27.-3-46.13	7207 Heath Markham Rd	58.-1-2.1	2760 Doran Rd
26.-2-14.2	1479 Dalton Rd	58.-1-4.2	2680 Pond Rd
27.-2-26.113	7637 Corby Rd	58.-1-16	2689 Doran Rd
27.-2-18	7710 Corby Rd	58.-1-4.12	2700 Pond Rd
27.-2-19	7700 Corby Rd	48.-1-26.4	2630 Doran Rd
27.-2-20.2	7650 Corby Rd	48.-1-26.3	2626 Doran Rd
27.-2-22	7630 Corby Rd	48.-1-22.2	2620 Doran Rd
27.-2-23	7620 Corby Rd	48.-1-19.2	2651 Doran Rd
27.-2-21.1	1240 York St	48.-1-22.121	2610 Doran Rd
27.-2-20.1	1245 York St	48.-1-22.122	2608 Doran Rd
27.-2-26.12	7618 Corby Rd	48.-1-20	2607 Doran Rd
27.-2-26.13	7566 Corby Rd	48.-1-18	2600 Pond Rd
48.-1-15.1	2519 Doran Rd	48.-1-17.2	2605 Pond Rd
48.-1-16.11	2500 Pond Rd	48.-1-19.3	2601 Doran Rd
48.-1-41	2310 Pond Rd	48.-1-19.12	2595 Doran Rd
38.-1-16.12	2243 Pond Rd	48.-1-22.111	7900 Chase Rd
48.-1-2.111	2266 Doran Rd	48.-1-22.114	7980 Chase Rd
48.-1-24.1	2500 Doran Rd	48.-1-16.2	2560 Pond Rd
58.-1-10.122	2934 Doran Rd	48.-1-17.1	2645 Pond Rd

48.-1-16.12	2450 Pond Rd	38.-1-11.12	2085 Doran Rd
48.-1-7.119	2423 Doran Rd	38.-1-12	2045 Doran Rd
48.-1-7.113	2409 Doran Rd	37.-1-24.11	2044 Doran Rd
48.-1-13	2410 Doran Rd	37.-1-23	2020 Doran Rd
48.-1-12	2400 Doran Rd	38.-1-15.22	2009 Doran Rd
48.-1-7.3	2389 Doran Rd	37.-1-22	2010 Doran Rd
48.-1-38.1	2370 Doran Rd	37.-1-21	2000 Doran Rd
48.-1-38.2	2366 Doran Rd	37.-1-20	1890 Doran Rd
48.-1-7.22	2369 Doran Rd	37.-1-19.11	1886 Doran Rd
<u>Tax Map Id</u>	<u>Property Address</u>	37.-1-19.12	1880 Doran Rd
48.-1-7.213	2401 Doran Rd	38.-1-15.1	1987 Doran Rd
48.-1-8.1	2355 Doran Rd	37.-1-19.13	1872 Doran Rd
48.-1-9	2282 Doran Rd	37.-1-19.14	1860 Doran Rd
48.-1-3.22	2275 Doran Rd	<u>Tax Map Id</u>	<u>Property Address</u>
48.-1-10.11	2360 Doran Rd	37.-1-19.15	1854 Doran Rd
48.-1-10.2	2270 Doran Rd	37.-1-19.16	1848 Doran Rd
48.-1-3.23	2269 Doran Rd	38.-1-14.112	1845 Doran Rd
48.-1-3.24	2267 Doran Rd	37.-1-19.171	1842 Doran Rd
48.-1-3.1	7980 Gleason Rd	38.-1-14.12	1843 Doran Rd
48.-1-2.2	2130 Doran Rd	37.-1-58.1	1830 Doran Rd
38.-1-10.2	8059 Gleason Rd	37.-1-17.1	1820 Doran Rd
37.-1-24.122	2126 Doran Rd	38.-1-14.2	1823 Doran Rd
38.-1-11.2	2125 Doran Rd	58.-1-5.2	2695 Pond Rd
37.-1-24.123	2096 Doran Rd	48.-1-4	8052 Gleason Rd
37.-1-24.2	2090 Doran Rd	48.-1-3.261	8042 Gleason Rd

38.-1-10.114	8067 Gleason Rd
48.-1-39	2375 Pond Rd
48.-1-22.117	2562 Doran Rd
58.-1-9.1	2803 Doran Rd
27.-2-26.3	7526 Corby Rd
27.-2-16	1279 York St
27.-2-17	1275 York St
27.-2-26.14	7556 Corby Rd
27.-2-28.1	1278 York St
27.-2-29	1290 York St
27.-2-24.1	7553 Corby Rd
58.-1-7.1	Doran Rd
56.-1-4.1	2714 Poplar Hill Rd

NOW THEREFORE BE IT ORDERED and RESOLVED, that the Map, Plan and Report for the Town of Lima Water District No. 5 as prepared by Clark Patterson Lee last dated January, 2025, is hereby acknowledged as received by the Lima Town Board, accepted by Resolution dated January 7, 2025 and has been filed in the Lima Town Clerk's Office on January 7, 2025; and be it further

RESOLVED, that pursuant to New York State Town Law, a public hearing be held on the 11th day of February, 2025 at 6:30 p.m. at the Lima Town Hall at 7329 East Main Street, Lima, New York, with respect to the formation of the Town of Lima Water District No. 5, to include the property noted and as more particularly described in the Map, Plan and Report for such proposed district, as filed in the Lima Town Clerk's Office; and be it further

RESOLVED, that the Map, Plan and Report calls for the installation of approximately 86,810 linear feet of 8-inch and 12-inch water main, fire hydrants, gate valves and water services. The water main will be installed along portions of Poplar Hill Road, Woodruff Road, Briggs Road, Doran Road, Jenks Road, Chase Road, Pond Road, Gleason Road, York Street, Corby Road, Dalton Road, Heath Markham Road and Egan Road and will provide water supply to approximately 201 residential and commercial properties. There are an additional 47 properties that will not be provided with service, as they are vacant; and be it further

RESOLVED, that the maximum amount proposed to be expended for the improvements above is \$15,260,000.00, of which \$5,951,400.00 is anticipated to come from a USDA-Rural Development grant, \$5,000,000.00 is anticipated to come from a NYS EFC WIIA grant and \$4,308,600.00 will be financed through a low interest USDA-Rural Development loan; and be it further

RESOLVED, that the anticipated cost to the typical property located within the Town of Lima Water District No. 5 is estimated to be **\$1,076.00**; and be it further

RESOLVED, that the estimated one-time costs for hook-up fees are \$3,750.00 for the typical property, including installation of a service line at the costs of approximately \$30.00 per linear foot (\$3,000.00 average), \$250.00 LCWSA permitting/inspection fee and \$500.00 for well isolation and interior plumbing modifications; and be it further

RESOLVED, that a copy of the Map, Plan and Report describing the proposed district formation and the improvements to be constructed therein shall be available for the public inspection at the Lima Town Clerk's Office; and be it further

RESOLVED, that at the time and date aforementioned, all interested parties may be heard concerning the formation of the proposed Town of Lima Water District No. 5.

The question of the adoption of the foregoing Resolution was duly submitted for approval by vote of the Lima Town Board on Thursday, January 9, 2025, recorded as follows:

VOTE OF THE BOARD:

The vote duly taken resulted as follows:

Michael J. Falk, Supervisor	Aye
Mark Petroski, Deputy Supervisor	Aye
Bill Carey	Aye

Steve Werner

Aye

Ron Blodgett

Aye

This is to certify that I, the undersigned, Clerk of the Town Board of the Town of Lima, Livingston Count, New York, was duly adopted by the Town Board of said Town on the date above, and that the same is a true and correct transcript of said resolution.

In witness where of I have hereunto set my hand and the official seal of the Town Clerk this 9th day of January, 2025.

Jennifer A. Heim – CMC, RMC - Town Clerk